

मुख्य कार्यालय - साकेत भवन, आई.टी.आई. चौक, कोरबा (छ.ग.)

मु.का. दूरभाष : 221288, 222672, फैक्स : 07759-221929, पो. बॉक्स नं.-12 पिन कोड - 495677

Website: www.korbamunicipal.in, Email: kosabadizone3@gmail.com

फा.क. / 483 / निर्माण / 2019

कोरबा, दिनांक 26.08.2019

सिस्टम निविदा क 54612 द्वितीय ई-निविदा आमंत्रण सूचना

नगर पालिक निगम कोरबा द्वारा शासकीय अर्द्धशासकीय विभागों में कार्यरत व्यवसाय से संबंधित अधिकृत विकेता/फर्मो/प्रदायकताओं से (निविदा खुलने के दिनांक तक समस्त संशोधनों के साथ) शेड्युल अनुसार आयटम दरों पर निविदाएं आमंत्रित की जाती है :--

क	कार्य का नाम	प्राक्कलन राशि में	कार्यावधि	अमानत राशि	निविदा खुलने की तिथि
1.	वार्ड क 24 में जिम सामग्री प्रदाय एवं स्थापना का कार्य	7,00,000/-	02 माह	5,500/-	12:09:2019 से

शर्ते :-

- निविदा फॉम बी में आमंत्रित की जा रही है।
- निविदाकार द्वारा वैध ट्रेड लाईसेंस (गुमास्ता लाइसेंस) का होना अनिवार्य हैं।
- निविदाकार द्वारा आपूर्ति किये जाने वाले सामग्री के निर्माता/कंपनी/फर्म द्वारा अधिकृत विकेता/डीलरशीप प्रमाण पत्र प्रस्तुत करना होगा।
- 4. निविदाकार द्वारा जिस निर्माता कंपनी के आइटम प्रदान करने हेतु दर प्रस्तुत की जा रही है उन्हें उस कंपनी का आई एस ओ. सर्टिफिकेट संलग्न करना अनिवार्य होगा अन्यथा निविदाकार इस निविदा के लिए अपात्र होगा।
- 5. निविदाकार आपूर्ति किये जाने वाले प्रत्येक जिम सामग्रियों की कंपनी का आइटम कैटलॉग जिसमें उस सामग्री की समस्त तकनीकी जानकारी स्पष्ट रूप से विनिर्दिष्ट हो प्रस्तुत किया जाना अनिवार्य होगा।
- 6. निविदाकार को आपूर्ति किये जाने वाली सामग्री से सम्बंधित यथा निविदा आमंत्रण पत्र के कंडिका कंमांक कमशः 2,3,4 एवं 5 में उल्लेख अनुसार समानता होना अनिवार्य है अर्थात जिस आपूर्ति किये जाने वाले सामग्री के निर्माणकर्ता / कंपनी / फर्म द्वारा जारी अधिकृत विकेता / डीलरशील प्रमाण पत्र, आइटम कैटलॉम एवं आई.एस.ओ होना अनिवार्य है।
- 7. निविदाकार के पास अधिकृत विकेता/डीलरशीप फर्म कंपनी में उत्पादों का पूर्व में किसी शासकीय संस्था में प्रदाय किये जाने संबंधी कार्यादेश प्रमाण पत्र एवं अनुभव प्रमाण पत्र प्रस्तुत करना होगा साथ ही यह भी सुनिश्चित करना होगा की उपरोक्त प्रमाण पत्र कार्यपालन अभियंता अथवा प्रवर श्रेणी के अधिकारी द्वारा जारी किया गया हो प्रस्तुत करना अनिवार्य होगा।
- निविदा अहस्तांतरणीय होगा एवं सशर्त निविदाओं पर विचार नही किया जावेगा।
- 9. निविदा के संबंध में किसी प्रकार की विवाद होने की स्थिति में आयुक्त का निर्णय अंतिम एवं सर्वमान्य होगा।
- 10. निविदा स्वीकृत करने अथवा अस्वीकृत करने का अधिकार नगर पालिक निगम के पास सुरक्षित रहेगा।

कार्यपालन अभियन्ता नगर पालिक निगम कोरबा (छत्तीसगढ)

Date-Time Detail(s)

Seq.	Nagar Nigam Stage	Contractor Stage	Start		Expiry		Remarks
No.		oonauotor oaago	Date	Time	Date	Time	
1	Release Tender		26.08.19	10.30	26.08.19	10.30	Release Tender
2		Bid Submission	26.08.19	10.30	11.09.19	17.30	
3	Tender Open		12.09.19	10.30	-		

EXECUTIVE ENGINEER
KORBA (CG)
For, Commissioner Korba (C.G.)

OFFICE OF THE MUNICIPAL CORPORATION, KORBA (C.G.)

Supply & Fixing of Gym Equipment at ... Ward No (29)

1	Make - 1) Aerofit 2) Star Trac 3) York with Equivalent Item Description					
1			Unit	Qty.	Rate	
-	Specifications:-	-				
	Dimensions - 1277 (1)	-	Nos.	1		1
	Dimensions: 125" (L) x 118" (W) x 80" (H)	-				1
	rame structures : Combination of high to "					1
	welded, factory assembled weight frame.	ous				T
	Ivalle of tube : Square tubing	-				
	Tube Size : 50 mm x 50 mm.	-				T
	Tube Gauge: 2.5 mm.	-	-			
	Weight Stack : $200 \times 2 = 400$ lbs and $150 \times 2 = 300$ lbs, total weight stack -700 lbs.	10	-			
	Weight Stack	IS				
	Weight Plate: Cast iron, machine drilled to exact spec and employ oversized nylon bushings for Super smooth					
	oversized nylon bushings for Super-smooth operations Weight Guide Rods: 25 mm chrome plated solid stool blood					
	Rods: 25 mm chrome plated solid steel, highly policed for smooth movements.					
	movements.				-	
	Weight Selector Pin: 10 mm steel pin.					
	Adjustments: Adjustable of seats, back					-
	requirements.					_
-	Pull Pins: Most adjustment secured with commercial grade spring loaded pull-pins.					
-	pull-pins.	3				-
1	Cable : 5.0 mm dia., 4200 lbs rated, commercial grade, nylon coated aircraft cables.					
F	Pulley: Maintenance from the		-			
P	Pulley: Maintenance free, fiber glass reinforced nylon pulleys fitted with premium grade -A quality roller bearings with V grooved channel.					
G	Pulley Sizes : 88 mm. Grips : High density foam rubber bearings with V grooved channel.					
G	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density for					
G G Fi	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam.					
G G Fi	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. inishing: Proprietary two coat powder process. ust Proof: All frame structures electrons.					
G C Fi Ru er	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. inishing: Proprietary two coat powder process. ust Proof: All frame structures electro statically powder coated to					
G G Fi Ru er	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. inishing: Proprietary two coat powder process. ust Proof: All frame structures electro statically powder coated to nsure maximum corrosion and chip resistance.					
G G Fi Ru er	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. inishing: Proprietary two coat powder process. ust Proof: All frame structures electro statically powder coated to nsure maximum corrosion and chip resistance.					
Fi Ru er Co	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Grips: High density foam rubber hand grips. Cushioning: Proprietary two coat powder process. Cust Proof: All frame structures electro statically powder coated to process. Insure maximum corrosion and chip resistance. Culti Bench Commercial	Nos.				
Fi Ru er Co Mi	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Inishing: Proprietary two coat powder process. ust Proof: All frame structures electro statically powder coated to ensure maximum corrosion and chip resistance. Jolor: Grey. Julti Bench Commercial	Nos.	1			
Fi Ru er Co Mi Sp	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Inishing: Proprietary two coat powder process. Cust Proof: All frame structures electro statically powder coated to ensure maximum corrosion and chip resistance. Customary in the proprietary two coates and the process of	Nos.	1			
Fi Ru er Co Mo Sp Shi	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. inishing: Proprietary two coat powder process. ust Proof: All frame structures electro statically powder coated to nsure maximum corrosion and chip resistance. olor: Grey. lulti Bench Commercial Decifications:- ip Weight: 304 lbs (138 Kg) eight: 74" (188 cm)	Nos.	1			
P G G C C Fill Rule er C C C Mill Spp Shi We Ler	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Jarips: High density foam rubber hand grips. Cushioning: Proprietary two coat powder process. Just Proof: All frame structures electro statically powder coated to ensure maximum corrosion and chip resistance. Juliti Bench Commercial Decifications:- July Weight: 304 lbs (138 Kg) Jeight: 74" (188 cm) Jungth: 65" (165 cm)	Nos.	1			
PP GG CC File Rule er CC Mile Spp Shi We Ler Hei	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Grips: High density foam rubber hand grips. Cushioning: Proprietary two coat powder process. Sust Proof: All frame structures electro statically powder coated to ensure maximum corrosion and chip resistance. Folior: Grey. Sulti Bench Commercial Decifications:- Sip Weight: 304 lbs (138 Kg) Sight: 74" (188 cm) Sight: 65" (165 cm) Sight: 60" (152 cm)	Nos.	1			
Pi GG CC Fi Ru er CC Mi Spp Shi We Ler Hei	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Inishing: Proprietary two coat powder process. ust Proof: All frame structures electro statically powder coated to insure maximum corrosion and chip resistance. Polor: Grey. Initi Bench Commercial Decifications:- Inip Weight: 304 lbs (138 Kg) Decifications:- Inip Weight: 65" (165 cm) Inight: 60" (152 cm) In Bench Commercial					
Pin GG GC GC Fi Fi Ru err CC GC Mi Spp Shi We Lerr Hei Flair Spp	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Grips: High density foam rubber hand grips. Cushioning: Proprietary two coat powder process. Cust Proof: All frame structures electro statically powder coated to ensure maximum corrosion and chip resistance. Color: Grey. Culti Bench Commercial Decifications:- Cuip Weight: 304 lbs (138 Kg) Eight: 74" (188 cm) Cust Proof: All frame structures electro statically powder coated to electro statically	Nos.	1			
P G G C C F i Ru er C C C M M S S D E S hi p S D E S	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Inishing: Proprietary two coat powder process. Ust Proof: All frame structures electro statically powder coated to insure maximum corrosion and chip resistance. Polor: Grey. Initiations:- Inip Weight: 304 lbs (138 Kg) Initiations:-					
Piant Spe Ship Leng	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Inishing: Proprietary two coat powder process. Ust Proof: All frame structures electro statically powder coated to ensure maximum corrosion and chip resistance. Inipulation Commercial Decifications: Inipulation Commercial Inipulation					
PI GG CC Fi Ru err CC Shi We Lerr Heig Spe Ship Leng Heige Heige Ship Leng Heige Ship Leng Heige Ship Leng Heige Ship Leng Ship Leng Heige Ship Leng Ship Le	Pulley Sizes: 88 mm. Grips: High density foam rubber hand grips. Cushioning: 02" inch high density top grade resilient foam. Inishing: Proprietary two coat powder process. Inishing: Proprietary two coat powder coated to process. Inishing: Proprietary two coat powder process. Inishing: Proprietary two coat powder resilient foam. Inishing: Proprietary two coat powder process. Inishing: Proprietary two coa					
Pictor Pi	Pulley Sizes : 88 mm. Grips : High density foam rubber hand grips. Cushioning : 02" inch high density top grade resilient foam. Grinshing : Proprietary two coat powder process. Ust Proof: All frame structures electro statically powder coated to ensure maximum corrosion and chip resistance. Foliations: Foliatio					

	vimension : 28"(L) x 27"(W) x 58"(H).				
	Motor: 2.0 HP, DC motor				
	Motor Control : Microprocessor control.				
1	Speed: 5 to 30 Hz.				
1	Quick Selection : Auto, Low, Medium & High				
	Set option: 3, 5, 8, and 10 minutes time can be set as per user				
	requirement. Display : Dot Matrix LED, 5 Window display.	-			
	Display Feedback : Time, Speed, Calories and distance.				
	Power Requirements : 220V AC.	1			
	France Francisco Dispulstury two cost powder process				
	Frame : Heavy-Gauge welded steel with textured proprietary two coat				
	electro statically powder process finish to ensure maximum corrosion &				
	chip resistance. Exercise Applications : Straight standing, horse riding,	No.			
	upper arm & body pose. Max User Weight: 120 Kgs.				
5	Multi Functional Trade Mill	Nos.	1		
	Specifications:-	1	-		-
	Foldable Mannual Trademill with stepper & Twister				
	Long handle bard with pulse			-	
	3 Levels adjustable incline.				
	Huge size monitor with 5 window display consist of speed, distance,				
	time, calories & pulse.				
	Running belt size: 48" (L) x 16" (W)				
	Max. User Weight: 100 kgs.			-	
6	Magnetic Uprit + Bike	Nos.	1		
	Technical Specifications:-	1405.	1		
	Dimension: 42"(L) x 24"(W) x 58"(H)				
	Maximum Watt: 300 Watts.				
	Resistance Level : 16 Levels.				
	Resistance System : Electro-magnetic resistance.				
	Power: 6 Volts DC adapter for self powered convenience.		100		
			100		
	Programs: 16 Programs - manual, polling, valley, fat burn, ramp,		20		
	mountain, random, body fat, target HR, 60% HRC, 75% HRC, 85% HRC and user setting 04 Nos.	Hone			
	Drive System : Centre design drive, super silent poly-V belt driven.				
	brive system . Centre design drive, super silent poly-v beit driven.				
	Fly Wheel : 9 Kgs precision balanced.				
_	Pedals: Self balanced extra wide pedals with adjustable straps fit to any				
	size user, close spacing, shock absorbing, air cushion and provides gentle				
	movements				
	Seat: Ergonomically designed comfortable seat with flex cushion 11				
	levels seat adjustment.				
	Handle Bars : U-Bar style with ergonomically elbow support pad and in-				
	built contact heart rate sensor with hand grips.				
	Centre of Gravity : Low COG combined with a balanced frame prevents				- 6
	rocking.				
	Cardio Monitor : In-built hand grip pulse sensor provided with handle				
	grips enables to the cardio monitoring on board.				
	Display : LCD with blue back light and computerized console.				
	Display Feedback : Multi feedback read out instantly displays time,				
	distance, RPM, calories, speed, pulse, watt, BMR and BMI.				
-	Speaker : In-built speaker for ipod and MP3 connectivity.				

	Jser Weight: 120 Kgs.			
۹	Transportation : Transportation wheels for easy movement.			
V	Accessory Holder: Book holder on the upper case of consol and mobile hone holder.			
1	Rating : Commercial.		1	1
	Crank Assembly: 3 Pieces crank assembly.			
	Frame Structure: Extra sturdy and stable steel frame			
	construction/Arched support frame for maximum durability and stability.			
	Frame Finishing: Proprietary two coat powder process.			
	Rust Proof : All frame structures electro statically powder coated to	Nos.		+
	ensure maximum corrosion and chip resistance.			
7	Roming Machine	Nos.	1	1
	Specifications:-			-
	Dimension : 70" (L) x 21" (W) x 17" (H)			-
	Resistance Levels & Type : 10 Levels, magnetic resistance.			-
N	Power: 2 x 1.5 volt AA size battery.	New	1	-
	Display : LCD display.	Non		-
16	Display Feedback : Scan, Time, CPM, count, Calories & Sum.	New		 -
	Transportation : Wheel for Easy transportation, Seat & Grip:			 -
	Ergonomically designed seat and grips. Fly wheel : 5 Kgs Fly wheel.			
	Folding System : Foldable.			-
8	Twister Commercial	Nos.	1	
	Specifications:-	1405.	1	-
	Weight: 55" (140 cm)			
	Length: 72" (183 cm)			
	Height: 36" (92 cm)			
9	Rubber Plat Commercial	len	100	
LO	Rubber Dumbbells	kg	100	
1	Steel Rod (SS) 24mm	kg	100	
12	Motorized Trademill	Fit	20	
	Specifications	Nos.	1	
	Dimension: 80"(L) x 36"(W) x 50"(H).			
	Motor: DC Motor, 3,0 HP continuous, 6.0 HP peak, digital concepts			
	P.W.M. Control.	-		
	Speed: 1.0 to 16 Kmph.			
	Elevation: 0% to 15%, Automatic.			
	Quick Selection: Speed and elevation.			
	Belt Size: 55" (L) x 20" (W).			
	DCTC 512E. 55 (L) X 20 (W).			
	Shock Absorption: 8-Point spring load deck suspension/Anti shock.			
	Safety Key Stop: Magnetic safety key.			
	Display: LCD blue back light, single window display.			
	Display Feedback: Heart rate elevation time display.			
	Display Feedback: Heart rate, elevation, time, distance, speed, calories, body fat and programs.			
$\overline{}$	Programs: 24 Programs, 18 preset, 5 user and 1 body fat.			
	Heart Rate Technology: Heart rate control with hand grip pulse sensor.			

Roston : Commer

	Y				
3	ower Saving Mode: System shutdown display underlO minutes if no		T		
24	instruction input, press any key to restore system. Speaker: In-built				
5	speaker for MP3, iPod connections.				
A. A.	Frame: Heavy-gauge welded steel with textured proprietary two coat				_
1 16	electro statically powder process finish to ensure maximum corrosion				
[a	and chip resistance.		1		
F	Foldable: Smart folding system.				
	tisure hastman corresion and chin resistance.		1	-	
1 T	ransportation: 4 Wheels transportation system for easy movement.				
1	Max User Weight: 135 Kgs.		-		-
13 D	Dumbbells Rack	Nos.	1		-
5	pecifications:-	1403.	-		-
S	hip Weight : 266 lbs (121 Kg)			-	-
	Veight : 29" (74 cm)		-		
L	ength : 205" (267 cm)	-	-	-	
	leight: 37" (94 cm)	-	-		
-	YM Ball (95 CM) Heavy Duty	No.	-		
	oga Mate (6mm) Size - 4"x6"	Nos.	1		
	B Slimmer	Nos.	1		
_	pecifications:-	Nos.	1	-	
	hip Weight : 266 lbs (121 Kg)				
	/eight : 29" (74 cm)				
	ength : 205" (267 cm)				
	eight: 37" (94 cm)				
THE RESERVE OF THE PERSON NAMED IN	ectrical Cross Trainer (Commercial)				
	echnical Specifications:-	Nos.	1		
	mension : 84" (L) x 30"(W) x 71"(H)				
	rides : 20 Inches natural strides.				
	aximum Watt: 250 Watts.				
	esistance Level : 16 Levels.				-
Re	esistance System: Electro-Magnetic resistance.				
Po	ower : Self generated power system.				
Pro	ograms : 06 Programs - Manual, HRC, random, weight loss, CV and hill				
lint	tervals. Drive System: Centre design drive, super silent poly-V belt				1
dri	ven.			-	
Pe	dals : Self balancing, close spacing, enlarge, impact-absorbing, fit to				
an	y size user and provides gentle movements to reduce lower body				
str	ess.				
Cei	ntre of Gravity: Low COG combined with a balanced frame prevents				
roc	cking. Cardio Monitor: In-built metallic pulse sensor provided with T				
par	r style handle grips enables to the cardio monitoring on board.				
Di-				an etra	neer
DIS	play: Dot matrix LED, scrolling text and computerized console.		1911		ation
DIS	play Feedback: Multi feedback read out instantly displays time,			arba (c.C.	
dist	tance, RPM, calories, heart rate, speed, work (resistance) levels, watts,				
and	mets.				
	er Weight: 140 Kgs.				
Tra	nsportation: Transportation wheels for easy movement.				
Acc	essory Holder: Water bottle and mobile phone holder.				
Rat	ing : Commercial.				

.

	tep-up Height: 12 Inches easy step-up height.		T		
	Strides Wheel: Dual wheels track, fiber glass reinforced nylon wheel with high quality bearing.				
1	scability.				-
	Frame Finishing : Proprietary two coat powder process.				
	Rust Proof : All frame structures electro statically powder coated to		1	101	
	ensure maximum corrosion and chip resistance.		STORE		
18	Spin Bike Commercial fit wheel				
	Technical Specification:-	Nos.	1	TO III	
	Dimension: 53"(I_) x 21"(W) x 44"(H).				
	Spin Wheel: 21 Kgs, high inertia spin wheel.				
	Resistance Level: Smart release has been wheel.		Cloker		
	Resistance Level: Smart release breaking system provides safe dependable performance for unsupervised rider.	HERENE W	State 8		
	Resistance System: Push brake system which make the bike safe and stable, two piece fender for comprehensive protection of brake and spin wheel.		Pill I	Tider year	
	Drive System: Centre design drive and metal belt driven.				
	Pedals: Self balanced wide pedals with adjustable straps fit to any size user, close spacing, shock absorbing air cushion and provides gentle movements. Seat: Pop-pin seat slider with 8 steps horizontal and 15 steps vertical adjustments deliver a great fit.		argon a		
	Handle Bars: Chrome with PVC dipping, 9 level vertical and 8 level horizontal adjustments.	A Ser .		21 BR 22	
- '	Centre of Gravity: Low COG combined with a balanced frame prevents rocking. User Weight: 150 Kgs.		72	OF ASSESS	
1	Transportation: Transportation wheels for easy movement.				
1,	Crank Assembly: 3 Pieces crank assembly with increased strength provides dependable performance for every rider.				
F	rame Design: Frame is designed based on human engineering theory which makes more comfortable.			B	
Fe	rame Structure: Strengthened main frame makes it sturdy stable and legant. Frame Finishing: Proprietary two coat powder process	Autien	or Bee	tind nes	a .
IK	sust Proof: All frame structures electro statically powder coated to nsure maximum corrosion and chip resistance.	Tra I	1		

(Rupees Six Lacs Ninety Nine Thousand Nine Hundred Only.)

Sub. Engineer Municipal corporation korba (c.G.)

Assitt Engineer

Municipal corporation

korba (c.G.)

ExecutiveEngineer Municipal corporation korba (c.G.)