

## कार्यालय, नगर पालिक निगम, कोरबा (छ.ग.)

मुख्य कार्यालय - साकेत भवन, आई.टी.आई. चौक, कोरबा (छ.म्.)

दर्री जोन

फा.क्र. / 578, 579, 580 एवं 583 / निर्माण (दर्श जोन) / 2023 /

कोरबा, दिनांक 26.07.2023

## निविदा आमंत्रण की सूचना

लोक निर्माण विभाग से एकीकृत पंजीयन प्रणाली अंतर्गत सक्षम श्रेणी में पंजीकृत ठेकेदारों से निम्नलिखित कार्य हेतु प्रमुख अभियन्ता लोक निर्माण विभाग, रायपुर द्वारा प्रचलित PWD Building SOR 01.01.2015 & PWD Electrical SOR 01.06.2020 से प्रभावशील दर अनुसूची पर (निविदा खुलने के दिनांक तक समस्त संशोधनों के साथ) कम अधिक या समान दरों पर तथा शेड्युल अनुसार आयटम दरों पर निम्नलिखित निर्माण कार्य हेतु मैन्युअल निविदा वेबसाईट से डाउनलोड कर त्रि-लिफाफा पद्धित माध्यम से आमंत्रित की जाती है :-

1. निर्धारित प्रारूप में निविदा प्रपत्र प्राप्त होने की अंतिम तिथि — 10.08.2023 सायंकाल 3:00 बजे तक

2. निविदा खुलने की अंतिम तिथि

- 10.08.2023 सायंकाल 4:30 बजे तक

| क्र |  |             |          |            |         | 025 (1194) |                 | 191 (14)   |
|-----|--|-------------|----------|------------|---------|------------|-----------------|------------|
| *'  | कार्य का नाम   | प्राक्कलन   | धरोहर    | निविदा     | निविदा  | कार्यावधि  | ठेकेदार         | निविदा     |
| .   |  | राशि में    | राशि रू  | प्रपत्र का | प्रपत्र |            | का वर्ग         | खुलने की   |
|     |  |             | में      | मूल्य      | *****   |            | ,               | अंतिम तिथि |
| 1   | वार्ड क्र. ४४ सी.एस.ई.बी. १४<br>ब्लॉक के पास में सामुदायिक<br>भवन निर्माण।<br>(विधायक मद २०२३–२४)<br>(द्वितीय निविदा)                                  | 10,00,000/- | 7,500 /- | 750/-      | Form-A  | 04 माह     | सक्षम<br>श्रेणी | 10.08.2023 |
| 2   | वार्ड क्र. 45 गरमपानी नहर व्ही.<br>आई.पी. रेस्ट हाउस के पास<br>पुलिया के नीचे छठघाट के पास<br>पचरी निर्माण।<br>(विधायक मद 2023–24)<br>(द्वितीय निविदा) | 2,00,000/-  | 2,000 /- | 350/-      | Form-A  | 02 माह     | सक्षम<br>श्रेणी | 10.08.2023 |
| 3   | वार्ड क्र. 46 नवीन स्कूल के<br>पास सामुदायिक भवन निर्माण।<br>(विधायक मद 2023–24)<br>(द्वितीय निविदा)   |             | 7,500 /- | 750/-      | Form-A  | 04 माह     | सक्षम<br>श्रेणी | 10.08.2023 |
| 4   | वार्ड क्र. 55 बल्गी कॉलोनी के<br>गायत्री मंदिर परिसर के पास<br>मंच निर्माण।<br>(प्रभारी मंत्री मद 2023–24)<br>(द्वितीय निविदा)                         | 5,00,000/-  | 5,000 /- | 750/-      | Form-A  | 03 माह     | सक्षम<br>श्रेणी | 10.08.2023 |

निविदा की शर्ते:--

1. निविदा दरे प्रचलित सी.एस.आर.से कम या अधिक प्रतिशत् दरों पर दिया जावे सी.एस.आर.के अंतर्गत के आयटमों पर पृथक से आयटम दरों का उल्लेख करने पर निविदा निरस्त मानी जावेगी।

3. निविदा के दस्तावेज हाथो-हाथ न लिया जाकर रजिस्टर्ड पोस्ट अथवा स्पीड पोस्ट से प्राप्त किया जावेगा। अन्य माध्यमों यथा कोरियर सर्विस, साधारण डाक इत्यादि से प्राप्त अथवा समयावधि के पश्चात् प्राप्त निविदाओं पर विचार नहीं किया जावेगा। निविदा आयुक्त, नगर पालिक निगम, आई.टी.आई. चौक साकेत भवन, जिला-कोरबा (छ.ग.) पिन नं.-495677 के पते पर भेजना होगा। निर्धारित तिथि को साय 3:00 के पश्चात् प्राप्त निविदाएँ स्वीकार नहीं किए जावेंगे।

निविदा प्रपन्न नगर पालिक निगम, कोरबा के वेबसाईट www.korbamunicipal.in/uad.cg.gov.in डाउनलोड किया जाकर नवीन निविदा प्रपत्र Form - A/B/ABC (जारी दिनॉक तक समस्त संशोधनों के साथ) निर्धारित शुल्क की डीडी के साथ संबंधित कार्य का नाम पूर्ण विवरण सहित भरकर भेजना होगा।

निविदा प्रपत्र त्रि-लिफाफा पद्धित से मान्य किया जावेगा जो निम्नानुसार होगा:-

प्रथम लिफाफा में ठेकेदार का जीवित पंजीयन प्रमाण पत्र, आयकर चुकता प्रमाण पत्र, निविदा सूचना आमंत्रण में उल्लेखित अन्य दस्तावेज के साथ निर्धारित प्रपत्र शुल्क का डीडी, निविदाओं में निविदाकार को फिजिकल दस्तावेज के साथ निविदा सूचना जारी होने के पश्चात् दिनांक का शपथ पत्र जिसमें संबंधित कार्य का नाम एवं

कार्य की निविदा क्रमांक अंकित हो प्रेषित करना अनिवार्य होगा एवं अमानत राशि का टी.डी.आर./एफ.डी.आर. जो कि आयुक्त, नगर पालिक निगम कोरबा के नाम पर देय होगा प्रस्तुत करना होगा।

द्वितीय लिफाफा में ठेकेदार द्वारा भरा हुआ निविदा प्रपत्र होगा।

तृतीय लिफाफा में उपरोक्त दोनो लिफाफे होंगे तथा आवश्यकता पड़ने पर मूल अभिलेख प्रस्तुत करना होगा।

5. जिन ठेकेदारों द्वारा नगर पालिक निगम (साडा) के किसी ठेके के कार्य में अनुबंध के अनुरूप कार्य न किया गया हो अथवा नगर पालिक निगम (साडा) के हित के विरूद्ध कार्य किया गया हो उन्हे निविदा भरने की पात्रता नहीं होगी।

6. निविदा हेतु इच्छुक ठेकेदारों को उचित वर्ग में पंजीयन की प्रमाणित प्रतिलिपि यदि साझेदारी फर्म हो तो उसका प्रमाण पत्र (पार्टनरशीप डीड) की सत्य प्रतिलिपि, उपलब्ध तकनीकी अमले की जानकरी पिछले वित्तीय वर्ष का आय चुकता प्रमाणपत्र, पेन नम्बर, जी.एस.टी. (जीवित) पंजीयन एवं प्रशिक्षित यंत्री नियुक्त करने संबंधी प्रमाण पत्र, कर्मचारी भविष्य निधि रांगठन,कर्मचारी, राज्य बीमा निगम रायपुर से पंजीयन एवं विस्तृत निविदा आमंत्रण सूचना (एनआईटी) हस्ताक्षरयुक्त निर्धारित प्रारूप में निविदा आमंत्रण सूचना के कंडिका क्र. 04 के अनुरूप लिफाफा (अ) में प्रस्तुत करना अनिवार्य होगा।

7. कार्य हेतु लिफाफे पर कार्य का नाम निविदा आमंत्रण सूचना कमॉक, निविदा खुलने की तिथि स्पष्ट रूप से लिखकर भेजना

निविदाकार का यह दायित्व है कि वे निविदा भरने के पूर्व स्थल का स्वयं निरीक्षण कर लेवें ताकि प्रारंभ करने में किसी प्रकार की कठिनाई न हो।

निर्धारित निविदा प्रपत्र में उल्लेखित कंडिकाएँ स्वमेव लागू मानी जावेगी एवं निविदा आमंत्रण सूचना निविदा का ही भाग

10. निर्धारित प्रारूप में निविदा प्रपत्र, निविदा प्रपत्र शुल्क, अमानत राशि, निविदा आमंत्रण सूचना पत्र में उल्लेखित दस्तावेज सही पाए जाने पर ही निविदा दर का लिफाफा खोला जावेगा अन्यथा निविदा निरस्त कर दी जावेगी।

11. ठेकेदार को अपनी दरें शब्दों एवं अंको में लिखना अनिवार्य होगा।

12. शासन के विभिन्न विभागों जैसे:— खजिन विभाग, श्रम विभाग, समाज कल्याण विभाग इत्यादि विभागों द्वारा समय-समय पर जारी निर्देशों/आदेशों के पालन की समस्त जिम्मेदारी संबंधित ठेकेदार की होगी।

13. ठेकेदार यदि कार्य को अपूर्ण स्थिति में छोड़ता है तो निविदा प्रपत्र में उल्लेख अनुसार इस संबंध में प्रावधान के अंतर्गत कार्यवाही की जावेगी।

14. कार्य प्रारंभ नहीं करने अथवा अपूर्ण स्थिति में छोड़ने पर निगम द्वारा ठेकेदार के विरूद्ध तत् समय में एम.आई. सी. द्वारा स्वीकृत प्रस्ताव के अधीन कार्यवाही की जावेगी जिसकी संपूर्ण जवाबदारी ठेकेदार की होगी।

15. सफल निविदा दाता से अनुबंध के समय अतिरिक्त परफार्मेंस राशि जमा कराई जावेगी जबकि निविदा की दरों में काफी कमी हो जैसे निविदादाता को निविदा दर एवं अनुमानित लागत से 10 प्रतिशत से अधिक निविदा दर होने पर सफल निविदादाता को निविदा दर एवं अनुमानित लागत के 90 प्रतिशत अंतर की राशि के समतुल्य परफामेंस गारंटी के रूप में राष्ट्रीयकृत बैंक का एफ.डी.आर. /टी.डी.आर. ऑफिस अथवा टाईम डिपॉजिट जो कि आयुक्त नगर पालिक निगम कोरबा के नाम से देय होगा, जो मांग तिथि से 15 दिवस के भीतर जमा करना अनिवार्य होगा। उपरोक्त राशि को जमा न करने की दशा में निविदा निरस्त कर दी जावेगी।

16. सम्पूर्ण किये गये कार्यों के लिये 5 प्रतिशत सुरक्षा राशि रिनंग देयकों के साथ 01 वर्ष हेतु साथ ही 5 प्रतिशत पृथक से 03

वर्ष की गारंटी के लिये परफारमेंस सिक्यूरिटी के रूप में रोकी जावेगी।

17. निविदा में भाग लेने वाले ठेकेदारों को छ.ग. भवन और अन्य सन्निर्माण कर्मकार (नियोजन एवं सेवा शर्तों का विनियमन) अधिनियम 1996 एवं तद्अंतर्गत निर्धारित नियमों के तहत् पंजीयन कराना आवश्यक होगा तथा निर्माण लागत का 1 प्रतिशत उपकर के रूप में प्रत्येक देयक से कटौती की जावेगी।

18. निविदाकार को प्रत्येक निविदा में पंजीयन क्षमता के अंतर्गत वर्तमान में नगर निगम या अन्य विभागों में किये जा रहे कार्यों का विवरण राशि सहित मूल प्रति में वैध शपथ पत्र राशि रू. 100/- नॉन ज्यूडिशियल स्टॉम्प पेपर पर कंडिका क्र. 04 के प्रथम लिफाफा (अ) में प्रस्तुत करना अनिवार्य होगा।

19. ईट से संबंधित निर्माण कार्यों में फ्लाई एश ब्रिक का उपयोग किया जाना अनिवार्य होगा।

20. निविदा प्रपत्र अहस्तांतरणीय होगा एवं सशर्त निविदाओं पर विचार नही किया जावेगा।

21. निविदा के संबंध में किसी प्रकार की विवाद होने की स्थिति में आयुक्त के द्वारा अधीनस्थ अधिकारियों का निर्णय अंतिम एवं

22. निविदा प्रपत्र Form-A के क्लॉज नम्बर-11 अनुसार एस्केलेशन देय नहीं होगा।

23. निविदा स्वीकृत करने अथवा अस्वीकृत करने का अधिकार आयुक्त, नगर पालिक निगम के पास सुरक्षित रहेगा।

24. निविदा खुलने की तिथि में अवकाश होने पर आगामी तिथि (कार्य दिवस) को निविदा संबंधी कार्यवाही मानी जावेगी।

10-

1. अमानत राशि के रूप में एफ.डी.आर. / टी.डी.आर. अथवा नगद जमा रसीद पृथक से लिफाफे में स्वीकार किए जावेंगे आयुक्त, नगर पालिक निगम, कोरबा के नाम पर देय हो। उपरोक्त तिथियों में किसी भी तिथि को शासकीय/स्थानीय अवकाश होने की स्थिति में अगले कार्य दिवस को

निर्धारित तिथि समय एवं स्थान माना जावे।

प्रतिलिपि :--प्रोग्रागर, संचालनालय, नगरीय प्रशासन एवं विकास विभाग, नया रायपुर (छ.ग.) को Uad.cg.gov.in में अपलोड किये जाने हेतु प्रेषित।

| (ठेकेदार के हस्ताक्षर)   | ्रकार्यपालन अभियंता<br>नगर पालिक निगम |
|--|---------------------------------------|
| THE COURSE OF TH | कोरबा (छ.ग.)                          |
| पूर्ण पता  | VIII (O. I.)                          |
| 49.0647-4, 1-4, 1-4, 1-4, 1-4, 1-4, 1-4, 1-4, 1  |                                       |
| मोबाईल नं  |                                       |

## OFFICE OF THE MUNICIPAL CORPORATION, KORBA (C.G.)

## DETAILED ESTIMATE

on ward No. 55

per Sor Schedule of Rates Public Works Department [ PWD BUILDING 01-01-2015]

| Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits  In all types of soils.  6 1.5 1.5 1.5 20.25  1 24.8 0.5 0.5 5.20  2 Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.  6 1.5 1.5 0.1 1.35  2 Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  4 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.  1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35  1 7 5 0.1 3.50  2 1:13:3 (1 cement : 11 coarse sand : 3 graded stone aggregate 20mm nominal size).  1 1 7 5 0.1 3.50  2 1:13:3 (1 cement : 11 coarse sand : 3 graded stone aggregate 20mm nominal size).  5 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6 82 0.3 1.7 6.12  6 1 24.8 0.3 7.44   | 1        | per con a series and a series and a series a ser | - opara          |      |     |              |        |               | · · · · · · |                 |
|--|----------|--|------------------|------|-----|--------------|--------|---------------|-------------|-----------------|
| trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits   |          | no.  | N                | L    | В   | H/D          | Qty    | Unit          | Rate        | Amount          |
| Including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits   In all types of soils.   |          |  |                  |      | 1   |              |        |               |             |                 |
| and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits  In all types of soils.  6 1.5 1.5 1.5 20.25  1 24.8 0.5 0.5 6.20  Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.  6 1.5 1.5 0.1 1.35  1 7 5 0.3 10.50  3 Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  4 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.  1:4:8 (1 cement: 4 coarse sand: 8 graded stone aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35  1 1 24.8 0.5 0.1 0.61  1 1 7 5 0.1 3.50  1 113:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size).  7 Providing and fixing form work including centring, shuttering, strutting, stagling, propping bracing etc. complete and including its removal at all levels, for: foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.4 1.7 6.12  1 24.8 0.3 7.44  |          |  |                  |      |     |              |        |               |             |                 |
| excavated area), including dressing and leveling of pits   In all types of soils.   6   1.5   1.5   1.5   20.25  |          |  |                  |      |     |              |        |               |             |                 |
| pits   In all types of soils.   6   1.5   1.5   20.25  |          |  |                  |      |     |              |        |               |             |                 |
| In all types of soils.   |          | excavated area), including dressing and leveling of  |                  |      |     |              | 1      |               |             |                 |
| 6  | L        |  |                  |      |     |              |        |               |             | -               |
| 1   24.8   0.5   0.5   6.20  | L        | In all types of soils.   |                  |      |     |              | ļ      |               |             |                 |
| Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.  | L        |  | 6                | 1.5  | _   |              |        |               |             | ,               |
| 2   Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.  |          |  | 1                | 24.8 | 0.5 | 0.5          |        |               |             |                 |
| dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.    1  |          |  |                  |      |     |              | 26.4   | 5 cum         | 185         | 4893.25         |
| exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete.    6   1.5   1.5   0.1   1.35  | 7        | Providing and filling in plinth with sand/ Crusher   |                  |      |     | 1            | 1      |               |             | -               |
| deposited layer by ramming and watering, including dressing etc. complete.   |          | dust and hard moorum under floor in layers not   | 1                | 1    |     |              |        | 1             | 1           |                 |
| dressing etc. complete.  | 1        | exceeding 20cm in depth consolidating each   |                  |      | 1   | 1            | 1      |               |             |                 |
| 1.5   1.5   0.1   1.35   |          | deposited layer by ramming and watering, including   |                  |      | 1   |              |        |               |             |                 |
| 1.5   1.5   0.1   1.35   |          | dressing etc. complete.  |                  |      |     |              |        |               |             |                 |
| 1  | $\vdash$ |  | 6                | 1.5  | 1.5 | 0.1          | 1.35   | 5             | 1           |                 |
| 11.85 cum 371 4396.:   3 Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.   4 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.   1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).   6   1.5   1.5   0.1   1.35   | $\vdash$ |  | +                |      | +   |              | 10.50  |               |             |                 |
| 3 Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  4 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.  1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35  1 24.8 0.5 0.1 1.24  1 12.1 0.5 0.1 0.61  1 7 5 0.1 3.50  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  7 Forviding and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  | $\vdash$ |  | <del>  '</del> - |      | +-  | 0.0          |        |               | 371         | 4396.35         |
| rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  4 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.  1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35  1 24.8 0.5 0.1 1.24  1 12.1 0.5 0.1 0.61  1 7 5 0.1 3.50  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1 1.6 1.2 0.15 0.29 cum 4073 1173.02  5 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16   | 1        | Filling from englishle exercised stuff (Evoluting  |                  |      | -   | <del> </del> | 11.05  | Cum           | 371         | 4000.00         |
| layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  4 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.  1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35  1 24.8 0.5 0.1 1.24  1 12.1 0.5 0.1 0.61  1 7 5 0.1 3.50  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1 1.6 1.2 0.15 0.29 cum 4073 1173.02  5 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44   | ,        |  | 1                |      |     |              |        |               |             | l,              |
| each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  4 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.  1:4:8 (1 cement: 4 coarse sand: 8 graded stone aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35   |          |  |                  |      |     |              |        |               |             | h               |
| a lead upto 50 M. and lift upto 1.5 M.   25.45 cum   65   1654.2   | 1        | layers not exceeding 20cm in depth consolidating   |                  |      | 1   |              |        |               |             |                 |
| A Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.  1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35  1 24.8 0.5 0.1 1.24  1 12.1 0.5 0.1 0.61  1 7 5 0.1 3.50  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1 1.6 1.2 0.15 0.29 cum 4073 1173.02  5 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44  |          |  | 1                |      | 1   |              | 25.45  | Cum           | 65          | 1654.25         |
| concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.  1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35  1 24.8 0.5 0.1 1.24  1 12.1 0.5 0.1 0.61  1 7 5 0.1 3.50  6:70 cum 2659 17802.0  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  7 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44  | Ļ        |  |                  | -    | -   |              | 23.43  | Cum           | - 55        | 100 1.20        |
| Concrete mixer in all works upto plinth level excluding cost of form work.   1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).   6  | 4        |  |                  |      |     |              | 7-01-0 |               |             |                 |
| excluding cost of form work.   1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).   6  |          |  | l                |      |     |              |        |               |             | - 42            |
| 1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).   6   |          | •  |                  |      |     |              |        |               |             | 3"              |
| aggregate 40mm nominal size).  6 1.5 1.5 0.1 1.35  1 24.8 0.5 0.1 1.24  1 12.1 0.5 0.1 0.61  1 7 5 0.1 3.50  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  7 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16   |          |  |                  |      |     |              |        |               |             | -               |
| 6 1.5 1.5 0.1 1.35   1 24.8 0.5 0.1 1.24   1 12.1 0.5 0.1 0.61   1 12.1 0.5 0.1 0.61   1 17 5 0.1 3.50   1 18.24   1 18.24   1 18.25   1 |          |  |                  |      |     |              |        |               |             |                 |
| 1 24.8 0.5 0.1 1.24  |          | aggregate 40mm nominal size).  |                  |      |     |              |        |               |             |                 |
| 1 12.1 0.5 0.1 0.61 1 7 5 0.1 3.50 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12 6x2 0.4 1.7 8.16 1 24.8 0.3 7.44  |          |  |                  |      |     |              |        | -             |             |                 |
| 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44   |          |  | 1                |      |     |              |        |               |             |                 |
| 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  1 1.6 1.2 0.15 0.29 cum 4073 1173.02  Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44   |          |  |                  |      |     |              |        |               |             |                 |
| 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44   |          |  | 1                | 7    | 5   | 0.1          |        | -             |             | A la            |
| aggregate 20mm nominal size).  1 1.6 1.2 0.15 0.29 cum 4073 1173.02  Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44  |          |  |                  |      |     |              | 6.70   | cum           | 2659        | 17802.01        |
| aggregate 20mm nominal size).  1 1.6 1.2 0.15 0.29 cum 4073 1173.02  Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44  |          | 1:11%:3 (1 cement : 11% coarse sand : 3 graded stone   |                  |      |     |              |        |               |             |                 |
| Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44   |          |  | 1                | 1.6  | 1.2 | 0.15         | 0.29   | cum           | 4073        | 1173.024        |
| shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12 6x2 0.4 1.7 8.16 1 24.8 0.3 7.44  |          |  |                  |      |     |              |        |               |             | *               |
| shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12 6x2 0.4 1.7 8.16 1 24.8 0.3 7.44  |          | Providing and fixing form work including centring,   | 1                |      |     | 1            |        |               |             |                 |
| complete and including its removal at all levels, for:  Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44  |          |  | - 1              |      | 1   | 1            |        |               |             |                 |
| Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44  |          |  |                  |      |     |              |        |               |             | 84.74           |
| beam, curtain wall in any shape and size and all type of wall below plinth level.  6x2 0.3 1.7 6.12  6x2 0.4 1.7 8.16  1 24.8 0.3 7.44   |          |  |                  |      |     |              |        |               |             | 77.             |
| of wall below plinth level.     6x2     0.3     1.7     6.12       6x2     0.4     1.7     8.16       1     24.8     0.3     7.44  |          |  |                  | - 1  |     |              |        |               |             | 41<br>11 (1883) |
| 6x2     0.3     1.7     6.12       6x2     0.4     1.7     8.16       1     24.8     0.3     7.44  |          |  | - 1              |      |     | 1            | l      |               |             | # function      |
| 6x2 0.4 1.7 8.16<br>1 24.8 0.3 7.44  | -        |  | 6x2              | 0.3  |     | 1.7          | 6.12   |               |             | 1               |
| 1 24.8 0.3 7.44  | $\dashv$ |  |                  |      |     |              |        | $\neg \vdash$ |             |                 |
|  | $\dashv$ |  |                  |      |     |              |        | _             |             |                 |
| 1 1 1 1 21.121801111 133 1 0010.00   | -        |  |                  |      |     |              |        | som           | 139         | 3019.08         |

| den .                     | ITEM DESCRIPTION   | T N |                  |       |          |            |       |      |                       |
|---------------------------|--|-----|------------------|-------|----------|------------|-------|------|-----------------------|
|                           | mns, Pillars, Piers and likes- rectangular or  | N   | <del>  _</del> _ | B     | H/D      | Qty        | Unit  | Rate | Amount                |
| -                         | re in shape  |     |                  |       | 4        |            |       |      |                       |
|                           |  | 5x2 | -                | -     |          |            |       |      |                       |
| 1                         |  | 5x2 | -                |       | 3.5      | 10.        | 5     |      |                       |
|                           | and the second s | 3,2 | 0.4              |       | 3.5      |            | 4     |      |                       |
|                           |  | +   |                  |       |          | 24.        | 5 sqm | 297  | 7276.5                |
| ,                         | Suspended floors, roofs, access platform, balconies  | 1   | 1                | İ     |          |            |       |      | - 13                  |
|                           | (plain surfaces) and shelves (cast in situ)  |     |                  |       |          |            |       | 1    | Ÿ                     |
|                           |  | -   | <del>  _</del>   |       |          |            |       |      |                       |
|                           |  | 1   | 8                | 6     |          | 4          | _     |      |                       |
|                           |  | 1   | 7.4              | 0.6   | <u> </u> | 4.4        |       |      |                       |
|                           | Beams, lintels, cantilevers & walls  | -   | <del> </del>     |       |          | 52.4       | 4 sqm | 235  | 12323.4               |
|                           |  | 20  | 47.0             |       |          |            |       |      |                       |
|                           |  | 2x2 | 17.8             |       | 0.2      | 14.2       | 4     |      | ,                     |
|                           |  | 1x2 | 7                |       | 0.5      |            | 7     |      |                       |
|                           |  | 1x2 | 5                |       | 0.4      |            | 1     |      |                       |
| 6                         |  | -   |                  |       |          | 25.24      | 1 sqm | 202  | 5098.48               |
|                           | Providing and placing in position reinforcement for  |     | 1                |       |          |            |       |      |                       |
|                           | R.C.C. work including straightening, cutting,  | i i |                  |       |          |            |       |      |                       |
|                           | bending, binding etc. complete as per drawings   |     |                  |       |          |            |       |      |                       |
|                           | including cost of binding wire in foundation and   | -   | 1                |       |          |            |       |      |                       |
|                           | plinth all complete:   |     |                  | 1     | 1        |            |       |      |                       |
|                           | Thermo-Mechanically treated bars FE 415  |     |                  |       | -        |            | ļ     |      |                       |
| 7                         | Providing and laying nominal mix reinforced cement   |     |                  | -     |          | 1800       | kg    | 54.5 | 98100                 |
|                           | concrete with crushed stone aggregate using  |     |                  | 1     |          |            |       |      |                       |
|                           | concrete mixer in all works upto plinth level  |     |                  |       | 1        |            |       |      |                       |
|                           | excluding cost of form work.   |     |                  | 1     |          |            |       |      |                       |
| $\neg$                    | 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone   |     |                  | -     |          |            |       |      | 1                     |
| - 1                       | aggregate 20mm nominal size).  |     | 1                |       |          |            |       |      | y. •                  |
|                           | -888ate 2011111 Horillital 312e).  |     |                  | -     |          |            |       |      |                       |
| $\dashv$                  |  | 6   | 1.5              | 1.5   | 0.3      | 4.05       |       |      |                       |
| $\dashv$                  |  | 5   | 0.3              | 0.4   | 4.5      | 2.70       |       |      |                       |
| $\dashv$                  |  | 1   | 0.3              | 0.4   | 1.7      | 0.20       |       |      |                       |
| $\dashv$                  |  | 1   | 24.8             | 0.2   | 0.3      | 1.49       |       |      |                       |
| +                         |  | 2   | 17.8             | 0.2   | 0.2      | 1.42       |       |      |                       |
| +                         |  | 1   | 8                | 6     | 0.12     | 5.76       |       |      |                       |
| $\dashv$                  |  | 1   | 7.4              | 0.6   | 0.1      | 0.44       |       |      | 45.7                  |
|                           |  | 1   | 7.4              | 0.4   | 0.5      | 1.48       |       |      | 21 2                  |
|                           |  | 1   | 6                | 0.3   | 0.4      | 0.72       |       |      |                       |
| $\top$                    |  |     |                  | 0.0   | 0.4      |            |       |      |                       |
| 8                         |  |     |                  |       |          | 18.27      | cum   | 4163 | 76058.01              |
|                           | Providing and loving visuities of the autiliary visual and   |     |                  | 1     |          |            |       |      | 1                     |
|                           | Providing and laying vitrified floor tiles with double   |     |                  |       |          |            |       |      | medical.              |
|                           | harge/ multi charge printing with water absorption   |     |                  |       | -        |            |       |      | 10 200                |
|                           | ess than 0.5% and conforming to IS :15622 of   | 1   |                  |       |          |            |       |      |                       |
|                           | pproved make in all colours and shades and size  | 1   |                  |       |          |            |       |      | ea <sup>7</sup> / - 1 |
| a                         |  |     |                  |       |          |            |       |      |                       |
| a<br>m                    | nentioned below (+/- 10mm), laid on 20mm thick   | J   |                  |       |          |            |       |      | -7-N                  |
| a<br>m<br>c               | ement mortar 1:4 (1 cement : 4coarse sand)   |     |                  |       | ı        |            |       |      |                       |
| a<br>n<br>c<br>ir         | ement mortar 1:4 (1 cement : 4coarse sand) ncluding grouting the joints with white cement and  |     |                  |       | =        |            |       |      | 2.5                   |
| a<br>m<br>co<br>ir<br>m   | ement mortar 1:4 (1 cement : 4coarse sand) ncluding grouting the joints with white cement and natching pigments etc. complete.   |     |                  |       | -        |            |       |      | -31                   |
| a<br>m<br>co<br>ir<br>m   | ement mortar 1:4 (1 cement : 4coarse sand) ncluding grouting the joints with white cement and  | 1   | 7                | 5     |          | 25         |       |      |                       |
| a<br>m<br>co<br>ir<br>m   | ement mortar 1:4 (1 cement : 4coarse sand) ncluding grouting the joints with white cement and natching pigments etc. complete.   |     |                  | 5     |          | 35         |       |      | 3000                  |
| a<br>m<br>co<br>ir<br>m   | ement mortar 1:4 (1 cement : 4coarse sand) ncluding grouting the joints with white cement and natching pigments etc. complete.   | 1   | 7 24.8           | 5 0.2 |          | 35<br>4.96 |       |      |                       |
| a<br>rr<br>co<br>ir<br>rr | ement mortar 1:4 (1 cement : 4coarse sand) ncluding grouting the joints with white cement and natching pigments etc. complete.   |     |                  |       |          |            |       | 2    |                       |

|          |     | ITEM DESCRIPTION   | N  | L              | В        | H/D   | Qty    | Unit   | Dota . | - 1 %        |
|----------|-----|--|--|----------------|----------|-------|--------|--|--------|--------------|
|          |     | 200 - 1  | <del>                                     </del> | <del>  -</del> | <b>─</b> | 11110 | Giy    | Onn  | Rate   | Amount       |
|          |     |  |  |                |          |       |        |  |        |              |
|          |     | ru 'ding and fixing in position collapsible steel        |  |                |          |       |        |  |        |              |
| /        |     | shutte with vertical channels 20x10x2mm and              |  |                |          |       |        |  |        | 82           |
| /        |     | braced ith flat iron diagonals 20x5mm size               |  |                |          |       |        |  |        | 100          |
|          |     | with top and bottom rails of T-iron 40x40x6mm with       | h  |                |          |       |        | 1  |        |              |
| ,        |     | 38mm steel pulleys complete with bolts, nuts,            |  |                |          |       |        | 1  | 1      |              |
|          |     | locking arrangement stoppers, handles                    |  |                |          |       |        |  |        | 44           |
| - 1      |     | including applying a priming coat of red oxide zinc      |  |                |          |       |        |  | 1      |              |
| L        |     | chromate primer.   | 1  | 7              |          | 2.2   | 15.    | 4 Sqn  | 3330   | 51282        |
|          | 10  |  |  |                |          |       |        |  |        |              |
|          |     | Providing and fixing steel door/ window with M.S.        |  |                |          |       |        |  |        |              |
|          |     | sheet 1mm thick, frame of angle iron, diagonal           |  |                |          |       | 1      |  |        | 25           |
| - 1      |     | braces of angle/ flat iron of suitable size, 3.00 mm     |  |                |          |       |        |  |        |              |
| - 1      |     | M.S. gusset plates at junctions and corners, all         |  |                |          |       |        |  |        | 1,181,65.75  |
|          |     | necessary fittings complete including applying a         |  |                | 1        |       |        | 1  |        |              |
|          |     | priming coat of red oxide zinc chromate primer.          |  |                |          |       | 150    | kg   | 75     | 11250        |
| Γ        | 11  | 7.5 Brick work with modular fly-ash lime bricks          | 3  |                |          |       |        |  |        | -            |
| 1        |     | (FaLG Bricks) confirming to IS:12894-2002 of class       | 3  |                |          |       |        |  |        |              |
|          |     | designation 4.0 in foundation and plinth in              |  |                |          |       |        |  |        |              |
| Γ        |     | Cement Mortar 1:6 (1 cement : 6 coarse sand)             |  |                |          |       |        |  |        |              |
|          |     |  | 1  | 24.80          | 0.30     | 0.70  | 5.2    | 2  |        |              |
| Γ        |     |  | 1  | 24.80          | 0.20     | 3.20  | 15.9   |  |        |              |
| Γ        |     |  | 1  | 26.00          | 0.20     | 0.20  | 1.0    |  |        |              |
|          |     | deduction SHUTTER  | 1  | 7.00           | 0.20     | 2.20  | -3.1   |  |        |              |
|          | 7   | P.   | 1  | 7.40           | 0.60     | 0.20  | 0.9    |  |        |              |
|          | 7   |  | 1  | 7.40           | 0.30     | 0.20  | 0.4    | <del>                                     </del> |        |              |
|          | 7   |  |  |                |          |       |        | Cum  | 3263   | 66473.836    |
| 1:       | 1   | Extra for brick work in superstructure above plinth      |  |                |          |       |        |  | -      | 30 11 01000  |
| 1        | 1   | evel for every floor or part thereof in addition to rate |  | 1              | 1        | 1     |        | 1  |        | 1            |
|          | f   | or foundation and plinth:                                |  |                |          |       | 100    | l  |        |              |
|          |     |  | 1  | 24.80          | 0.20     | 3.20  | 15.9   |  |        |              |
|          | T   | Ar -   | 1  | 26.00          | 0.20     | 0.20  | 1.0    |  |        |              |
|          | d   | eduction SHUTTER   | 1  | 7.00           | 0.20     | 2.20  | -3.1   |  |        |              |
| _        |     |  |  |                |          |       | 13.8   | Cum  | 121.00 | 1673.67      |
| 13       |     | roviding and making 6mm thick cement plaster of          |  |                |          | _     |        |  |        | Sand Market  |
| $\vdash$ | +-  | nix:  1 Cement mortar 1:4 (1 cement : 4 fine sand)       |  | -              |          |       |        |  |        |              |
| 一        | ۳   | recinent mortal 1.4 (1 cement : 4 mie sand)              | 1  | 8.00           | 6.00     |       | 48     |  |        | 140 140 150  |
| 一        | 1   |  | 1  | 7.40           | 0.90     |       | 6.66   |  |        | 3.20         |
|          | 1   |  |  | 11.0           | 0.50     |       | 54.66  |  | 87.00  | 4755.42      |
| 14       | P   | roviding and making 12mm thick cement plaster of         |  |                |          |       |        | 34   | 07.00  |              |
|          | -   | ix:  |  |                |          |       |        |  |        | 23.0         |
|          | In  | Cement Mortar 1:5 (1 cement : 5 fine sand)               |  | 24.00          |          |       |        |  |        | 1 V-14       |
|          | de  | eduction SHUTTER   | 1  | 24.80          |          | 4.50  | 111.60 |  |        | 1/12         |
|          | -   |  | 1  | 7.00           |          | 2.20  | -15.40 |  |        | A CONTRACTOR |
|          | -   |  | 1  | 24.80          |          | 0.50  | 12.40  |  |        |              |
| 15       | 11  | .3 Providing and making 15mm thick cement                |  |                |          |       | 108.60 | Sqm  | 96.50  | 10479.9      |
|          | pl  | aster on the rough side of single or half brick wall     |  |                |          |       |        |  |        | and the same |
|          | lof | mix  |  | 1              | - 1      |       | 1      | - 1.   |        | 4 1847 -     |

| Sex.                | ITEM DESCRIPTION   | H                            | L                             | 1  | 3 H/0                       | Qty        | Uni   | Rato     | Amount    |
|---------------------|--|------------------------------|-------------------------------|--|-----------------------------|------------|-------|----------|-----------|
|                     | ement Mortar 1:5 (1 cement : 5 fine sand)  | Median A - Perint Col Marine |                               | William & House,   | STREET, COURSEAS BUT        |            |       |          |           |
|                     | gatte bed for the second of th | 1                            | 24.8                          | 0  | 4.5                         | 0 111.60   |       |          |           |
| 100                 | jedu don SHUTTER   | 1                            | 7.0                           | 5  | 2.2                         | -15.40     |       |          |           |
|                     |  | Miles - emissionaux          | Marine A. Marine Constitution | and the last of th | Million and American Street | 96.20      | Sqrr  | 113.00   | 10870.6   |
|                     | Providing and applying 2mm thick ready mix exterior  |                              |                               |  |                             |            |       |          |           |
|                     | grade putty (manufactured with cow dung processing) o  | n                            |                               |  | 1                           |            |       |          |           |
| ĺ                   | walls to make the surface smooth aid even.   |                              |                               |  |                             |            |       |          |           |
| -00000              | A supplement of the control of th    | 1                            | 8.00                          | 6.0  | 0                           | 3          | 5     |          |           |
| - 6220090           |  | 1                            | 7.40                          | 0.9  | 0                           | 6.6        | 6     |          |           |
| -                   |  | 1                            | 24.8                          | )  | 3.50                        | 86.80      |       |          |           |
| -                   | deduction SHUTTER  | 1                            | 7.00                          |  | 2.20                        | -15.40     |       |          |           |
| - Climit & some     |  | 1                            | 24.80                         |  | 0.50                        | 10.40      |       |          |           |
| -400/100000         | and the second control of the second control | 1                            | 24.80                         |  | 4.50                        | 93.60      |       |          |           |
| - describing        | - CONTRACTOR AND CONT |                              |                               |  |                             | 217.06     | Sqm   | 101.00   | 21923.06  |
| 17                  | Wall painting with premium emulsion (plastic)  |                              |                               |  |                             |            |       |          |           |
|                     | manufactured with the cow dung processing emulsion   |                              | 1                             |  |                             |            |       |          |           |
| 1                   | paint of required shade to give an even shade.   |                              |                               |  |                             |            |       |          |           |
| - MINISTER SPANISCO | On new work (two or more coats)  |                              |                               |  |                             |            |       |          |           |
| -                   |  | 1                            | 8.00                          | 6.00   |                             | 35         | -     |          | -         |
| - DESIGNATION.      | - CO 200 - C | 1                            | 7.40                          | 0.90   |                             | 6.66       | -     |          |           |
|                     |  | 1                            | 24.80                         |  | 3.50                        | 86.80      | -     |          | -         |
|                     | deduction SHUTTER  | 0.5                          | 7.00                          | -  | 2.20                        | -7.70      | 6     | 69.00    | 8332.44   |
|                     |  |                              |                               | -  | -                           | 120.76     | Sqm   | 69.00    | 0332.44   |
| 18                  | Painting exterior surface with SMOOTH exterior   |                              | 1                             | 1  |                             | 8          |       |          |           |
|                     | emulsion paint manufactured with the cow dung<br>processing to give protective and decorative finish   |                              | l                             | -  |                             |            |       |          | and to    |
|                     | including cleaning washing of surface etc. complete with:  |                              |                               |  |                             |            |       |          |           |
| - 1                 |  |                              |                               |  | -                           | -          |       |          |           |
| - 1.                | On new work (Two or more coats applied @1.43 ltr/ 10   |                              |                               |  |                             | 1.4        |       |          |           |
|                     | gm over.   | 1                            | 24.80                         |  | 4.50                        | 111.60     |       |          |           |
|                     | leduction SHUTTER  | 0.5                          | 7.00                          |  | 2.20                        | -7.70      |       |          |           |
|                     |  |                              |                               |  |                             | 103.90     | Sqm   | 79.00    | 8208.1    |
| 19                  | 4.22 Painting on new work (two or more coats) to   |                              | _                             |  |                             |            |       |          |           |
| 18                  | ive an even shade with:  |                              |                               |  |                             |            | _     |          |           |
| 5                   | atin synthetic enamel paint  | 1X2                          | 7.00                          |  | 2.20                        | 30.80      | Sqm   | 55.00    | 1694      |
|                     |  |                              | P                             | s per  | SOR To                      | tal Estima | te Am | ount Rs. | 484952.22 |
| -                   | for internal electrification   |                              |                               |  |                             |            |       |          | 15000.00  |
| -                   | Net amount   |                              |                               |  |                             |            |       |          | 499952.22 |
|                     |  |                              |                               |  |                             | Sa         | y amo | unt Rs.  | 500000.00 |

Sub Engineer Municipal Corporation Korba (C.G.) Asst. Engineer Municipal Corporation Korba (C.G.)