

क्रायालय, नगर पालिक निगम, क्रोरवा (छ.ग.) मुख्य कार्यालय - साकेत भवन, आई.टी.आई. चौक, कोरबा (छ.म.)

5. 1906,1993,1994,1997,1998,1999, 2000, 2001, 2002, 2003, 2004, 2007,

2008, 2009, 2010, 2011 एवं 2012/निमान्। व्यास्त्रीमी

कोरबा, दिनांक

निविदा आमंत्रण की सूचना

लोक निर्माण विभाग से एकीकृत पंजीयन प्रणाली अंतर्गत सक्षम श्रेणी में पंजीकृत ठेकेदारों से निम्नलिखित कार्य हेतु प्रमुख अभियन्ता लोक निर्माण विभाग, रायपुर द्वारा प्रचलित PWD Building SOR 01.01.2015 से प्रभावशील दर अनुसूची पर (निविदा खुलने के दिनांक तक समस्त संशोधनों के साथ) कम अधिक या समान दरों पर तथा शेड्युल अनुसार आयटम दरों पर निम्नलिखित निर्माण कार्य हेतु मैन्युअल निविदा वेबसाईट से डाउनलोड कर वंद लिफाफा के माध्यम से आमंत्रित की जाती है :--

- (अ) अनुक्रमांक 01 से 11 तक में उल्लेखित कार्य हेतू :-
 - 1. निर्धारित प्रारूप में निविदा प्रपत्र प्राप्त होने अंतिम तिथि
- 01.01.2024 सायंकाल 3:00 बजे तक

2. निविदा खुलने की अंतिम तिथि

- 01.01.2024 सायंकाल 4:30 बजे तक
- अनुक्रमांक 12 से 17 तक में उल्लेखित कार्य हेत् :-(ब)
 - 1. निर्धारित प्रारूप में निविदा प्रपत्र प्राप्त होने अंतिम तिथि
- 05.01.2024 सायंकाल 3:00 बजे तक

2. निविदा खुलने की अंतिम तिथि

– 05.01.2024) सायंकाल 4:30 बजे तक

क.	कार्य का नाम	प्राक्कलन राशि	धरोहर राशि	निविदा प्रपत्र का मूल्य	निविदा प्रपत्र	कार्य अवधि	ठेकेदार का वर्ग	निविदा खुलने की तिथि
1	वार्ड क्र. 35 नागरिक कल्याण समिति बालको के पास कक्ष सह टॉयलेट का निर्माण कार्य। (सांसद मद 2021—22) (चतुर्थ निविदा)	5,00,000 / —	5,000 / —	750 / —	Form-A	03 माह	सक्षम श्रेणी	01.01.2024
2	वार्ड क्र. 36 नया रिस्दा भदरापारा चंद्रा समाज भवन के पास अमर सिंह चंद्रा के घर के पास वाली गली में सामुदायिक भवन निर्माण। (प्रभारी मंत्री मद 2023–24) (द्वितीय निविदा)	20,00,000/-	15,000 / —	750/-	Form-A	06 माह	सक्षम श्रेणी	01.01.2024
3	वार्ड क्र. 36 नया रिस्दा कब्रिस्तान के पीछे झेरिया धोबी / बरेठ समाज भवन के पास शौचालय मूत्रालय निर्माण (महिला / पुरुष) कार्य। (प्रभारी मंत्री मद 2023—24) (द्वितीय निविदा)	5,00,000/-	5,000 / —	750/-	Form-A	03 माह	सक्षम श्रेणी	01.01.2024
4	वार्ड क्र. 37 अंतर्गत डुग्गूपारा रिथत सामुदायिक भवन का संधारण एवं नई सुविधाओं की व्यवस्था का कार्य। (पार्षद मद 2023–24) (द्वितीय निविदा)	7,00,000 / —	5,250/-	750/-	Form-A	04 माह	सक्षम श्रेणी	01.01.2024
5	वार्ड क्र. 37 पुराना गुरुघासी दास चौक भदरापारा में सी.सी.रोड मरम्मत एवं निर्माण कार्य। (मरम्मत एवं संधारण मद) (द्वितीय निविदा)	3,04,000/-	3,050/-	750/-	Form-A	03 माह	सक्षम श्रेणी	01.01.2024

	वार्ड क २० ०				_			
6	वार्ड क्र. 39 आजाद नगर में चबुतरा निर्माण कार्य एवं सी.सी.रोड निर्माण कार्य। (पार्षद मद 2023–24) (द्वितीय निविदा)	7,00,000 /—	5,250/-	750 / -	Form-A	03 माह	सक्षम श्रेणी	01.01.2024
7	वार्ड क्र. 40 नेहरुनगर बालको में बाजार के पास उप स्वास्थ्य केंद्र में सी.सी.रोड, पाथवे एवं नाली का निर्माण कार्य। (एल्डरमेन निधि 2022–23) (द्वितीय निविदा)	6,00,000 /—	4,500 / -	750 / —	Form-A	03 माह	सक्षम श्रेणी	01.01.2024
8	वार्ड क्र. 40 बालको अंतर्गत विभिन्न सांस्कृत मंच का जीर्णोद्धार कार्य। (चर्च के पास, आयुष्मान क्लीनिक के पीछे एवं मुक्तिधाम के पास) (पार्षद मद 2023–24) (द्वितीय निविदा)	1	5,250 /—	750/-	Form-A	04 माह	सक्षम श्रेणी	01.01.2024
9	वार्ड क्र. 41परसाभाठा 02 में सार्वजनिक मंच (कांजी हाउस के नीचे) में नई सुविधाओं की व्यवस्था एवं सी.सी.रोड, नाली का निर्माण कार्य।(पार्षद मद 2023–24) (द्वितीय निविदा)	7,00,000 / —	5,250/-	750/-	Form-A	04 माह	सक्षम श्रेणी	01.01.2024
10	वार्ड क्र. 41बालको आदर्श सतनाम समिति के पास सामुदायिक भवन में अतिरिक्त विकास कार्य। (महापौर मद 2023–24) (द्वितीय निविदा)	10,00,000 / —	7,500 / -	750/-	Form-A	03 माह	सक्षम श्रेणी	01.01.2024
11	वार्ड क्र. 42 रुमगरा बालको में चबुतरा (परमात्मा सोनी गली में, बिहारी मोहल्ला में एवं टीपपारा में चबुतरा) निर्माण कार्य। (पार्षद मद 2023–24) (द्वितीय निविदा)	7,00,000/-	5,250 /—	750/-	Form-A	04 माह	सक्षम श्रेणी	01.01.2024
12	वार्ड क्र. 34 लालघाट अंतर्गत चेकपोस्ट के पास स्थित सामुदायिक भवन में नई सुविधाओं की व्यवस्था का कार्य। (पार्षद मद 2023—24) (प्रथम निविदा)	7,00,000 / —	5,250 / —	750/-	Form-A	04 माह	सक्षम श्रेणी	05.01.2024
13	वार्ड क्र. 35 बालको हाउसिंग बोर्ड कालोनी डी टाईप में नाली का मरम्मत/निर्माण कार्य। (मरम्मत एवं संधारण मद) (प्रथम निविदा)	3,71,000 /—	3,750/-	750/—	Form-A	03 माह	सक्षम श्रेणी	05.01.2024
14	वार्ड क्र. 35 शांतिनगर बालको में शेखर वर्मा घर से दीपक जाटवर घर तक रोड का मरम्मत एवं संधारण कार्य। (मरम्मत एवं संधारण मद) (प्रथम निविदा)	2,01,195/—	2,100 /—	750/-	Form-A	03 माह	सक्षम श्रेणी	05.01.2024
15	वार्ड क्र. 35 शांतिनगर बालको में मन्नू श्रीवास्तव घर से आर.एन.ओझा घर तक नाली का मरम्मत एवं संघारण कार्य। (मरम्मत एवं संघारण मद) (प्रथम निविदा)	3,26,116/-	3,300/-	750/-	Form-A	03 माह	सक्षम श्रेणी	05.01.2024
16	वार्ड क्र. 36 बालको में मुस्लिम कब्रिस्तान के पास शेड का मरम्मत एवं संधारण कार्य। (मरम्मत एवं संधारण मद) (प्रथम निविदा)	3,94,000/-	4,000 / -	750/-	Form-A	03 माह	सक्षम श्रेणी	05.01.2024
17	वार्ड क्र. 41 परसाभाठा क्र. 02 बालकोनगर शिव मंदिर के पास रिथत मंच का मरम्मत कार्य। (मरम्मत एवं संधारण मद) (प्रथम निविदा)	3,98,200 / —	4,000 / —	750/-	Form-A	०३ साह ।	सक्षम श्रेणी	05.01.2024

- 1. निविदा दरे प्रचलित सी.एस.आर.से कम या अधिक प्रतिशत दरों पर दिया जावे सी.एस.आर.के अंतर्गत के आयटमों पर पृथक से आयटम दरों का उल्लेख करने पर निविदा निरस्त् मानी जावेगी।
- 2. निविदा के दस्तावेज हाथो—हाथ न लिया जाकर रिजस्टर्ड पोस्ट अथवा स्पीड पोस्ट से प्राप्त किया जावेगा। अन्य माध्यमों यथा कोरियर सर्विस, साधारण डाक इत्यादि से प्राप्त अथवा समयाविध के पश्चात् प्राप्त निविदाओं पर विचार नहीं किया जावेगा। निविदा आयुक्त, नगर पालिक निगम, आई.टी.आई. चौक साकेत भवन जिला—कोरबा (छ.ग.) पिन नं.—495677 के पते पर भेजना होगा। निर्धारित तिथि को सायं 3:00 बजे के पश्चात् प्राप्त निविदाऍ स्वीकार नहीं किए जावेंगे।
- 3. निविदा प्रपत्र नगर पालिक निगम, कोरबा के वेबसाईट www.korbamunicipal.in/uad.cg.gov.in डाउनलोड किया जाकर नवीन निविदा प्रपत्र Form A/B/ABC (जारी दिनॉक तक समस्त संशोधनों के साथ) निर्धारित शुल्क की डीडी के साथ संबंधित कार्य का नाम पूर्ण विवरण सहित भरकर भेजना होगा।
- 4. निविदा प्रपत्र बंद लिफाफा के माध्यम से मान्य किया जावेगा जो निम्नानुसार होगाः—
 - (अ) प्रथम लिफाफा में ठेकेदार का जीवित पंजीयन प्रमाण पत्र, आयकर चुकता प्रमाण पत्र, निविदा सूचना आमंत्रण में उल्लेखित अन्य दस्तावेज के साथ निर्धारित प्रपत्र शुल्क का वैध डीडी, निविदाओं में निविदाकार को फिजीकल दस्तावेज के साथ निविदा सूचना जारी होने के पश्चात् दिनांक का शपथ पत्र (राशि रु.100/— के नॉन ज्यूडिसियल स्टाम्प पेपर में) जिसमें संबंधित कार्य का नाम एवं कार्य की निविदा क्रमांक प्रत्येक लिफाफे में अंकित कर प्रेषित करना अनिवार्य होगा एवं अमानत राशि का वैध टी.डी.आर./एफ.डी.आर. नगद निगम कोष में जमा कर जो कि आयुक्त, नगर पालिक निगम कोरबा के नाम पर देय होगा प्रस्तुत करना होगा।
 - (ब) द्वितीय लिफाफा में ठेकेदार द्वारा भरा हुआ निविदा प्रपत्र होगा।
 - (स) बंद लिफाफा में उपरोक्त दोनो लिफाफाऍ होगी तथा आवश्यकता पड़ने पर मूल अभिलेख प्रस्तुत करना होगा।
- 5. जिन ठेकेदारों द्वारा नगर पालिक निगम (साडा) के किसी ठेके के कार्य में अनुबंध के अनुरूप कार्य न किया गया हो अथवा नगर पालिक निगम (साडा) के हित के विरूद्ध कार्य किया गया हो उन्हें निविदा भरने की पात्रता नहीं होगी।
- 6. निविदा प्रपत्र प्राप्त करने हेतु इच्छुक ठेकेदारों को आवेदन पत्र के साथ उचित वर्ग में पंजीयन की प्रमाणित प्रतिलिपि यदि साझेदारी फर्म हो तो उसका प्रमाण पत्र (पार्टनरशीप डीड) की सत्य प्रतिलिपि, पूर्व में इस प्रकार की किए गए कार्यों की प्रमाणित सूची, उपलब्ध तकनीकी अमले की जानकरी पिछले वित्तीय वर्ष का आय चुकता प्रमाण पत्र, पेन नम्बर, जी.एस.टी. पंजीयन, शपथ पत्र (मुल प्रति) एवं प्रशिक्षित यंत्री नियुक्त करने संबंधी प्रमाण पत्र, कर्मचारी भविष्य निधि संगठन, कर्मचारी, राज्य बीमा निगम रायपुर से पंजीयन एवं विस्तृत निविदा आमंत्रण सूचना (एनआईटी) हस्ताक्षरयुक्त एवं निर्धारित प्रारूप में निविदा आमंत्रण सूचना के कंडिका क. 04 के लिफाफा (अ) में प्रस्तुत करना अनिवार्य होगा।
- 7. कार्य हेतु प्रत्येक लिफाफे पर कार्य का नाम निविदा आमंत्रण सूचना क्रमॉक, निविदा खुलने की तिथि स्पष्ट रूप से लिखकर भेजना होगा।
- 8. निविदाकार का यह दायित्व है कि वे निविदा भरने के पूर्व स्थल का स्वयं निरीक्षण कर लेवें ताकि प्रारंभ करने में किसी प्रकार की कठिनाई न हो।
- 9. निर्धारित निविदा प्रपत्र में उल्लेखित कंडिकाऍ स्वमेव लागू मानी जावेगी एवं निविदा आमंत्रण सूचना निविदा का ही भाग माना जावेगा।
- 10. निर्धारित प्रारूप में निविदा प्रपत्र, निविदा प्रपत्र शुल्क, अमानत राशि, निविदा आमंत्रण सूचना पत्र में उल्लेखित दस्तावेज सही पाए जाने पर ही निविदा दर संबंधी लिफाफा खोला जावेगा अन्यथा निविदा निरस्त कर दी जावेगी।
- 11. ठेकेदार को अपनी दरें शब्दों एवं अंको में लिखना अनिवार्य होगा।
- 12. शासन के विभिन्न विभागों जैसे:— खजिन विभाग, श्रम विभाग, समाज कल्याण विभाग इत्यादि विभागों द्वारा समय—समय पर जारी निर्देशों / आदेशों के पालन की समस्त जिम्मेदारी संबंधित ठेकेदार की होगी।
- 13. ठेकेदार यदि कार्य को अपूर्ण स्थिति में छोड़ता है तो निविदा प्रपन्न में उल्लेख अनुसार इस संबंध में प्रावधान के अंतर्गत कार्यवाही की जावेगी।
- 14. कार्य प्रारंभ नहीं करने अथवा अपूर्ण स्थिति में छोड़ने पर निगम द्वारा ठेकेदार के विरूद्ध तत् समय में एम.आई. सी. द्वारा स्वीकृत प्रस्ताव के अधीन कार्यवाही की जावेगी जिसकी संपूर्ण जवाबदारी ठेकेदार की होगी।
- 15. सफल निविदा दाता से अनुबंध के समय अतिरिक्त परफार्मेंस राशि जमा कराई जावेगी जबिक निविदा की दरों में काफी कमी हो जैसे निविदादाता को निविदा दर एवं अनुमानित लागत से 10 प्रतिशत से अधिक निविदा दर होने पर सफल निविदादाता को निविदा दर एवं अनुमानित लागत के 90 प्रतिशत अंतर की राशि के समतुल्य परफार्मेंस गारंटी के रूप में राष्ट्रीयकृत बैंक का एफ.डी.आर. /टी.डी.आर. ऑफिस, टाईम डिपॉजिट अथवा एन.एस. सी. जो कि आयुक्त नगर पालिक निगम कोरबा के नाम से देय होगा, जो मांग तिथि से 15 दिवस के भीतर जमा करना अनिवार्य होगा। उपरोक्त राशि को जमा न करने की दशा में निविदा निरस्त कर दी जावेगी।

- 16. सम्पूर्ण किये गये कार्यों के लिये **5 प्रतिशत** सुरक्षा राशि रनिंग देयकों के साथ 01 वर्ष के लिए एवं 5 प्रतिशत परफार्मेंस राशि 03 वर्ष के लिए रोकी जावेगी। (मरम्मत कार्यो के लिए परफार्मेंस गारंटी की राशि नहीं काटी जावेगी।)
- 17. निविदा में भाग लेने वाले ठेकेदारों को छ.ग. भवन और अन्य सिन्मिण कर्मकार (नियोजन एवं सेवा शर्तों का विनियमन) अधिनियम 1996 एवं तद्अंतर्गत निर्धारित नियमों के तहत् पंजीयन कराना आवश्यक होगा तथा निर्माण लागत का 1 प्रतिशत उपकर के रूप में प्रत्येक देयक से कटौती की जावेगी।
- 18. निविदाकार को प्रत्येक निविदा में पंजीयन क्षमता के अंतर्गत वर्तमान में नगर निगम या अन्य विभागों में किये जा रहे कार्यो का विवरण राशि सहित मूल प्रति में वैध शपथपत्र कंडिका क. 04 के प्रथम लिफाफा (अ) में प्रस्तुत करना अनिवार्य होगा।
- 19. ईट से संबंधित निर्माण कार्यों में पलाई एश ब्रिक का उपयोग किया जाना अनिवार्य होगा।
- 20. निविदा प्रपत्र अहस्तांतरणीय होगा एवं सशर्त निविदाओं पर विचार नही किया जावेगा।
- 21. निविदा के संबंध में किसी प्रकार की विवाद होने की स्थिति में आयुक्त के द्वारा अधीनस्थ अधिकारियों का निर्णय अंतिम एवं सर्वमान्य होगा।
- 22. निविदा प्रपत्र Form-A के क्लॉज नम्बर-11 अनुसार एस्केलेशन देय नही होगा।
- 23. निविदा स्वीकृत करने अथवा अस्वीकृत करने का अधिकार नगर पालिक निगम के पास सुरक्षित रहेगा।
- 24. निविदा खुलने की तिथि में अवकाश होने पर आगामी तिथि (कार्य दिवस) को निविदा संबंधी कार्यवाही मानी जावेगी।

नोट:-

- अमानत राशि के रूप में एफ.डी.आर. / टी.डी.आर. अथवा नगद जमा रसीद पृथक से लिफाफे में स्वीकार किए जावेंगे आयुक्त, नगर पालिक निगम, कोरबा के नाम पर देय हो।
- उपरोक्त तिथियों में किसी भी तिथि को शासकीय / स्थानीय अवकाश होने की स्थिति में अगले कार्य दिवस को निर्धारित तिथि समयएवं स्थान माना जावे।

प्रतिलिपि :- प्रोग्रामर, संचालनालय, नगरीय प्रशासन एवं विकास विमाग, नया रायपुर (छ.ग.) को Uad.cg.gov.in में अपलोड किये जाने हेतु प्रेषित।

(ठेकेदार के हस्ताक्षर)	
नाम	W _
पूर्ण पता	कार्यपालन् अभियंता
	नुगर पालिक निगम
मोबाईल नं.—	्रीकोरबा (छ.ग.)

OFFICE OF THE MUNICIPAL CORPORATION, KORBA (C.G.)

ABSTRACT TO THE CONTROL OF A

Name of Work: 1 3 5 0 3 6 121 122 1	Name	ABSTRACT	2/10	T *** 13	AIT	THUS
As per Sor : Schedule of Rates Public Works Department [PWD ELECTRICAL 01:08:020] As per Sor : Schedule of Rates Public Works Department [PWD ELECTRICAL 01:08:020] As per Sor : Schedule of Rates Public Works Department [PWD ELECTRICAL 01:08:020] As per Sor : Schedule of Rates Public Works Department [PWD ELECTRICAL 01:08:020] As per Sor : Schedule of Rates Public Works Department [PWD ELECTRICAL 01:08:020] It Excavation for all types and sizes of foundations, treaches and drains or for any other purpose including disposal of excavated sturf got to Jin I and a lead pto 50 m., at leas 5m away from the excavated area), including dressing and leveling of pits In all types of soil As per Sor soil of the second of the soil of the soil of foundations of soil in the soil of		or work: वार का 36 मया रिस्टा कविरत्ना केपाई		1) 4		1
As per Sor : - Schedule of Rates Public Works Department [PWD BULINGS 071-072] Apper Sor : - Schedule of Rates Public Works Department [PWD ELECTRICAL 0106-2020] Apper Sor : - Schedule of Rates Public Works Department [PWD ELECTRICAL 0106-2020] Apper Sor : - Schedule of Rates Public Works Department [PWD ELECTRICAL 0106-2020] B.N. TEMDESCRIPTION The Public Works Department [PWD ELECTRICAL 0106-2020] In Excavation for all types and sizes of foundations, reaches and drains or for any other purpose including disposal of covavaried stuff upto 1.5 m lift and lead pto 50 m, (at leas 5m away from the excavaried area), including dressing and leveling of pits 44.52 Cum 185.00 8235.83 In all types of soil Lift Public Publi	Maria Na	राज्य के गाम न्याला निर्माण (मिट	er!	<u>पुरुष</u>) 00121	
As per 8 or: - Schedulu of Rates Public Works Department PWU Cele Company Comp	Ac no	Ser & Sebadule of Dates Bublic Works Department PWD BUILDING 01.01.201	5]			
Excavation for all types and sizes of foundations, reaches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead pto 50 m, (at leas 5m away from the excavated area,) including dressing and leveling of pits In all types of soil In all types	As no	er Sor : Schedule of Rates Public Works Department [PWD ELECTRICAL 01.06.	2020]		in nation to 12 to hotelik	Amount
1 Exervation for all types and sizes of foundations, trenches and drains or for any other purpose including disposed of executate start girol 1.5 m lift and lead pto 50 m, at leas 5m away from the executed area), including dressing and leveling of pits 1 In all types of soil 1.17 Filling from available executed staff (Excluding rock) in trenches, plinth, sides of 1 1.75 foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and waterings with add upto 90 M. and lift upto 1.5 M 3 Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete. 4 providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 4 providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 5 providing and laying nominal mix reinforcement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form lasting concrete mixer in all works upto floor five level excluding cost of reinforcement and form lasting concrete mixer in all works upto floor five level excluding cost of reinforcement and form part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bearing placing in position reinforcement for R.C.C. work including straightening cutting bearing placing in position reinforcement for R.C.C. work including straightening cutting bearing and fixing formwork including centering shuttering strutting stagging propping braxing etc. complete and including its removal	SNI	ITEM DESCRIPTION	Qty	Unit	Rate	Alloun
including disposal of exeavated stuff upfo 1.5 m litt and least pot 30 ml, at ceasured area, including dressing and leveling of pits In all types of soil In all types of soil	3.14.	Figure 1 - 1 - 2 - 6 Coundations trenches and drains or for any other purpose				
executed area), including dressing and leveling of pits In all types of soil 2 1.17 Filling from available executed staff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20m in depth consolidating each deposited layer by ramming and watering with a lead upto 30 M. and lift upto 1.5 M 3 Providing and filling in plinth with sand/ Crusher dust and hard mooruru under floor in layers not exceeding 20m in depth consolidating each deposited layer by ramming and watering, including dressing, etc. complete. 4 providing and laying nominal mix center concrets with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 11:15:3 (I centert: 12 Coards sand: 15 graded stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement centent concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding stc. complete as per drawings including cost of binding wire all complete. 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding stc. complete as per drawings including cost of binding wire all complete. 8 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding stc. complete as per drawings including cost of binding wire all complete. 9 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding stc. complete	1	Excavation for all types and sizes of foundations, reflectes and district the size of foundations, reflected and district the size of foundations, reflected and district the size of foundations and district the size of foundations.	>			
In all types of soil 1.17 Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M. 21.75 Cum 371.00 2179.25		inclinding disposal of excavated still upto 1.3 in the and lead people and leading of pits				0225 02
2 I.17 Filling from available excavated stuff (Excluding rock) in trenches, plinth, stose of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M 3 Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete. 4 providing and laving nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 1:36:10 (cement: 1:1/2 coarse sand : 3 graded stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate susing concrete mixer in all works upto floor five level excluding cost of from work. 5 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate susing concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form susing concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form susing concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form susing concrete mixer in all works upto floor five level excluding cost of reinforcement and form susing concrete mixer in all works upto floor five level excluding cost of reinforcement and form susing concrete mixer in all works upto floor floor susing concrete mixer in all works upto floor floor suspense to the providing and placing in position reinforcement for R.C.C. work including straightening cutting benefits and the providing and placing in posit			44.52			
foundation etc. in layers not exceeding 20cm in depth consolidating search printing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete. 4 providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 13-36 (I cement: 1½ coares sand: 3 graded stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement concrete with crushed stone aggregate sum of the s		In all types of soil	21.25	Cum	65.00	1381.25
animing and watering with a lead upto 30 M. and int upto 13 M. and interest once exceeding 20cm in depth consolidating each deposited layer by ramming and watering including dressing etc. complete. 4 providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 13 M. 200 M. 2	2	1.17 Filling from available excavated stuff (Excluding roots) at the state of the consolidating each deposited layer by	,		I	
Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers on exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete. 4 providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 11:36 (1 cement: 3 Coarde sand: 6 graded stone aggregate 40mm nominal size). 5.87 Cum 2970.00 17445.78 11:36 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form ising concrete mixer in all works upto floor five level excluding cost of reinforcement and form ising concrete mixer in all works upto floor five level excluding cost of reinforcement and form part thereof in addition to rate for foundation and plinth. Froviding and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. Thermo-Mechanically treated bars Foundations, footines, bese of columns and plinth beam in any shape and size. Foundations, footines, bese of columns and plinth beam in any shape and size. Foundations, footines, bese of columns and plinth beam in any shape and size. Columns, Fillars, Piers and likes-rectangular or square in shape Beams, limites, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (reat in situ) Suspended floors, roofs, access platform, balconies (plain surfaces) and s		foundation etc. in layers not exceeding 200m in department of the layers and lift unto 1.5 M	1			
Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20em in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete. 4 providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 1:3:6 (1 cement: 3 Courds and: 6 graded stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate 20mm nominal size). 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). 1:11/2:3 (1 cement: 11/2 coarse sand: 3 graded stone aggregate 20mm nominal size). 5 Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 Providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and including its removal at all levels, for etc. complete and including its removal at all levels, for etc. Complete and including its removal at all levels, for etc. Complete and including its removal at all levels, for etc. Complete and including its removal at all levels, for etc. Complete and i						2170 25
not exceeding 20cm in depth consolidating each deposited right by 1 michaling dressing etc. complete. 4 providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 1:3-6 (1 cement: 12 coarnes and: 3 graded stone aggregate 20mm nominal size) 5. Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate 1:11:13:6 (1 cement: 12 coarnes and: 3 graded stone aggregate 20mm nominal size) 5. Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate and from using concrete mixer in all works upto floor five level excluding cost of reinforcement and form is using concrete mixer in all works upto floor five level excluding cost of reinforcement and form is using concrete mixer in all works upto floor five level excluding cost of reinforcement and form is using concrete mixer in all works upto floor five level excluding cost of reinforcement and form is using concrete mixer in all works upto floor five level excluding cost of reinforcement and form is part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and including its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. 6 columns, Flints, Plers and likes- rectangular or squars in shape 12.60 Sym 297.00 3742.20 12.00 Sym 297.00 3742.20 23.22.00 Suppreded floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 39.25 Sqm 235.00 9223.75 8 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894- 2002 of class designation 4.0 in foundation and plinth in: 12. Extra for brick work i		The state of the s	5.87	Cum	3/1.00	21/3.23
including dressing etc. complete. revisiting and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation plinth and at ground level excluding cost of form work. 1:3:6 (1 cement: 3 Coarde sand: 6 graded stone aggregate 40mm nominal size) 1:1½:3 (1 cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size) 5 Providing and laying nominal mix reinforcement cement concrete with trushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor floor level excluding cost of reinforcement and form using concrete mixer in all works upto floor floor part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and including its removal at all levels, for except and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and including its removal at all levels, for except place and planth in any shape and size. 8 providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and including its removal at all levels, f	3	Providing and filling in planth with sand Crushel dust and hard between the ramming and watering	,			
4 providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work. 1:3:6 (I cement: 13 Coarde sand : 6 graded stone aggregate 20mm nominal size). 5:11½:3 (I cement: 1½ coarse sand: 3 graded stone aggregate 20mm nominal size). 7:12 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using content in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and inxiding its removal at all levels, for etc. complete and inxiding its removal at all levels, for etc. complete and inxiding its removal at all levels, for etc. complete and inxiding its removal at all levels, for etc. complete and inxiding its removal at all levels, for etc. complete and inxiding its removal at all levels, for etc. complete and inxiding formwork inxiding and plinth beam in any shape and size. 8 providing and floors, roofs, access platform, balconi		not exceeding 20cm in depth consolidating each deposited any		1	i	
mixer in foundation, plinth and at ground releve extunding corts. 1:3:61 (cement : 1 Core sand : 6 graded stone aggregate 40mm nominal size). 1:11/2:3 (1 cement : 11/2 coarse sand : 3 graded stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using control in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and including its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. 5 Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 9 Beams, limitels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 9 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: 10 Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing	1					
mixer in foundation, plinth and at ground releve extunding corts. 1:3:61 (cement : 1 Core sand : 6 graded stone aggregate 40mm nominal size). 1:11/2:3 (1 cement : 11/2 coarse sand : 3 graded stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using control in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and including its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. 5 Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 9 Beams, limitels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 9 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: 10 Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing		in I wis coment concrete with crushed stone aggregate using concrete		1		
1.13-6 (1 cement : 11½ coarse sand : 3 graded stone aggregate 20mm nominal size). 2.90 Cum 4073.00 11827.99 1.114:3 (1 cement : 11½ coarse sand : 3 graded stone aggregate 20mm nominal size). 5 Provinding and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form 15.12 Cum 4163.00 62927.91 1:1 1/2 :3 (1 Cement : 1 1/2 coarse sand : 3 graded stone aggregate 20mm nominal size) 5 Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 7 Providing and fixing formwork involuding centering shuttering strutting stageing propping braxing etc. complete and involuding its removal at all levels, for etc. complete and involuding its removal at all levels, for etc. complete and involuding its removal at all levels, for Columns, Pillars, Piers and likes- rectangular or square in shape 12.60 Sqm 297.00 3742.20 12.60 Sqm 297.00 3742.20 12.60 Sqm 297.00 3742.20 32.50 Sqm 235.00 9223.75 32.50 Sqm 235.00 9223.75 4 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to 1S:12894-2002 of class designation 4.0 in foundation and plinth in: 25.60 Sqm 87.00 2059.42 26.71.70 Cum 121.00 2059.42 27.70 Providing and making swater proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 10 Providing and making 6mm thick cement plaster of mix. 11 Providing and making 12mm thick cement plaster of mix. 12 Providing and making 12mm thick cement plaster of mix. 13 In Cement mortar 1:4 (1 cemen	4	providing and laying nominal mix centent concrete with distributions of form work.				17445 70
1:11/4:3 (1 cement : 11/4 coarse sand : 3 graded stone aggregate 20mm nominan subsystem is using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. 1209.60 Kg 54.50 65923.20 1209.60 Kg 54.50 65923.20 1209.60 Kg 54.50 65923.20 1200.60 Jams. Pillars. Piers and likes- rectangular or square in shape 16.00 Sqm 297.00 3742.20 201.60 Jams. Pillars. Piers and likes- rectangular or square in shape 16.00 Sqm 202.00 3232.00 9 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: 10 Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing and making form thick cement plaster of mix: 13 In Cement mortar 1:3 (1 Cement: 5 fine sand) 14 In Cement mortar 1:4 (1 cement: 5 fine sand) 15 In Cement mortar 1:5 (1 cement: 5 fine sand		mixer in foundation, plinth and at ground ever excitating every state of the mixer in foundation, plinth and at ground every excitating every state of the mixer in foundation, plinth and at ground every excitating every state of the mixer in foundation, plinth and at ground every excitating every state of the mixer in foundation, plinth and at ground every excitating every state of the mixer in foundation.	5.87			
5 Provinding and laying nominal mix reinforcement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form using concrete mixer in all works upto floor five level excluding cost of reinforcement and form 1:11/2:3 (ICement:11/2 coarse sand:3 graded stone aggrgate 20mm nominal size) 1:11/2:3 (ICement:11/2 coarse sand:3 graded stone aggrgate 20mm nominal size) 5 Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 Providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. 100 Foundations, footings, base of columns and plinth beam in any shape and size. 100 Foundations, footings, base of columns and plinth beam in any shape and size. 100 Foundations, footings, base of columns and plinth beam in any shape and size. 100 Foundations, footings, base of columns and plinth beam in any shape and size. 100 Foundations, footings, base of columns and plinth beam in any shape and size. 100 Foundations, footings, base of columns and plinth in: 101 Foundation and flies rectangular or square in shape form, balconies (plain surfaces) and shelves (cast in situ) footing and making fly ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: 102 Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) 103 Extra for brick work in superstructure above plinth level for every floor or part thereof in foundation and plinth: 103 Providing and making lamm thick cement plaster of mix: 104 Providing and making 12mm thick cement plaster of mix: 105 In		1:3:6 (1 cement : 3 Coarde sand : 3 graded stone aggregate 20mm nominal size).	2.90	Cum	40/3.00	11027.55
1:1 1/2 :3 (1 Cement :) 1/2 coarse sand : 3 graded stone aggrgate 20mm nominal size) 1:1 1/2 :3 (1 Cement :) 1/2 coarse sand : 3 graded stone aggrgate 20mm nominal size) 5:1 1/2 :3 (1 Cement :) 1/2 coarse sand : 3 graded stone aggrgate 20mm nominal size) 6: Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 7: Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending bending bending bending bending bending bending bending binding etc. complete as per drawings including cost of binding wire all complete. 8: Providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. 6: Sqm 139.00 7872.96 Foundations, footings, base of columns and plinth beam in any shape and size. 7: Sqm 297.00 3742.20 8: Deams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 9: Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: 9: Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) 10: Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 10: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 11: Providing and making form thick cement plaster of mix: 12: Providing and making form thick cement plaster of mix: 13: In Cement mortar 1:4 (1 cement: 4 fine sand) 14: In Cement Mortar 1:5 (1 cement: 5 fine sand) 15: In Cement Mortar 1:5 (1 cement: 5 fine sand) 16: In Cement Mortar 1:5 (1 cement: 5 fine sand) 17: In Cement Mortar 1:3 (1 cement: 3 fine sand) 18:	1	1:1½:3 (1 cement: 1½ coarse sand . 3 graded stone aggregate 2				
1:1 1/2 :3 (1 Cement :) 1/2 coarse sand : 3 graded stone aggrgate 20mm nominal size) 1:1 1/2 :3 (1 Cement :) 1/2 coarse sand : 3 graded stone aggrgate 20mm nominal size) 5:1 1/2 :3 (1 Cement :) 1/2 coarse sand : 3 graded stone aggrgate 20mm nominal size) 6: Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 7: Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending bending bending bending bending bending bending bending binding etc. complete as per drawings including cost of binding wire all complete. 8: Providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. 6: Sqm 139.00 7872.96 Foundations, footings, base of columns and plinth beam in any shape and size. 7: Sqm 297.00 3742.20 8: Deams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 9: Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: 9: Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) 10: Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 10: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 11: Providing and making form thick cement plaster of mix: 12: Providing and making form thick cement plaster of mix: 13: In Cement mortar 1:4 (1 cement: 4 fine sand) 14: In Cement Mortar 1:5 (1 cement: 5 fine sand) 15: In Cement Mortar 1:5 (1 cement: 5 fine sand) 16: In Cement Mortar 1:5 (1 cement: 5 fine sand) 17: In Cement Mortar 1:3 (1 cement: 3 fine sand) 18:		Service Concrete with crushed stone aggregate				
1:1 1/2 :3 (ICement :1 1/2 coarse sand : 3 graded stone aggrgate 20mm nominal state) Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. Thermo-Mechanically treated bars Providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. Foundations, footings, base of columns and plinth beam in any shape and size. Columns, Pillars, Piers and likes- rectangular or square in shape 12.60 Sqm 297.00 3742.20 Columns, Pillars, Piers and likes- rectangular or square in shape 15.60 Sqm 292.00 3232.00 Beams, Intiels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. Providing and making form thick cement plaster of mix: In Cement mortar 1:4 (1 cement: 4 fine sand) Forwiding and making form thick cement plaster of mix In Cement Mortar 1:5 (1 cement: 5 fine sand) Forwiding and making ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	5	Provinding and laying nominal mix reinforcement content content content content of reinforcement and form				
Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 Providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and including its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. 9 Foundations, footings, base of columns and plinth beam in any shape and size. 12.60 Sqm 139.00 7872.96 Foundations, footings, base of columns and plinth beam in any shape and size. 12.60 Sqm 297.00 3742.20 Columns, Pillars, Piers and likes-rectangular or square in shape 16.00 Sqm 202.00 3232.00 Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (east in situ) 39.25 Sqm 235.00 9223.75 9 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (I Cement: 5 Coarse Sand) 25.87 Cum 3350.00 86671.20 Extra for brick work in superstructure above plinth level for every floor or part thereof in 17.02 Cum 121.00 2059.42 10 Extra for brick work in superstructure above plinth level for every floor or part thereof in 17.02 Cum 121.00 2059.42 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion 5.00 Kg 43.50 217.50 12 Providing and making 6mm thick cement plaster of mix: 13 Providing and making 6mm thick cement plaster of mix: 14 In Cement Mortar 1:5 (I cement: 4 fine sand) 19 Providing and making 12mm thick cement plaster of mix: 15 In Cement Mortar 1:5 (I cement: 5 fine sand) 19 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Morta		using concrete mixer in all works upto noor live level exercises 20mm nominal size)	15.12	Cum	4163.00	62927.91
Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth level for every floor or part thereof in addition to rate for foundation and plinth: 7 Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. 8 Providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for expension and stage in any shape and size. 8 providing spiral providing and making high etc. confirming to its its stage propring braxing etc. complete and inxluding at all levels, for expension and shape etc. complete and inxluding etc.		1:1 1/2:3 (1Cement:1 1/2 coarse sand: 3 graded stolle aggregate 201111 Hospitalian stolle				
part thereof in addition to rate for foundation and plinth: Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. Thermo-Mechanically treated bars Providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. Columns, Pillars, Piers and likes- rectangular or square in shape Columns, Pillars, Piers and likes- rectangular or square in shape 10.00 Sqm 202.00 3232.00 Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 39.25 Sqm 235.00 9223.75 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement : 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. Providing and mixing water proofing material in PCC/ RCC work in the proportion for the proportion recommended by the manufacturer. Providing and making form thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) 14 I Smm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 I Smm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and j		the secretary shave plinth level for every floor or	6.89	Cum	97.50	671.78
Providing and placing in position reinforcement for R.C.C. work including straightening cutting bending binding etc. complete as per drawings including cost of binding wire all complete. Thermo-Mechanically treated bars Providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. Columns, Pillars, Piers and likes- rectangular or square in shape 12.60 Sqm 297.00 3742.20 Columns, Pillars, Piers and likes- rectangular or square in shape 15.60 Sqm 202.00 3232.00 Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (I Cement : 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. Providing and making 6mm thick cement plaster of mix: In Cement Mortar 1:5 (I cement: 5 fine sand) Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:5 (I cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	6	Extra for laying PCC/RCC of any grade in superstructure above pintal level as		1		
bending binding etc. complete as per drawings including cost of olding who are temptions and providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for Columns, Pillars, Piers and likes- rectangular or square in shape 112.60 Sqm 297.00 3742.20 Columns, Pillars, Piers and likes- rectangular or square in shape 16.00 Sqm 202.00 3232.00 Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 39.25 Sqm 235.00 9223.75 Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 39.25 Sqm 235.00 9223.75 Suspended floors, roofs access platform, balconies (plain surfaces) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: 25.10 Cement Mortar 1:5 (I Cement: 5 Coarse Sand) 25.87 Cum 3350.00 86671.20 Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 10 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 11 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (I cement: 4 fine sand) 25.60 Sqm 87.00 2227.20 In Cement Mortar 1:5 (I cement: 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (I cement: 5 fine sand) 13 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (I cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		part thereof in addition to rate for foundation and pillul.				
bending binding etc. complete as per drawings including cost of olding who are temptions and providing and fixing formwork including centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for etc. complete and inxluding its removal at all levels, for Columns, Pillars, Piers and likes- rectangular or square in shape 112.60 Sqm 297.00 3742.20 Columns, Pillars, Piers and likes- rectangular or square in shape 16.00 Sqm 202.00 3232.00 Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 39.25 Sqm 235.00 9223.75 Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 39.25 Sqm 235.00 9223.75 Suspended floors, roofs access platform, balconies (plain surfaces) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: 25.10 Cement Mortar 1:5 (I Cement: 5 Coarse Sand) 25.87 Cum 3350.00 86671.20 Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 10 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 11 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (I cement: 4 fine sand) 25.60 Sqm 87.00 2227.20 In Cement Mortar 1:5 (I cement: 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (I cement: 5 fine sand) 13 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (I cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		for R C C work including straightening cutting				
Thermo-Mechanically treated bars Providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. Foundations, footings, base of columns and plinth beam in any shape and size. Columns, Pillars, Piers and likes- rectangular or square in shape Columns, Pillars, Piers and likes- rectangular or square in shape Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Parick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894- 2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement : 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. Providing and making form thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) To Cement Mortar 1:5 (1 cement : 5 fine sand) In Cement Mortar 1:5 (1 cement : 5 fine sand) To Cement Mortar 1:5 (1 cement : 5 fine sand) Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	7	Providing and placing in position reinforcement for receive work including wire all complete.)		
Thermo-Mechanically treated bars providing and fixing formwork inxluding centering shuttering strutting staging propping braxing etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. Foundations, footings, base of columns and plinth beam in any shape and size. Columns, Pillars, Piers and likes- rectangular or square in shape Columns, Pillars, Piers and likes- rectangular or square in shape 12.60 Sqm 207.00 3742.20 Columns, Pillars, Piers and likes- rectangular or square in shape Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Prick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894- 2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement : 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. Providing and making water proofing material in PCC/ RCC work in the proportion for the foundation for the foundation for the foundation for mix: In Cement mortar 1:4 (1 cement: 4 fine sand) 13 Providing and making 12mm thick cement plaster of mix: In Cement Mortar 1:5 (1 cement: 5 fine sand) 14 Ismm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement: 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		bending binding etc. complete as per drawings merdaning cost of the period of the peri				
8 providing and fixing formwork inxluding centering shuttering strutting staging properties etc. complete and inxluding its removal at all levels, for Foundations, footings, base of columns and plinth beam in any shape and size. Foundations, footings, base of columns and plinth beam in any shape and size. Columns, Pillars, Piers and likes- rectangular or square in shape 10.00 Sqm 202.00 3232.00 Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Prick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement : 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. Providing and making form thick cement plaster of mix: In Cement Mortar 1:4 (1 cement : 4 fine sand) To Cement Mortar 1:5 (1 cement : 5 fine sand) 10 Cement Mortar 1:5 (1 cement : 5 fine sand) 11 Cement Mortar 1:5 (1 cement : 5 fine sand) 12 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		and the state of t	1209.60	Kg	54.50	65923.20
etc. complete and inxluding its removal at all levers, for Foundations, footings, base of columns and plinth beam in any shape and size. Foundations, footings, base of columns and plinth beam in any shape and size. Columns, Pillars, Piers and likes- rectangular or square in shape Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894- 2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement : 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		Thermo-Mechanically treated bals				
Foundations, footings, base of columns and plinth beam in any stape and size. Columns, Pillars, Piers and likes-rectangular or square in shape Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894- 2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement: 4 fine sand) Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement: 5 fine sand) 12 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement: 5 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement: 5 fine sand) 14 Ismm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement: 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	8	providing and fixing formwork inxidum contents status and fixing formwork inxidum contents and fixing formwork in the fixing				
Columns, Pillars, Piers and likes- rectangular or square in snape 16.00 Sqm 202.00 3232.00		etc. complete and inxidumg its removal at all relatives.	56.64	Sqm		
Beams, lintels, cantilevers & walls Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) 9 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894- 2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) 10 Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement: 4 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement: 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement: 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		Foundations, 100tings, base of commission programme and pr	12.60	Sqm		
Suspended floors, roofs, access platform, balconies (plan surfaces) and sherves (cast in star) 9 Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894- 2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) 10 Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement: 4 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement: 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement: 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		9	16.00	Sqm		
Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894- 2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement : 5 Coarse Sand) Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		Beams, liniels, cantilevers & Walls Reams, liniels, cantilevers & Walls Reams, liniels, cantilevers & Walls Reams, liniels, cantilevers & Walls	39.25	Sqm	235.00	9223.75
2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) 25.87						
2002 of class designation 4.0 in foundation and plinth in: Cement Mortar 1:5 (1 Cement: 5 Coarse Sand) 25.87	-	Diele work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-				
Cement Mortar 1:5 (1 Cement : 5 Coarse Sand) 17.02 Cum 121.00 2059.42	9	Brick Work Will Indulate Hyusan Into order (1)				
Extra for brick work in superstructure above plinth level for every floor of part flieror in addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		- 1.5 (1 Coment: 5 Coarse Sand)	25.87	Cum		
addition to rate for foundation and plinth: 11 Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) 25.60 Sqm 87.00 2227.20 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		Cement Wortain 1.5 (1 Centers 1.5 County 50 County 1.5 County 50 County 1.5 C	17.02	Cum	121.00	2059.42
Providing and mixing water proofing material in PCC/ RCC work in the proportion recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	10	EXITA IOL DUCK MOLY III subcisit define and plinth.				
recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) 25.60 Sqm 87.00 2227.20 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	1 1					
recommended by the manufacturer. 12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) 25.60 Sqm 87.00 2227.20 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		Partition of mining water proofing material in PCC/ RCC work in the proportion	5.00	Kg	43.50	217.50
12 Providing and making 6mm thick cement plaster of mix: In Cement mortar 1:4 (1 cement : 4 fine sand) 25.60 Sqm 87.00 2227.20 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	11	Providing and mixing water profiting material in 1967 reserved	1			
In Cement mortar 1:4 (1 cement : 4 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		recommended by the manufacturer.	-			
In Cement mortar 1:4 (1 cement : 4 fine sand) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		De 11 de lieu Com thick coment placter of mix				
In Cement mortar 1:4 (1 cement : 4 line said) 13 Providing and making 12mm thick cement plaster of mix In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	12	Providing and making omin unick centeric plaster of this.	25.60	Sqm	87.00	2227.20
In Cement Mortar 1:5 (1 cement : 5 fine sand) 14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 130.68 Sqm 113.00 14766.84 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	اليا	In Cement mortar 1:4 (1 cement . 4 line said)		-		
14 15mm thick cement plaster on the rough side of single or half brick wall of mix: In Cement Mortar 1:5 (1 cement : 5 fine sand) 130.68 Sqm 113.00 14766.84 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	13	Providing and making 12mm inick cement plaster of thix	142.20	Sam	96.50	13722.30
In Cement Mortar 1:5 (1 cement : 5 fine sand) 130.68 Sqm 113.00 14766.64 15 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		In Cement Mortar 1:5 (1 cement : 5 line sand)				5
15 Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	14	15mm thick cement plaster on the rough side of single of half office wan of this.	130.68	Sam	113.00	14766.84
make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per		In Cement Mortar 1:5 (1 cement : 5 fine sand)	200.00			
Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per	15	Providing and fixing ceramic glazed wall tiles conforming to 15: 13022 of approved	ł			
Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement sturry (@ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.		make, colours, shades and size on wall and dados over 12 mm thick bed of cement	ı	1	1	
sqm including pointing in white cement mixed with matching pigment complete.		Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement sturry (@ 3.3kg per		l		
	لـــا	sqm including pointing in white cement mixed with matching pigment complete.				

16	Size upto 200x300mm	34.20	Sqm	587.00	20075.40
ľ	Providing and laying ceramic glazed floor tiles conforming to IS: 15622 of approve	d			1
m	size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement: 4 coars	e			1
The same of	sand) including pointing the joints with white cement mixed with matching pigment etc	.,	1		
	complete				
	Size 300x300mm	21.90	Sqm	692.00	15154.80
17	14.51 Providing and applying 2mm thick ready mix exterior grade putty (manufactured with cov	v 272.08	sqm	101.00	27480.08
- (dung processing) on wall to make the surface smooth and even.				
18	14.49 wall painting with premium emulsion (plastic)manufactured with cow dung processing	g			
(emulsion paint of required shade to give an even shade.				
	14.49.1 on new work (two or more coats)	141.40	sqm	69.00	9756.60
	14.50 painting exterior surface with SMOOTH exterior emulsion paint manufactured with the			1	1
	cow dung processing to give protective and decorative finish including cleaning washing of	ıl .		*	1
	surface etc. complete with:				
	14.50.1 on new work (tow or more coats applied @1.43ltr/10sqm over	130.68	sqm	79.00	10323.72
20	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron	250.00	kg	75.00	18750.00
	diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and	l			
	corners, all necessary fittings complete including applying a priming coat of red oxide zinc				
	chromate primer.		 	67.50	6310.00
21	Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars	92.00	kg	67.50	6210.00
	welded to steel frame of windows etc. including applying a priming coat welded to frame with all				
r	necessary fitting complete including applying a priming of red oxide zinc chromate primer.				1
			 	 	
	14.22 Painting on new work (two or more coats) to give an even shade with	24.00		FF 00	1873.08
	Satin synthetic enamel paint	34.06	Sqm	55.00	18/3.08
	8.17 Providing and fixing vitreous china wash basin with C.I. brackets, 32 mm C.P. brass waste				
	of standard pattern, including painting of brackets, cutting and making good the walls wherever		-	1	
Ire	equired :		1		
	Vhite Size 550x450 mm	4.00	each	1430.00	5720.00
	8.25 Providing and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C.	4.00	eacii	1430.00	3720.00
	vaste fittings complete.			1	
	8.25.1 32 mm dia	6.00	each	68.50	411.00
	9.14 Providing and fixing 15 mm nominal bore C.P. brass fittings of approved make and	0.00	cuen	55.55	722.00
	onforming to IS:8931 including C.P. brass extension if required:				
	9.14.1 Bib cock (400 grams)	4.00	each	382.00	1528.00
$\overline{}$	9.14.4 Piller Cock (400 grams)	6.00	each	398.00	2388.00
	9.14.6 Stop cock (concealed) (600 grams)	4.00	each	494.00	
	9.15 Providing and fixing stainless steel drain jali of approved make/quality				1976.00
		10.00	each	51.00	1976.00 510.00
4/ [1]		10.00			
	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe	10.00			
fo	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability	10.00			
fo w	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe	10.00			
fo	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC	10.00			
fo wi so	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC olvent cement and testing of joints complete as per direction of Engineer in Charge.	10.00			
fo wi so	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC	15.00		51.00	510.00
fo wi so	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC olvent cement and testing of joints complete as per direction of Engineer in Charge.		each	51.00	510.00
fo wi so 19	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC olvent cement and testing of joints complete as per direction of Engineer in Charge. 9.4.1)15 mm nominal outer dia .Pipes.	15.00	each	51.00	510.00
19 19 28 Pr	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC olvent cement and testing of joints complete as per direction of Engineer in Charge. 9.4.1)15 mm nominal outer dia .Pipes. 9.4.3)25 mm nominal outer dia .Pipes.	15.00	each	51.00	510.00
19 19 28 Pr	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe in the clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC olvent cement and testing of joints complete as per direction of Engineer in Charge. 9.4.1)15 mm nominal outer dia .Pipes. 10.4.3)25 mm sominal outer dia .Pipes.	15.00	each	51.00	510.00
19 19 28 Pr pij (4)	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain between the clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain between the clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain between the pipes with one step CPVC plain between the pipes in the clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain between the pipes in the pipe	15.00	each	51.00	510.00
19 19 28 Pr pip (4) lea	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC olivent cement and testing of joints complete as per direction of Engineer in Charge. 9.4.1)15 mm nominal outer dia .Pipes. 9.4.3)25 mm nominal outer dia .Pipes. 19.4.3)25 mm nominal outer dia .Pipes. 19.4.4 pipes (single socketed) having 3.2mm wall thickness conforming to IS : 13592 kg/sqcm) including required couplers, jointing with seal ring conforming to IS : 5382	15.00	each	51.00 110.00 199.00	510.00 1650.00 4975.00
19 19 28 Pr pip (4) lea	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain & brass threaded fittings i/c fixing the pipe includes jointing of pipes & fittings with one step CPVC plain & brass per direction of Engineer in Charge. 9.4.1)15 mm nominal outer dia .Pipes. 10.4.3)25 mm nomi	15.00 25.00	metre metre	51.00	510.00
19 19 28 Pr pip (4) lea 11	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain & brass threaded fittings i/c fixing the pipe including of pipes & fittings with one step CPVC plain & brass threaded fittings i/c fixing the pipe including and testing of joints complete as per direction of Engineer in Charge. 9.4.1)15 mm nominal outer dia .Pipes. 9.4.3)25 mm nominal outer dia .Pipes. 19.4.3)25 mm nominal out	15.00 25.00	metre metre	51.00 110.00 199.00	510.00 1650.00 4975.00
19 19 28 Pr pip (4) lea 11 19 Pro acc	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC olvent cement and testing of joints complete as per direction of Engineer in Charge. 9.4.1)15 mm nominal outer dia .Pipes. 9.4.3)25 mm nominal outer dia .Pipes. 10.4.3)25 mm nominal outer dia .Pipes. 10.4.3)25 mm nominal outer dia .Pipes. 10.4.3)25 mm nominal outer dia .Pipes. 10.4.3)26 mm nominal outer dia .Pipes. 10.4.3)27 mm vall face or under floor UV stabilized Unplasticised Rigid PVC pipes (single socketed) having 3.2mm wall thickness conforming to IS : 13592 kg/sqcm) including required couplers, jointing with seal ring conforming to IS : 5382 aving 10 mm gap for thermal expansion etc complete. 10.4.7 mm dia pipe. 10.4.8 oviding and fixing on wall face UV stabilized Unplasticised - PVC moulded fittings/cessories having 3.2mm wall thickness for Rigid PVC pipes conforming to IS : 13592	15.00 25.00	metre metre	51.00 110.00 199.00	510.00 1650.00 4975.00
19 19 28 Pr pip (4) lea 11 29 Pro acc (he	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with seal fixing on wall face or under floor UV stabilized Unplasticised Rigid PVC plain & brass threaded fittings with seal ring conforming to IS : 5382 plain fixing on wall face UV stabilized Unplasticised - PVC moulded fittings/cessories having 3.2mm wall thickness for Rigid PVC pipes conforming to IS : 13592 plain with seal ring conforming to IS : 5382 plain plain with seal ring conforming to IS : 5382 plain pl	15.00 25.00	metre metre	51.00 110.00 199.00	510.00 1650.00 4975.00
19 19 28 Pr pip (4) lea 11 29 Pr acc (he ex)	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with seal fixing on wall face or under floor UV stabilized Unplasticised Rigid PVC plain & brass threaded fittings with seal fixing plain fixing thread fittings with seal fixing on wall face UV stabilized Unplasticised - PVC moulded fittings/cessories having 3.2mm wall thickness for Rigid PVC pipes conforming to IS: 13592 plans with seal fixing conforming to IS: 5382 plans for thermal plansion.	15.00 25.00	metre metre	51.00 110.00 199.00	510.00 1650.00 4975.00
19 19 28 Pr pip lea 11 29 Pr acc (he ex)	9.4 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability or hot & cold water supply including all CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain & brass threaded fittings i/c fixing the pipe ith clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with one step CPVC plain & brass threaded fittings with seal ring conforming to IS in 13592 kg/sqcm) including required couplers, jointing with seal ring conforming to IS in 13592 with plain fixing on wall face UV stabilized Unplasticised - PVC moulded fittings/cessories having 3.2mm wall thickness for Rigid PVC pipes conforming to IS in 13592 plans with seal ring conforming to IS in 13592 plans with seal ring conforming to IS in 13592 plans with seal ring conforming to IS in 13592 plans with door/Bend 45°/Bend 90°	15.00 25.00	metre metre	51.00 110.00 199.00	510.00 1650.00 4975.00

Ÿ c

	18.1 Providing and fixing water closet squatting pan (Indian type W.C. pan), 100mm sand cast Iron P or S trap, 10 litre low level P.V.C. flushing cistern (same colour) conforming to IS: 7231, with flush bend and other fittings and fixtures complete including cutting and making good the walls and floors wherever required:				
30401032	18.1.3 White Orissa pattern W.C. pan of size 580x440 mm	6.00	each	2899.00	17394.00
31	18.13 Providing and fixing white vitreous china urinal basin with waste fitting as per IS: 2556,				
	and other couplings in C.P. brass complete:	2.00	each	1529.00	3058.00
	18.13.2 Flat back type urinal of size 460x380x250mm	2.00	each	1659.00	3318.00
	18.13.3 Wall corner type urinal of sizes 340x410x265mm	2.00			
32	19.42 Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI: 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank	1000.00	liter	7.30	7300.00
	m. I	A	An Par	S.O.R. Rs.	483757.04
-	Total	Amount	lectrica	work Rs.	16243.00
				mount Rs.	500000.00

Sub Engineer Municipal Corporation Korba (C.G.)

Asst. Engineer Municipal Corporation Korba (C.G.)

OFFICE OF THE MUNICIPAL CORPORATION, KORBA (C.G.) Abstract

Electrification Work PWD (Elec. 01.06.2020)

No	Ref.	Item of Work	Unit	Rate	Qty	Amount
1	2.7	Wiring for light/ fan/ exhaust fan / call bell point with 3x1.5 sqmm FRLS PVC insulated stranded copper conductor wire for phase, neutral and earth in surface FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) with 5/6 amp modular switch, modular base and cover plate, suitable size G.I. box as per specification and IS: 694 (2010), IS. 9537 (2000 Part 5)				
	2.7.1	Short Point	Point	227.00	2.00	454.00
	2.7.2	Modium Delat	Point	347.00	2.00	454.00 694.00
	2.7.3	Long Point	Point	465.00	1.00	465.00
2	2.11	Wiring for power plug point with 3x4 sq mm FRLS PVC insulated stranded copper conductor wire for phase, neutral and earth in surface FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) along with modular type 16 Amp switch and 6 pin 16 amps socket outlet with modular base and cover plate, suitable size G.I. box, earthing the switch box and socket outlet with same size wire etc. as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)				
	2.11.2	Medium Point	Doint	017.00	4.00	
3	2.13	Wiring for circuit/ sub main wiring along with earth wire with the following sizes of FRLS PVC insulated copper conductor, wire in surface FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) etc as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)	Point	817.00	1.00	817.00
	2.13.2	3 X 2.5 sq. mm in 20mm conduit	Metre	87.00	25.00	2175.00
4	5 4	Supplying and fixing following modular switch, socket, other accessories on the existing modular plate & switch box including connections but excluding modular plate etc. as per specification.	Wietre	07.00	23.00	2175.00
		Fan regulator (two module size) electronic stepped type moving all rounds	Each	223.00	2.00	446.00
		Ceiling rose 3 pin 5 amp	Each	40.00	2.00	80.00
		Batten/ angle holder	Each	41.00	2.00	82.00
-		3 pm 5/6 amp socket outlet	Each	96.00	2.00	192.00
5		5/6 amps one way switch	Each	69.00	2.00	138.00
3	0.5	Supplying installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.				
	6 1.3	1200 mm sweep				
6	- 1	Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio ≥ 100 lumens /watt	Each	1697.00	2.00	3394.00
_	-	15 Watt	Each	210.00		
		18/20 Watt (LED Rod)		249.00	2.00	498.00
7		Supplying and fixing on surface/ recess horizontal type following way, 415 volts, TPN MCB distribution board of sheet steel phosphatized and powder painted, complete with tinned copper busbar, neutral busbar, earth bar, din bar, detachable gland plate, including interconnections, earthing etc. as per specification. (But without MCB/RCCB/Isolator)		266.00	2.00	532.0
é	9.4.1	4 way Single door				
			Each	1317.00	1.00	1317.0

3		Supplying and fixing SP MCB, 240 volts, 'B' curve, suitable for lighting and other loads in the existing MCB DB complete with connections, testing and commissioning etc. as per specification.		-		
The same of the sa	2 10 1		8-	1		.= 3
	3.10.1	6 amps to 32 amps	Each	151.00	3.00	453.00
g		Providing and fixing metal clad, SP&N switch fuse unit (re-wirable), 230/250 volts, with porcelain re-wireble fuses including drilling holes on the board, connections, earthing the body etc. as per specification. (Thimbeling shall be paid separately).				
3 7	7.0.1	22	Each	978.00	1.00	978.00
-	12.1	32 amps Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal and salt as per specification and IS Code 3043: 1987(R 2016)	Set	3243.00	1.00	3243.00
11 1	12.18	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing along with existing surface/ concealed conduit/ submain wiring/ cable as per specification.	Metre	19.00	15.00	285.00
				T	otal Rs.	16243.00

Sub Engineer
Municipal Corporation, Korba
(C.G.)

Assitt. Engineer Municipal Corporation, Korba (C.G.)