

### कार्यालय, नगर पालिक निगम, कोरबा (छ.ग.)

मुख्य कार्यातय - साकेत भवन, वाई.टी.वाई. चौक, कोरवा (छ.म.)

कोरवा जोन

फा.क. / 173,174,175,176,177,178,179,180 एवं 181 / निर्माण (कोरवा जोन) / 2024 /

कौरवा, दिनांक 18.09.2024

### निविदा आमंत्रण की सूचना

लोक निर्माण विभाग से एकीकृत पंजीयन प्रणाली अंतर्गत सक्षम श्रेणी में पंजीकृत ठेकेदारों से निम्नलिखित कार्य हेतु प्रमुख अभियन्ता लोक निर्माण विभाग, रायपुर द्वारा प्रचलित PWD Building SOR 01.01.2015 & PWD Electrical SOR 01.06.2020 से प्रभावशील दर अनुसूची पर (निविदा खुलने के दिनांक तक समस्त संशोधनों के साथ) कम अधिक या समान दरों पर तथा शेड्युल अनुसार आयटम दरों पर निम्नलिखित निर्माण कार्य हेतु मैन्युअल निविदा वैबसाईट से डाउनलोड कर मुहरबंद लिफाफा में निविदा आमंत्रित की जाती है:—

निर्धारित प्रारूप में निविदा प्रपत्र प्राप्त होने की अंतिम तिथि – 09.10.2024 सायंकाल 3:00 बजे तक

2. निविदा खुलने की अंतिम तिथि

- 09.10.2024 सायंकाल 4:30 बजे

-		,	,					
Ø.	कार्य का नाम	प्राक्कलन	धरोहर	निविदा	निविदा	कार्यावधि	ठेकेदार	निविदा
		राशि में	राशि रू	प्रपत्र	प्रपत्र		का वर्ग	खुलने की
-			में	का मूल्य				अंतिम तिथि
	वार्ड क्र. 04 इंदिरा नगर में							
1	सी.सी. रोड् व नाली निर्माण	10,00,000/-	7,500 /-	750/-	Form-A	04 माह	सक्षम	09.10.2024
	कार्य। (अघोसंरचना मद 7.00			100	FORM-A	04 416	श्रेणी	
	करोड, 2024—25)							
	वार्ड क्र. ०९ वरवसपुर							
2	हाउसिंग बोर्ड कालोनी में शेड	5,00,000/-	5,000 /-	750/-		00 7777	सक्षम	09.10.2024
-	निर्माण कार्य। (अघोसंरचना	5,00,000/-	3,0007	750/-	Form-A	03 माह	श्रेणी	09.10.2024
	मद 7.00 करोड, 2024-25)							
	वार्ड क्र. ०९ रापाखरी धीवर							
	मोहल्ला में सी.सी. रोड निर्माण	7,00,000/-	5.500 /	750/		03 माह	सक्षम श्रेणी	
3	कार्य। (अधोसंरचना मद 7.00	7,00,000/-	5,500 /-	750/-	Form-A			09.10.2024
	करोड, 2024—25)							
	वार्ड क्र. 09 रापांखरी बस्ती में							
	मुक्तिधाम निर्माण कार्य।						सक्षम	
4	(अधोसंरचना मद 7.00 करोड,	8,00,000/-	6,000 /-	750/-	Form-A	03 माह	अंग <u>ी</u>	09.10.2024
	2024–25)			x.			4-11	
	वार्ड क्र. 11 नई बस्ती में							
and the same of th	लक्ष्मणबन तालाब काली मंदिर						110-11	
5	के पास सांस्कृतिक मंच	6,00,000/-	4,500 /-	750/-	Form-A	०३ माह	सक्षम	09.10.2024
	निर्माण कार्य। (अघोसंरचना	, , , , , , , , , , , , , , , , , , , ,	1,000	, , ,	rorm-A	03 716	श्रेणी	W7:1VeaUan
	मद 7.00 करोड, 2024-25)							
-	वार्ड क. 09 देलवाडीह में						A COURSE OF STREET	
	किशन बंधेल घर के पास							
6	सांस्कृतिक मंच निर्माण कार्य।	5,00,000/-	£ 000 c	7701			सक्षम	
0		5,00,000/-	5,000 /-	750/-	Form-A	०३ माइ	भेणी	09.10.2024
	(अघोसंरचना मद 7.00 करोड,						24.48	
-	2024-25)							
	वार्ड क्र. 07 सीतामणी		O COLOR					
	मोतीसागरपारा कोरबा में		11,500 /-	and the same of th				
7	आश्रय होटल के पीछे	15,00,000/-		750/- Form-A		1-A 04 HTS	सक्षम् भेजी	
and the same	सामुदायिक भवन निर्माण।	w solar A A A A A A A			Form-A			69.10.2024
9	(अपोसंरचना मद 7.00 करोड,						- F - F - F	No. of the last of
	2024-25)						E 1000	

	/							
8	वार्ख क्र. 05 भावना चौहान के पर रो लेकर प्रार्थना साहू के घर तक सी.सी. रोड एवं नाली निर्माण कार्य। (अधोरांरचना मद 7.00 करोड, 2024–25)		9,000 /-	750/-	Form-A	04 माह	सक्षम श्रेणी	09.10.2024
9	वार्ड क्र. 06 क्षेत्रांतर्गत पुरानी बरती स्थित सियान सदन के उपर छत में शौचालय एवं बाध सहित हॉल एवं स्टोर निर्माण कार्य। (अधोसंरचना मद 7.00 करोड, 2024–25)	10,00,000/-	7,500 /-	750/-	Form-A	04 माह	सक्षम श्रेणी	09.10.2024

#### निविदा की शर्ते:-

1. निविदा दरे प्रचलित् सी.एस.आर.से कम या अधिक् प्रतिशत् दरों पर दिया जावे सी.एस.आर.के अंतर्गत के

आयटमों पर पृथक से आयटम दरों का उल्लेख करने पर निविदा निरस्त मानी जावेगी।

निविदा के दस्तावेज रजिस्टर्ड पोस्ट अथवा स्पीड पोस्ट से भेजना होगा अन्य माध्यमों यथा कोरियर सर्विस, साधारण डाक इत्यादि से प्राप्त अथवा समयाविध के पश्चात् प्राप्त निविदाओं पर विचार नहीं किया जावेगा। निविदा आयुक्त, नगर पालिक निगम, आई.टी.आई. चौक साकेत भवन, जिला-कोरबा (छ.ग.) पिन नं.-495677 के पते पर भेजना होगा। निर्धारित तिथि को सायं 3:00 के पश्चात प्राप्त निविदाएँ स्वीकार नहीं किए जावेंगे।

निविदा प्रपूत्र नुगर पालिक निगम, कोरबा के वेबसाईट www.korbamunicipal.in/uad.cg.gov.in डाउनलोड किया जाकर नवीन निविदा प्रपन्न Form - A/B/ABC (जारी दिनॉक तक समस्त संशोधनों के साथ) आयुक्त, नगर पालिक निगम, कोरबा के नाम पर देय निर्धारित शुल्क की डीडी के साथ संबंधित कार्य का नाम पूर्ण विवरण सहित भरकर भेजना

निविदा मुहरबंद लिफाफा में मान्य किया जावेगा जो निम्नानुसार होगा:--

प्रथम लिफाफा में ठेकेदार का जीवित पंजीयन प्रमाण पत्र, आयकर चुकता प्रमाण पत्र, निविदा सूचना आमंत्रण में उल्लेखित अन्य दस्तावेज के साथ निर्धारित निविदा प्रपत्र शुल्कू का डीडी, निविदाओं में निविदाकार को फिजिकल दस्तावेज के साथ निविदा सूचना प्रसारित होने के पश्चात् राशि रू. 100/- के स्टॉम्प पर निष्पादित शपथ पत्र जिसमें संबंधित कार्य का नाम एवं कार्य की निविदा क्रमांक अंकित हो प्रेषित करना अनिवार्य होगा एवं अमानत राशि का टी.डी.आर./एफ.डी.आर. जो कि आयुक्त, नगर पालिक निगम कोरबा के नाम पर देय होगा प्रस्तुत

द्वितीय लिफाफा में ठेकेदार द्वारा भूरा हुआ निविदा प्रपत्र होगा।

(स) तृतीय लिफाफा में उपरोक्त दोनो लिफाफे होंगे तथा आवश्यकता पड़ने पर मूल अभिलेख प्रस्तुत करना होगा। जिन ठेकेदारों द्वारा नगर पालिक निगम, कोरबा के किसी ठेके के कार्य में अनुबंध के अनुरूप कार्य न किया गया हो अथवा नगर पालिक निगम, कोरबा के हित के विरूद्ध कार्य किया गया हो उन्हे निविदा भरने की पात्रता नहीं होगी। निविदा हेतु इच्छुक ठेकेदारों को उचित वर्ग में पंजीयन की प्रमाणित प्रतिलिपि यदि साझेदारी फर्म हो तो उसका प्रमाण पत्र (पार्टनरशीप डीड) की सत्य प्रतिलिपि, उपलब्ध तकनीकी अमले की जानकरी पिछले 03 वित्तीय वर्षों का आय चुकता प्रमाण पत्र, पेन नम्बर, जी.एस.टी. (जीवित) पंजीयन एवं प्रशिक्षित यंत्री नियुक्त करने संबंधी प्रमाण पत्र, कर्मचारी मिविय निविद्य त्यविवर्ष के सत्य प्रतिलिपि, राज्य बीमा निगम रायपुर से पंजीयन एवं विस्तृत निविदा आमंत्रण सूचना ठेकेदार के हस्ताक्षर सहित

निविदा दस्तावेजों के साथ प्रस्तुत करना अनिवार्य होगा। 7. कार्य हेतु लिफाफे पर कार्य का नाम निविदा आमंत्रण सूचना कमॉक, निविदा खुलने की तिथि स्पष्ट रूप से लिखकर भेजना

निविदाकार का यह दायित्व है कि वे निविदा भरने के पूर्व स्थल का स्वयं निरीक्षण कर लेवें ताकि प्रारंभ करने में किसी प्रकार की कठिनाई न हो।

निर्धारित निविदा प्रपत्र में उल्लेखित कंडिका स्वमेव लागू मानी जावेगी एवं निविदा आमंत्रण सूचना निविदा का ही भाग

10. निर्धारित प्रारूप में निविदा प्रपत्र, निविदा प्रपत्र शुल्क, अमानत राशि, निविदा आमंत्रण सूचना पत्र में उल्लेखित दस्तावेज सही पाए जाने पर ही निविदा दर संबंधी लिफाफा खोला जावेगा अन्यथा निविदा निरस्त कर दी जावेगी।
11. ठेकेदार को अपनी दरें शब्दों एवं अंको में लिखना अनिवार्य होगा।

12. शासन के विभिन्न विभागों ज़ैसे:— खुजिन विभाग, श्रम विभाग, समाज कृत्याण विभाग इत्यादि विभागों द्वारा समय-समय पर जारी निर्देशों/आदेशों के पालन की समस्त जिम्मेदारी संबंधित ठेकेदार की होगी। 13. ठेकेदार यदि कार्य को अपूर्ण रिथति में छोड़ता है तो निविदा प्रपन्न में उल्लेख अनुसार इस संबंध में प्रावधान

के अंतर्गत कार्यवाही की जावेगी।

क अतगत काववाहा का जावना।

14. कार्य प्रारंभ नहीं करने अथवा अपूर्ण स्थिति में छोड़ने पर निगम द्वारा ठेकेदार के विरुद्ध निविदा शर्तानुसार एवं मेयर इन काउंसिल के निर्णयों के अनुरूप कार्यवाही की जावेगी जिसकी संपूर्ण जवाबदारी ठेकेदार की होगी।

15. सफल निविदा दाता से अनुबंध के समय अतिरिक्त परफार्मेंस राशि जमा कराई जावेगी जबकि निविदा की दरों में काफी कमी हो जैसे निविदादाता को निविदा दर एवं अनुमानित लागत से 10 प्रतिशत से अधिक निविदा दर स्वेत पर प्रारंभ के उपलब्ध के समय स्वेत स्वारंभ के सम्बन्ध के सम्बन्ध के सम्बन्ध के सम्बन्ध के सम्बन्ध के सम्बन्ध के स्वारंभ के सम्बन्ध के सम्य के सम्बन्ध के सम् होने पर राफल निविदादाता को निविदा दर एवं अनुमानित लागत के 90 प्रतिशत अंतर की राशि के समतुल्य परफार्मेंस गारंटी के रूप में राष्ट्रीयकृत बैंक का एफ.डी.आर. / टी.डी.आर. ऑफ्रिस अथवा टाईम डिपॉजिट जो कि आयुक्त नगर पालिक निगम कोरबा के नाम से देय होगा, जो मांग तिथि से 15 दिवस के भीतर जमा करना

//03// अनिवार्य होगा। उपरोक्त राशि को जमा न करने की दशा में निविदा निरस्त कर दी जावेगी।

18. सम्पूर्ण किये गये कार्यों के लिये 5 प्रतिशत की दूर से सुरक्षा राशि रूनिंग देयकों के साथ 01 वर्ष हेतु साथ ही मुरम्मत एवं संघारण प्रकृति के कार्यों को छोड़कर शेष कार्यों के देयकों से 5 प्रतिशत की दर से पृथक से 03 वर्ष की गारंटी के लिये परफानेंस सिक्यूटिटी के रूप में रोकी जायेगी। सुरक्षा राशि एवं परफारमेंस गारंटी राशि वापसी हेतु समयाविध की गणना कार्य पूर्णता तिथि से किया जायेगा। उक्त समयाविध में निर्माण कार्य की भौतिक स्थिति सही होने तथा सक्षम प्राधिकारी के संतुष्टि के आधार पर भुगतान किया जायेगा।

17. निविदा में भाग लेने वाँले टेकेदारों को छ.ग. भवन और अन्य सन्निर्माण कर्मकार (नियोजन एवं सेवा शूर्तों का विनियमन) अधिनियम 1996 एवं तद्श्रंतर्गत् निर्धारित नियमों के तहत् पंजीयन कराना आवश्यक होगा तथा निर्माण लागत का

1 प्रतिशत उपकर के रूप में प्रत्येक देयक से कटौती की जावेगी।

18. निविदाकार को प्रत्येक निविदा में पंजीयन क्षमता के अंतर्गत वर्तमान में नगर निग्म या अन्य विभागों में किये जा रहे कार्यों का विवरण राशि सहित राशि रू. 100/- नॉन ज्यूडिशियल स्टॉम्प पेपर पर निष्पादित शपथ पत्र निविदा दस्तावेजो के साथ संलग्न करना अनिवार्य होगा।

19. ईंट से संबंधित निर्माण कार्यों में फ्लाई एश ब्रिक का उपयोग किया जाना अनिवार्य होगा।

20. निविदा प्रपत्र अहस्तांतरणीय होगा एवं संशर्त निविदाओं पर विचार नही किया जावेगा।

21. निविदा के संबंध में किसी प्रकार की विवाद होने की स्थिति में आयुक्त, नगर पालिक निगम कोरबा का निर्णय अंतिम एवं

सर्वमान्य होगा।

22. निविदा में सफल निविदाकार को ऐसे कार्य जिसकी अनुवंध राशि 10.00 लाख या उससे अधिक है, उनको प्रत्येक कार्यों हेतु पृथक से छ.ग. भवन और सन्निर्माण कर्मचार मण्डल का पंजीयन प्रमाण पत्र प्रस्तुत करना अनिवार्य होगा अन्यथा देयक भुगतान् किया जाना संभव नहीं होगा।

23. कार्य कियान्वयन से संबंधित गुणवत्ता परीक्षण संबंधी रिपोर्ट पर होने वाले व्यय का वहन संबंधित ठेकेदार द्वारा किया

24. ठेकेदार को निर्माण कार्य के दौरान "निर्माण एवं अपशिष्ट प्रबंधन नियम 2016" में किये गए प्रावधानों का पालन करना

25. ठूँकूदार द्वारा संपादित किये गए कार्यों के देयकों का भुगतान वजट आवंटन और राशि उपलब्ध होने पर किया जाएगा।

26. निविदा स्वीकृत करने अथवा अस्वीकृत करने का अधिकार आयुक्त, नगर पालिक निगम के पास सुरक्षित रहेगा।

27. निविदा खुलने की तिथि में अवकाश होने पर आगामी तिथि (कार्य दिवस) को निविदा संबंधी कार्यवाही मानी जावेगी।

प्रोग्रामर, संचालनालय, नगरीय प्रशासन एवं विकास विमाग, नया रायपुर (छ.ग.) को Uad.cg.gov.in में अपलोड प्रतिलिपि :--किये जाने हेत् प्रेपित।

(ठेकेदार के हस्ताक्षर)

पूर्ण पता .....

मोबाईल नं.- .....

नुगुर पालिक निगम कोरबा (छ.ग.)

## OF THE MUNCIPAL CORPORATION, KORBA (C.G.) ABSTRACT

Construction of Cultural Manch At Near Kishan Bghel Home Dhelwadih Ward

Schedule of rates public works department[PWD BUILDING-01-01-2015]

	Ref.	THE DESCRIPTION	QTY	וואט	Darr	
	1.	Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of pits.		ONI	RATE	AMOUNT
		In all types of soil	30.47	Cum	185.00	5636.95
2		Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.		,	700,00	<i>5</i> 5.55.85
		1:4:8 (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size).	7.35	Cum	2659.00	19543.65
3		Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:				
		Foundations, footings, base of columns and plinth beam in any shape and size.	33.60	Sqm	139.00	4670.40
		Columns, Pillars, Piers and likes- rectangular or square in shape	14.50	sqm	297.00	4306.50
		Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ)	52.38	sqm	235.00	12309.30
		Beams, lintels, cantilevers & walls	35.40	sqm	202.00	7150.80
4		Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.				
		1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	18.96	Cum	4163.00	78930.48
5		Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in foundation and plinth all complete:				
	1	Thermo-Mechanically treated bars FE 415	1858.08	Kg	54.50	101265.36
6		Brick work with modular fly-ash lime bricks (FaLG Bricks) confirming to IS:12894-2002 of class designation 4.0 in foundation and plinth in:				
		Cement Mortar 1:5 (1 cement : 5 coarse sand)	25.63	Cum	3350.00	85860.50
7	7.6	Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth:	14.616	Cum	121.00	1768.54
8		Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work.				
		1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).	1.80	Cum	4073.00	7331.40
9	9.13	Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete including applying a priming coat of red oxide zinc chromate primer.	105.90	Kg	75.00	7942.50

		NIT				
		ITEM DESCRIPTION	QTY	UNIT	RATE	AMOUNT
		ng and fixing in position collapsible steel shutters with channels 20x10x2mm and braced with flat iron diagonals 5mm size with top and bottom rails of T-iron 40x40x6mm with 38mm steel pulleys complete with bolts, nuts, locking arrangement stoppers, handles including applying a priming coat of red oxide zinc chromate primer.	7.92	Sqm	3330.00	26373.60
1	11.1	Providing and making 6mm thick cement plaster of mix				
		n Cement mortar 1:4 (1 cement : 4 fine sand)	44.28	Sqm	87.00	3852.36
12	11.2	Providing and making 12mm thick cement plaster of mix				
	4 1	n Cement Mortar 1:6 (1 cement : 6 fine sand)	85.46	Sqm	91.50	7819.59
13		Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix:				
		n Cement Mortar 1:6 (1 cement : 6 fine sand)	168.21	Sqm	107.00	17998.47
14		Providing and laying vitrified floor tiles with double charge/ multicharge printing with water absorption less than 0.5% and conforming to IS: 15622 of approved make in all colours and shades and size mentioned below (+/- 10mm), laid on 20mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joints with white cement and matching pigments etc. complete.				
	1	Size 600x600mm	41.04	Sqm	1151.00	47237.04
15	12.7	Providing and fixing ceramic glazed wall tiles conforming to IS: 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete.				
	2	Size above 200x300mm	4.12	Sqm	646.00	2661.52
16	14.13	approved make putty (like Birla wall care, Alltek Superfine W/R of (NCL), Asian, ICI, Nerolac, J.K. wall putty) on walls to make the surface smooth and	297.95	Sqm	94.50	28156.28
1	7 14.	1 Wall painting with acrylic premium emulsion (plastic) paint of				
	-	required shade to give an even shade.  1 On new work (Two or more coats)	129.74	Sqm	44.50	5773.43
1	8 14.1	4 Finishing walls with water proofing cement paint of required shade to give an even shade.	124 (4)	La CALC		. 并作《深刻
	-	1 On new work (Two or more coats )	125.30	Sqm	41.00	5137.30
1 -		· · · · · · · · · · · · · · · · · · ·				101707.00

Total = 481725.96

Total = 401125.50

FIC. Work= 18274=000

Total => 4,99,999=96

Eary De > 5,00,000=00

Sub Efigineer Municipal Corporation Korba (C.G.)

Asstr Engineer Municipal Corporation Korba (C.G.)

# OFFICE OF THE MUNICIPAL CORPORATION, KORBA ( C.G.) ABSTRACT

Work <u>ELECTRIFICATION WORK OF CULTURAL MANCH AT NEAR KISHAN BAGHEL HOME DHILWADIH WARD NO.-09.</u>
SOR :SCHEDULE OF RATES PUBLIC WORKS DEPARTMENT [PWD ELECTRICAL-01-06-2020]

1 1.1 Wiring for light/ fan/ exhaust fan / call bell point with 3x1 5 sgmm RRUS PVC insulated stranded copper conductor wire for phase, neutral and earth in concealed FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) with 5x6 amp piano type switch, phenolic laminated sheet, suitable size with 5x box etc as per specification and Its. 694 (2010), IS: 9537 (2000 Part 5)  1.1 Short Point P	EN	REF	ITEM DESCRIPTION	1-00-2020	)j		
concealed FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) with 5/6 amp piano type switch, phenolic laminated sheet, suitable size M.S. box etc as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  1.1. Short Point 4.00 240.00 960  1.1. Short Point 90 Mcdium Point Point 90 Mcdium 90 Mc	5.N	A MATERIAL PRODUCTION OF THE PARTY OF THE PA		UNIT	QTY	RATE	AMOUNT
concealed FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) with 5/6 amp piano type switch, phenolic laminated sheet, suitable size M.S. box etc as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  1.1. Short Point 4.00 240.00 960  1.1. Short Point 90 Mcdium Point Point 90 Mcdium 90 Mc	1	1.1	Wiring for light/ fan/ exhaust fan / call bell point with 3x1.5 sgmm ERLS BVC.				
contention PRES PVC conduit (heavy duty, thickness of pipe should be 2 mm) with 56 amp piano type switch, phenolic laminated sheet, suitable size M.S. box eta as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  1.1. Short Point			insulated stranded copper conductor wire for phase, neutral and earth in	U			
M.S. box otc as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  1.1. Short Point  1.2. Medium Point  1.3. Long Point  2.1.3 Wring for circuit/ sub main writing along with earth wire with the following sizes of FRLS PVC insulated copper conductor, wire in concealed FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  3.1.1 3 X 1.5 sq. mm in 20mm conduit  3.1.1 3 X 1.5 sq. mm in 20mm conduit  3.1.1 6 X 2.5 sq. mm in 32mm conduit  3.1.1 6 X 2.5 sq. mm in 32mm conduit  3.1.1 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification  3.1.1 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  4. 5.1 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1.2 Fan regulator Electronic, step type moving all round  2. 5.1 Supplying see 3 pin 5 amps  2. 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  4. 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat strik and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9, LED chip efficacy ratio = 100 lumens /watt.  4. 6.1 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat strik and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9, LED			concealed FRLS PVC conduit (heavy duty, thickness of nine should be 2				
1.1. Short Point 4.00 240.00 960 1.2. Medium Point Point Point Point 3.00 376.00 1,128 1.3. Long Point Point Point Point 2.00 469.00 938 2 1.13 Writing for circuit/ sub main wiring along with earth wire with the following sizes of FRLS PVC insulated copper conductor, wire in concealed FRLS PVC conduit (heavy duly, thickness of pipe should be 2 mm) as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5) 3.1.1 6X 2.5 sq. mm in 32mm conduit Metre 26.00 182.00 4,732 3 4.3 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification. 3.4 205mmX94mm (6 Module) 4 5.1 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification. 1.1.3 5/6 amps one way switch 1.1.5 6/6 amps one way switch 1.1.5 Gaimps socket outlet Each 6.00 42.00 250. 1.1.5 Gaimps one way switch sufficient Each 6.00 42.00 250. 1.1.1 Ceiling rose 3 pin 5 amps Each 6.00 32.00 192. 1.1.1 Sattern/ angle holder 1.1.1 Sattern/ angle holder Each 9.00 38.00 342.1 1.1.1 Sattern/ angle holder 1.1.1 Sattern/ and above, IS: 374:2019 including all amendments. Each 2.00 1697.00 3,394.0 1697.00 1697.00 1697.00 1697.00 1697.00 1697.00 1697.00 1697.00 16			mm) with 5/6 amp piano type switch, phenolic laminated sheet, suitable size		1		
1.1 Short-Point 1.2 Medium Point 1.3 Long Point 1.3 Wring for circuit/ sub main wiring along with earth wire with the following sizes of FRLS PVC insulated copper conductor, wire in concealed FRLS PVC conduit (henry duty, thickness of pipe should be 2 mm) as per specification and IS: 694 (2010). IS: 9537 (2000 Part 5) 13.1 3 X 1.5 sq. mm in 20mm conduit 13.1 3 X 1.5 sq. mm in 32mm conduit 13.1 3 X 1.5 sq. mm in 32mm conduit 13.1 3 X 1.5 sq. mm in 32mm conduit 14.3 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification 13.4 205mmX94mm (6 Module) 13.5 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification. 13.5 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification. 13.5 Sign specification. 13.6 Ceiling rose 3 pin 5 amps socket outlet Each 6.00 42.00 252. 13.1 Sign shaten/angle holder 13.1 Ceiling rose 3 pin 5 amps Eaten/ 6.00 32.00 192. 14.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments. 13.1 200 mm sweep 14.5 Supplying, fixing, testing and commissioning of following LED lamps with ohild telectronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens Avatt.			M.S. box etc as per specification and IS: 694 (2010), IS: 0537 (2000 Part 5)				
1.2 Medium Point Point 3.00 376.00 1,128  1.3 Long Point 2.00 469.00 938  1.3 Wring for circuit/ sub main wiring along with earth wire with the following sizes of FRLS PVC insulated copper conductor, wire in concealed FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  1.3.1 3 X 1.5 sq. mm in 20mm conduit  3.1.1 6 X 2.5 sq. mm in 32mm conduit  3.1.2 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification  3.4 205mmX94mm (6 Module)  3.4 205mmX94mm (6 Module)  5.1 Supplying and fixing following piano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1.1 5/6 amps one way switch  1.1.2 Fan regulator Electronic, step type moving all round  1.1.3 Ceiling rose 3 pin 5 amps  1.1.5 Battern/ angle holder  1.1.5 Battern/ angle holder  1.1.6 Battern/ angle holder  1.1.7 Supplying, installation, testing and commissioning of following sizes ceiling fan including wring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9, LED chip efficacy ratio = 100 lumens Avatt.		1.1	Short Point	Deint	4.00	040.00	
1.13 Long Point Point 2.00 469.00 938  1.14 Wring for circuit/ sub main wiring along with earth wire with the following sizes of FRLS PVC insulated copper conductor, wire in concealed FRLS PVC conduit (heavy duty, thickness of pipo should be 2 mm) as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  1.13.1 3 X 1.5 sq. mm in 20mm conduit Metre 41.00 92.00 3.772  3.11 6 X 2.5 sq. mm in 20mm conduit Metre 26.00 182.00 4.732  3.12 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification switches with modular base and cover plates on surface complete as per specification the existing switch box/ cover including connections etc. as per specification.  3.4 205mmX94mm (6 Module)  4 5.1 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1.1 5/6 amps one way switch Each 8.00 25.00 200.  1.1.2 Fan regulator Electronic, step type moving all round Each 6.00 42.00 252.1 1.12 Fan regulator Electronic, step type moving all round Each 6.00 32.00 192.1 1.13 Ceiling rose 3 pin 5 amps Each 6.00 32.00 192.1 1.15 Battervi angle holder  1.1.3 Supplying, installation, testing and commissioning of following sizes ceiling fan including wring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with nothing efficacy ratio = 100 lumens Avatt.  1.75 12 Watt Each 3.00 215.00 645.0		1.2	Medium Point				960.00
2 1.13 Wring for circuit/ sub main wiring along with earth wire with the following sizes of FRLS PVC insulated copper conductor, wire in concealed FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) as per specification and IS: 684 (2010), IS: 9537 (2000 Part 5)  13.1 3 X 1.5 sq. mm in 20mm conduit Metre 26.00 182.00 4,732  3 4.3 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification witches with modular base and cover plates on surface complete as per specification.  3.4 205mmX94mm (6 Module) Each 4.00 178.00 712.  4 5.1 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1.5 3/6 amps one way switch  1.5 3/6 amps one way switch  1.1.5 3/6 amps one way switch  1.1.5 Batterv angle holder  1.1.1 Ceiling rose 3 pin 5 amps Each 6.00 42.00 250.  1.1.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  1.7.5 12 Watt Each 3.00 215.00 645.0		1.3	Long Point				1,128.00
sizes of HRLS PVC insulated copper conductor, wire in concealed FRLS PVC conduit (heavy duty, thickness of pipe should be 2 mm) as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  13.11	2	1.13	Wiring for circuit/ sub main wiring along with earth wire with the following		2.00	469.00	938.00
PVC conduit (heavy duty, thickness of pipe should be 2 mm) as per specification and IS: 694 (2010), IS: 9537 (2000 Part 5)  3.11 6X 2.5 sq. mm in 32mm conduit  3.11 6X 2.5 sq. mm in 32mm conduit  3.13 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification  3.4 205mmX94mm (6 Module)  5.1 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch  1.1. 5/6 amps one way switch  1.2 Fan regulator Electronic, step type moving all round  1.3 Pattern/ angle holder  1.1. Ceiling rose 3 pin 5 amps  1.1. Battern/ angle holder  1.1. Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  1.5 Supplying, fixing, testing and commissioning of following sizes ceiling from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  1.4 1200 mm sweep  1.5 1200 mm sweep  1.7 1200 mm sw			sizes of FRLS PVC insulated, copper conductor, wire in coppered at FRLS	U			
specification and Is: 694 (2010), Is: 9537 (2000 Part 5)  13.1 3 X 1.5 sq. mm in 20mm conduit  3.11 6 X 2.5 sq. mm in 32mm conduit  4.3 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification  3.4 205mmX94mm (6 Module)  4 5.1 Supplying and fixing following piano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch  1.5 3 pin 5/6 amp socket outlet  1.12 Fan regulator Electronic, step type moving all round  1.13 Celling rose 3 pin 5 amps  1.15 Battern/ angle holder  5 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9, LED chip efficacy ratio = 100 lumens /watt.			PVC conduit (heavy duty, thickness of pipe chould be 2 mm) as as				
13.1 3 X 1.5 sq. mm in 20mm conduit  3.11 6 X 2.5 sq. mm in 20mm conduit  4.3 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification  3.4 205mmX94mm (6 Module)  5.1 Supplying and fixing following piano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch  1.1.2 Fan regulator Electronic, step type moving all round  1.1.3 Ceiling rose 3 pin 5 amps  1.1.5 Batten/ angle holder  1.1.5 Batten/ angle holder  5 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required, P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.			specification and IS: 694 (2010), IS: 0537 (2000 Part 5)	1			
3.11 6 X 2.5 sq. mm in 32mm conduit  3 4.3 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification  3.4 205mmX94mm (6 Module)  4 5.1 Supplying and fixing following piano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch  1.5 3 pin 5/6 amp socket outlet  1.12 Fan regulator Electronic, step type moving all round  1.13 Ceiling rose 3 pin 5 amps  Each 6.00 42.00 252.1  1.14 Satten/ angle holder  5 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required, P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9, LED chip efficacy ratio = 100 lumens /watt.		13.1	3 X 1.5 sq. mm in 20mm conduit				
4.3 Supplying and fixing of following sizes PVC switch box suitable for modular switches with modular base and cover plates on surface complete as per specification  3.4 205mmX94mm (6 Module)  4 5.1 Supplying and fixing following piano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch  1.5 3 pin 5/6 amps one way switch  1.6 Fan regulator Electronic, step type moving all round  2.00 130.00 260.1  1.12 Fan regulator Electronic, step type moving all round  2.00 130.00 260.1  1.13 Ceiling rose 3 pin 5 amps  2.00 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  5 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9, LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt  26.0 182.00 178.00 178.00 25							3,772.00
switches with modular base and cover plates on surface complete as per specification  3.4 205mmX94mm (6 Module)  5.1 Supplying and fixing following plano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch  1.5 3 pin 5/6 amp socket outlet  1.6 3 pin 5/6 amp socket outlet  1.7 5 amps socket outlet  1.8 Batter/ angle holder  5 1.9 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  1.3 1200 mm sweep  1.4 2.5 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.	3				26.00	182.00	4,732.00
specification  3.4 205mmX94mm (6 Module)  4 5.1 Supplying and fixing following piano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch  1.5 3 pin 5/6 amp socket outlet  Fan regulator Electronic, step type moving all round  Each 2.00 130.00 260.1  1.13 Ceiling rose 3 pin 5 amps  Ceiling rose 3 pin 5 amps  Each 6.00 32.00 192.0  1.15 Batter/ angle holder  Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  Each 2.00 1697.00 3,394.0  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9, LED chip efficacy ratio = 100 lumens /watt.  Each 3.00 215.00 645.0		,,,,	switches with modular base and cover plates on surface several to	0			
3.4 205mmX94mm (6 Module)  4 5.1 Supplying and fixing following piano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch  1.5 3 pin 5/6 amps socket outlet  Each 6.00 42.00 252.0  1.12 Fan regulator Electronic, step type moving all round  Each 2.00 130.00 260.1  1.13 Ceiling rose 3 pin 5 amps  Each 6.00 32.00 192.0  1.15 Batten/ angle holder  Each 9.00 38.00 342.0  5 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  Each 3.00 215.00 645.0			specification	.			
4 5.1 Supplying and fixing following piano type switch, socket, other accessories on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch 1.5 3 pin 5/6 amp socket outlet 1.12 Fan regulator Electronic, step type moving all round 1.13 Ceiling rose 3 pin 5 amps 1.15 Batten/ angle holder 1.15 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep 1.3 1200 mm swee	-	3.4					
on the existing switch box/ cover including connections etc. as per specification.  1.1 5/6 amps one way switch 1.5 3 pin 5/6 amps socket outlet 1.6 Each 6.00 42.00 252.1 1.12 Fan regulator Electronic, step type moving all round 1.13 Ceiling rose 3 pin 5 amps 1.15 Batten/ angle holder 1.15 Batten/ angle holder 1.16 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep 1.3 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  1.7.5 12 Watt 17.6 15 Watt  Each 8.00 25.00 200.  200.  200.  200.  200.  200.  200.  200.  210.0  25.00 200.  25.00 192.0  260.0  27.00 33.00 342.0  38.00 342.0  38.00 342.0  38.00 342.0  38.00 342.0  38.00 342.0  48.00 38.00 342.0  48.00 38.00 342.0  48.00 38.00 342.0  48.00 38.00 342.0  48.00 38.00 342.0  48.00 38.00 342.0  48.00 38.00 342.0  48.00 38.00 342.0  48.00 38.00 342.0  48.00 38.00 38.00 342.0  48.00 38.00 38.00 342.0  48.00 38.00 38.00 342.0  48.00 38.00 38.00 342.0  48.00 38.00 38.00 342.0  48.00 38.00 38.00 342.0  48.00 38.00 38.00 342.0  48.00 38.00 38.00 38.00 342.0  48.00 38.00 38.00 38.00 342.0  48.00 38.00 38.00 38.00 342.0  48.00 38.00 38.00 38.00 38.00 342.0  48.00 38.00 38.00 38.00 38.00 342.0  48.00 38.00 38.00 38.00 38.00 342.0  48.00 38.	4			Each	4.00	178.00	712.00
specification.  1.1 5/6 amps one way switch Each 8.00 25.00 200.1 1.5 3 pin 5/6 amp socket outlet Each 6.00 42.00 252.1 1.12 Fan regulator Electronic, step type moving all round Each 2.00 130.00 260.0 1.13 Ceiling rose 3 pin 5 amps Each 6.00 32.00 192.0 1.15 Batten/ angle holder Each 9.00 38.00 342.0 5 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep Each 2.00 1697.00 3,394.0 6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt Each 3.00 215.00 645.0	7	0.1					
1.1 5/6 amps one way switch  1.5 3 pin 5/6 amp socket outlet  1.6 3 pin 5/6 amp socket outlet  1.7 5 par regulator Electronic, step type moving all round  Each 6.00 42.00 252.0  Each 6.00 130.00 260.1  Each 6.00 32.00 192.0  Each 6.00 32.00 192.0  Each 9.00 38.00 342.0  Each							
1.5 3 pin 5/6 amp socket outlet  Each 6.00 42.00 252.0  1.12 Fan regulator Electronic, step type moving all round Each 2.00 130.00 260.0  1.13 Ceiling rose 3 pin 5 amps Each 6.00 32.00 192.0  1.15 Batter/ angle holder Each 9.00 38.00 342.0  5 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep Each 2.00 1697.00 3,394.0  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt Each 3.00 215.00 645.0		- 1 1					
1.12 Fan regulator Electronic, step type moving all round  Each 2.00 130.00 260.0  1.13 Ceiling rose 3 pin 5 amps  Each 6.00 32.00 192.0  1.15 Batten/ angle holder  Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  Each 2.00 1697.00 3,394.0  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  Each 3.00 215.00 645.0							200.00
1.13 Ceiling rose 3 pin 5 amps  Each 6.00 32.00 192.0  1.15 Batten/ angle holder  Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  Each 2.00 1697.00 3,394.0  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt  Each 3.00 215.00 645.0							252.00
1.15 Batten/ angle holder  Each 9.00 38.00 342.0  5 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep Each 2.00 1697.00 3,394.0  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt Each 3.00 215.00 645.0						130.00	260.00
5 6.1 Supplying, installation, testing and commissioning of following sizes ceiling fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  Each 2.00 1697.00 3,394.00 inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt  Each 3.00 215.00 645.0					6.00	32.00	192.00
fan including wiring the down rods of standard length up to 30 cm with 1.5 sq. mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  Each 2.00 1697.00 3,394.0  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt  Each 3.00 215.00 645.0					9.00	38.00	342.00
mm FRLS PVC insulated, copper conductor, single core cable, earthing etc. complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  Each  Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  Each  3.00 215.00 645.0	5	6.1		0			
complete as required. P.F. should be greater than 0.9, with BEE Star rating from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  Each  Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  Each  3.00 215.00 645.0			•				
from 3 star and above, IS: 374:2019 including all amendments.  1.3 1200 mm sweep  Each  Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  Each  3.00 215.00 645.0					}	}	
1.3 1200 mm sweep  Each 2.00 1697.00 3,394.0  6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt Each 3.00 215.00 645.0							
6 6.17 Supplying, fixing, testing and commissioning of following LED lamps with inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt  Each 3.00 215.00 645.0		,					
inbuilt electronic driver heat sink and all other accessories in existing holder/ luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt Each 3.00 215.00 645.0				Each	2.00	1697.00	3,394.00
luminaries as per specification and P.F. should be greater than 0.9. LED chip efficacy ratio = 100 lumens /watt.  17.5 12 Watt Each 3.00 215.00 645.0	6	6.17	•	0			
efficacy ratio = 100 lumens /watt.  17.5 12 Watt Each 3.00 215.00 645.0							
17.5 12 Watt Each 3.00 215.00 645.0							
17.6 15 Watt 5.00 215.00 645.0							
1 17.61 15 Watt				Each	3.00	215.00	645.00
		17.6	TISW CT	Each	3.00	249.00	747.00

As per Estimate Amount Rs.

18274.00

- Malo-

The state of the s