

द्वितीय ई-निविदा आमंत्रण सूचना


कार्यालय नगर पालिक निगम, कोरबा द्वारा लोक निर्माण विभाग एकीकृत पंजीयन प्रणाली अंतर्गत सक्षम श्रेणी में पंजीकृत ठेकेदारों से प्रमुख अभियंता लोक निर्माण विभाग, रायपुर द्वारा भवन कार्य हेतु दिनांक 01.01.2015 से प्रभावशील दर अनुसूची पर (निविदा खुलने के दिनांक तक समस्त संशोधनों के साथ शेड्यूल अनुसार प्रतिशत दर पर ई-प्रोक्चुरमेंट (E-Tendering) के माध्यम से निविदा प्रपत्र Form-A में निविदा आमंत्रित की जाती है:-

1. फिजिकल सबमिशन लिफाफा प्राप्त होने की अंतिम तिथि - 31.12.2025 सायंकाल से 3.00 बजे तक
2. निविदा खुलने की अंतिम तिथि - 31.12.2025 सायंकाल 4.00 बजे से

| क. | कार्य का नाम | प्राक्कलन राशि (लाख में) | धरोहर राशि (FDR/TDR) | कार्यावधि | निविदा प्रतिभागी शुल्क (डिमांड ड्राफ्ट) | ठेकेदार का वर्ग | निविदा खुलने की तिथि |
|----|---|--------------------------|----------------------|-----------|---|--------------------------|----------------------|
| 1 | नगर पालिक निगम, कोरबा क्षेत्रांतर्गत कोरबा जोन अंतर्गत 13 शासकीय स्कूलों में बालक-बालिका शौचालय का निर्माण कार्य (जि.ख.न्या मद) | 65.00 | 48800/- | 10 माह | 3000/- | वर्ग डी एवं प्रवर श्रेणी | 31.12.2025 से |

शर्त:-

1. निविदा दरे प्रचलित सी.एस.आर.से कम या अधिक प्रतिशत दरों पर दिया जावे सी.एस.आर.के अंतर्गत के आयटमों पर पृथक से आयटम दरों का उल्लेख करने पर निविदा निरस्त मानी जावेगी
2. जिन ठेकेदारों द्वारा नगर पालिक निगम (साडा) के किसी ठेके के कार्य में अनुबंध के अनुरूप कार्य न किया गया हो अथवा नगर पालिक निगम (साडा) के हित के विरुद्ध कार्य किया गया हो उन्हें निविदा भरने की पात्रता नहीं होगी।
3. इच्छुक ठेकेदारों को उचित वर्ग में पंजीयन की प्रमाणित प्रतिलिपि यदि साझेदारी फर्म हो तो उसका प्रमाण पत्र (पार्टनरशीप डीड) की सत्य प्रतिलिपि, उपलब्ध तकनीकी अमले की जानकारी, विगत 3 वर्षों का आयकर चुकता प्रमाण पत्र, पेन नम्बर, वैध जी.एस.टी. पंजीयन प्रमाण पत्र एवं अमानत राशि के FDR/TDR की प्रति ऑनलाईन अपलोड करना अनिवार्य होगा, प्रशिक्षित यंत्री नियुक्त करने संबंधी प्रमाण पत्र, कर्मचारी भविष्य निधि रायपुर से पंजीकरण का कोड, निविदा प्रतिभागी शुल्क का डिमांड ड्राफ्ट एवं धरोहर राशि FDR/TDR, शपथपत्र का स्कैन कापी ऑन लाईन सिस्टम पर अपलोड करना अनिवार्य होगा।
 - अमानत राशि का वैध FDR/TDR, निविदा प्रतिभागी शुल्क का डिमांड ड्राफ्ट एवं निर्धारित प्रारूप में शपथ पत्र की मूल प्रति लिफाफा में कार्य का नाम एवं अन्य विवरण अंकित कर केवल स्पीड पोस्ट/रजिस्टर्ड डाक के माध्यम से आयुक्त, नगर पालिक निगम, कोरबा साकेत भवन, आई.टी.आई.चौक रामपुर कोसावाड़ी पिन- 495677 कोरबा के पते पर भेजना होगा। निर्धारित तिथि को सायं 03:00 बजे के पश्चात् फिजिकल सबमिशन लिफाफा स्वीकार नहीं किया जायेगा।
 - निविदाकार को प्रत्येक निविदा में पंजीयन क्षमता के अंतर्गत वर्तमान में नगर निगम या अन्य विभागों में उनके द्वारा किये जा रहे कार्यों का विवरण राशि सहित मूलप्रति में निर्धारित प्रारूप में वैध शपथपत्र (राशि रु. 100/- नॉनज्यूडिशियल स्टाम्प) निविदा आमंत्रण दिनांक के पश्चात् का, निविदा क्रमांक एवं कार्य का नाम अंकित करना अनिवार्य होगा।
 - अमानत राशि का FDR/TDR एवं निविदा प्रतिभागी शुल्क का डिमांड ड्राफ्ट जो कि आयुक्त, नगर पालिक निगम, कोरबा के नाम पर देय हो प्रस्तुत करना अनिवार्य होगा।
4. सम्पूर्ण किये गये कार्यों के लिए प्रत्येक चल देयकों में से 5 प्रतिशत सुरक्षा राशि 01 वर्ष के लिए एवं मरम्मत एवं संधारण मद को छोड़कर शेष कार्यों में 5 प्रतिशत परफार्मेंस सिक्योरिटी की गारंटी के रूप में से 03 वर्ष के लिए रोकी जावेगी। सुरक्षा राशि एवं परफार्मेंस गारंटी राशि वापसी हेतु समयावधि की गणना कार्य पूर्णता तिथि से किया जायेगा। उक्त समयावधि में निर्माण कार्य की भौतिक स्थिति सही होने तथा सक्षम प्राधिकारी के संतुष्टि के आधार पर भुगतान किया जायेगा।
5. जिन निविदाकारों द्वारा कर्मचारी भविष्य निधि संगठन (वर्तमान तक वैधता) एवं कर्मचारी राज्य बीमा निगम, रायपुर से पंजीयन कराकर कोड प्राप्त कर लिया हो वे निविदाकार ही निविदा हेतु पात्र होंगे। कर्मचारी भविष्य निधि संगठन (ई.पी.एफ.) एवं विभिन्न प्रावधानों की धारा 1952 के तहत निविदाकार का जीवित पंजीयन होना आवश्यक है साथ ही निविदा आमंत्रण दिनांक से विगत 03 माह की अवधि में जमा किये गये TRRN Payment Details चालान की प्रति प्रस्तुत करना तथा ऑनलाईन अपलोड किया जाना अनिवार्य होगा।
6. निविदा में भाग लेने वाले ठेकेदारों को छ.ग. भवन और अन्य सन्निर्माण कर्मकार (नियोजन एवं सेवा शर्तों का विनियमन) अधिनियम 1996 एवं तदंतर्गत निर्धारित नियमों के तहत पंजीयन कराना आवश्यक होगा तथा निर्माण लागत का 1 प्रतिशत उपकर के रूप में प्रत्येक देयक से कटौती की जावेगी।
7. ईट से संबंधित निर्माण कार्यों में फ्लाई एश ब्रिक का उपयोग किया जाना अनिवार्य होगा।
8. प्रयुक्त लोहा का बिल एवं टेस्ट रिपोर्ट तथा प्रयुक्त सीमेंट का बिल संलग्न करना अनिवार्य होगा।
9. निविदा दरों असामान्य कमी प्रतीत होने पर सफल निविदा दाता से अनुबंध के पूर्व एस.ओ.आर. एवं निविदा दर की अंतर की राशि के समतुल्य परफार्मेंस गारंटी के रूप में राष्ट्रीयकृत बैंक एफ.डी.आर., पोस्ट ऑफिस, टाईम डिपॉजिट अथवा एन.एस.सी. जो कि आयुक्त नगर पालिक निगम, कोरबा के नाम पर देय होगा जो मांग तिथि से 15 दिवस के भीतर जमा करना अनिवार्य होगा। उपरोक्त राशि समयावधि में जमा न करने की दशा में निविदा स्वमेव निरस्त मानी जावेगी।
10. निविदा अहस्तांतरणीय होगा एवं सशर्त निविदाओं पर विचार नहीं किया जावेगा।
11. निविदा प्रपत्र फार्म -ए की कंडिका 11 Price Adjustment (एस्कलेशन) देय नहीं होगा।
12. निविदा के संबंध में किसी प्रकार की विवाद होने की स्थिति में आयुक्त का निर्णय अंतिम एवं सर्वमान्य होगा।
13. निविदा स्वीकृत करने अथवा अस्वीकृत करने अथवा निरस्त करने का अधिकार नगर पालिक निगम के पास सुरक्षित रहेगा।
14. उपरोक्त निविदा सूचना की विस्तृत प्रति नगर पालिक निगम, कोरबा के साकेत भवन स्थित निर्माण शाखा से प्राप्त किये जा सकते हैं।
15. ठेकेदार द्वारा संपादित किए गए कार्यों के देयकों का भुगतान कार्य विशेष हेतु बजट आवंटन एवं राशि उपलब्ध होने पर किया जाएगा।
16. निविदा में सफल निविदाकार को ऐसे कार्य जिसकी अनुबंध राशि 10.00 लाख या उससे अधिक है, उनको प्रत्येक कार्यों हेतु पृथक से छ.ग. भवन और सन्निर्माण कर्मचार मण्डल का पंजीयन प्रमाण पत्र प्रस्तुत करना अनिवार्य होगा अन्यथा देयक भुगतान किया जाना संभव नहीं होगा।
17. कार्य कियान्वयन से संबंधित गुणवत्ता परीक्षण संबंधी रिपोर्ट पर होने वाले व्यय का वहन संबंधित ठेकेदार द्वारा किया जावेगा।
18. ठेकेदार को निर्माण कार्य के दौरान "निर्माण एवं अपशिष्ट प्रबंधन नियम 2016" में किये गए प्रावधानों का पालन करना अनिवार्य होगा।


अधीक्षक अभियंता
नगर पालिक निगम
कोरबा (छ.ग.)

प्रतिलिपि-

प्रोग्रामर, संचालनालय, नगरीय प्रशासन एवं विकास विभाग, रायपुर को uad.cg.gov.in में अपलोड करने हेतु प्रेषित।

Date-Time Detail(s)

| Seq. No. | Nagar Nigam Stage | Contractor Stage | Start | | Expiry | | Remarks |
|-------------|-------------------|---------------------------------|------------|-------|------------|-------|----------------|
| | | | Date | Time | Date | Time | |
| 1 | Release Tender | | 11.12.2025 | 15.30 | 11.12.2025 | 15.30 | Release Tender |
| 2 | | Bid Submission | 11.12.2025 | 15.30 | 29.12.2025 | 17.30 | |
| 3 | | Physical Document Submission | 11.12.2025 | 15.30 | 31.12.2025 | 15.00 | |
| 4 | Tender Open | | 31.12.2025 | 16.00 | -- | -- | |


4 SUPERITENDING ENGINEER
KORBA (CG)
For, Commissioner Korba (C.G.)

OFFICE OF THE MUNICIPAL CORPORATION, KORBA (C.G.)

ABSTRACT

Work :- Construction of Girls & Boys Toilet At 13 Nos Govt. School Under Korba Zone, Nagar Nigam Korba Area.

Part :- Schedule of Rates Public Works Department [PWD BUILDING 01-01-2015]

| REF | ITEM DESCRIPTION | UNIT | QTY | RATE | AMOUNT |
|-----|---|-------|---------|---------|----------|
| 1 | 1.2 Surface dressing of the ground including removing vegetation and making up undulations and in-equalities not exceeding 15 cms in depth/ height including disposal of rubbish upto 1.5 m lift and lead upto 50m (at least 5m away from the dressed | sqm | 200.00 | 7.20 | 1440.00 |
| 2 | 1.1 Excavation for all types and sizes of foundations, trenches and drains or for any other purpose including disposal of excavated stuff upto 1.5 m lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling | | | | |
| | 1.1 In all types of soils. | cum | 48.32 | 185.00 | 8939.20 |
| 3 | 1.6 Extra for every additional lift of 1.5 m of part thereof. | | | | |
| | 6.1 All types of soils. | cum | 2.26 | 26.50 | 59.89 |
| 4 | 1.17 Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M. | cum | 24.16 | 65.00 | 1570.40 |
| 5 | 1.18 Providing and filling in plinth with sand/ Crusher dust and hard moorum under floor in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering including dressing etc. complete. | cum | 6.06 | 371.00 | 2248.26 |
| 6 | 1.19 Providing filling and compacting local earth (from approved source pit) in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering, including dressing etc. complete. | cum | 9.60 | 242.00 | 2323.20 |
| 7 | 3.1 Providing and laying nominal mix plain cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. | | | | |
| | 1.4 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 40mm nominal size). | cum | 3.28 | 3552.00 | 11650.56 |
| 8 | 3.2 Providing and laying nominal mix reinforced cement concrete with crushed stone aggregate using concrete mixer in all works upto plinth level excluding cost of form work. | | | | |
| | 2.1 3.2.1 1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size). | cum | 18.07 | 4163.00 | 75225.41 |
| 9 | 3.12 Providing and placing in position reinforcement for R.C.C. work including straightening, cutting, bending, binding etc. complete as per drawings including cost of binding wire in foundation and plinth all complete: | | | | |
| | 12.1 Thermo-Mechanically treated bars FE 415 | kg | 1259.47 | 54.50 | 68641.11 |
| 10 | 2.1 Providing and fixing form work including centring, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for: | | | | |
| | 1.1 Foundations, footings, bases of columns plinth beam, curtain wall in any shape and size and all type of wall below plinth | sqm | 39.72 | 139.00 | 5521.08 |
| | 1.3 Window sills, anchor blocks, string course, bends, copings, bed plates and like | sqm | 1.92 | 184.00 | 353.28 |
| | 1.4 Edge of slab, breaks in floor and walls upto 200mm. | Metre | 36 | 34.00 | 1224.00 |


| REF | ITEM DESCRIPTION | UNIT | QTY | RATE | AMOUNT |
|-----|--|-------|-------|---------|-----------|
| 1.6 | Columns, Pillars, Piers and likes- rectangular or square in shape | sqm | 20 | 297.00 | 5,940.00 |
| 1.7 | Suspended floors, roofs, access platform, balconies (plain surfaces) and shelves (cast in situ) | sqm | 40 | 235.00 | 9,400.00 |
| 1.8 | Beams, lintels, cantilevers & walls | sqm | 33.6 | 202.00 | 6,787.20 |
| 11 | 3.13 Providing and laying damp proof course (upto 50mm thick) with plain cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded crushed stone aggregate 20mm nominal size) including form work. | cum | 0.56 | 4237.00 | 2,372.72 |
| 12 | 3.14 Providing and mixing water proofing material in PCC/RCC work in the proportion recommended by the manufacturer. | kg | 20 | 43.50 | 870.00 |
| 13 | 3.16 Making 50mm thick plinth protection of plain cement concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded crushed stone aggregate 20mm nominal size) over 75mm bed of dry brick ballast 40mm nominal size well rammed and consolidated and grouted with sand including finishing the top smooth. | sqm | 13.72 | 273.00 | 3,745.56 |
| 14 | 4.3 Providing and laying water proofing treatment to vertical and horizontal surfaces of depressed portions of WC, kitchen and the like consisting of: i) 1st course of applying cement slurry @ 4.4 Kg/sqm mixed with water proofing compound conforming to IS 2645 including rounding off junction of vertical and horizontal surface. ii) 2nd course of 20mm cement plaster 1:3 (1 cement : 3 coarse sand) mixed with water proofing compound including rounding off junction of vertical and horizontal surface. iii) 3rd course of applying blown or residual bitumen applied hot @ 1.7 Kg. per sqm of area. iv) 4th course of 400 micron thick PVC sheet (Overlaps at joints of PVC sheet should be 100 mm wide and pasted to each other with bitumen @ 1.7 Kg. per sqm of area. | sqm | 24 | 445.00 | 10,680.00 |
| 15 | 4.13 Grading roof for water proofing treatment with: | | | | |
| | 13.1 Cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) | cum | 0.8 | 3817.00 | 3,053.60 |
| 16 | 7.5 Brick work with modular fly-ash lime bricks (FaLG Bricks) conforming to IS:12894-2002 of class designation 4.0 in foundation and plinth in: | | | | |
| | 5.1 Cement Mortar 1:3 (1 cement : 3 coarse sand) | cum | 1.06 | 3641.00 | 3,859.46 |
| | 5.3 Cement Mortar 1:5 (1 cement : 5 coarse sand) | cum | 17.92 | 3350.00 | 60,032.00 |
| 17 | 7.6 Extra for brick work in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and plinth: | cum | 11.48 | 121.00 | 1,389.08 |
| 18 | 7.11 Half brick thick brick masonry with fly-ash lime bricks (FaLG Bricks) conforming to IS:12894-2002 of class designation 4.0 in superstructure above plinth level upto plinth level: | | | | |
| | 11.2 Cement Mortar 1:4 (1 cement : 4 coarse sand) | sqm | 17 | 382.00 | 6,494.00 |
| 19 | 3.151 Providing and fixing factory made P.V.C. door frame of size 50x47mm with a wall thickness of 5mm, made out of extruded 5mm rigid PVC foam sheet mitred at corners and joined with 2 Nos of 150mm long brackets of 15x15mm M.S. square tube, the vertical door profiles to be reinforced with 19x19mm M.S. square tube of 19 gauge, EPDM rubber gasket weather seal to be provided through out the frame. The door frame to be fixed to the wall using M.S. screws of 65/100mm size complete as per manufacturers specification and direction of Engineer-in-Charge. | metre | 10 | 346.00 | 3,460.00 |
| 20 | 3.152 Providing and fixing 30mm thick factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19mm x 19mm for styles and 15x15mm for top & bottom rails. M.S. frame shall have a coat of steel primers of approved make and | | | | |


| REF | ITEM DESCRIPTION | UNIT | QTY | RATE | AMOUNT |
|-----|---|------|------|---------|-----------|
| | manufacture. M.S. frame covered with 5mm thick heat moulded PVC 'C' channel of size 30mm thickness, 70mm width out of which 50mm shall be flat and 20mm shall be tapered in 45degree angle on either side forming styles; and 5mm thick, 95mm wide PVC sheet out of which 75mm shall be flat and 20mm shall be tapered in 45 degree on the inner side to form top and bottom rail and 115mm wide PVC sheet out of which 75mm shall be flat and 20mm shall be tapered on both sides to form lock rail. Top, bottom and lock rails shall be provided either side of the panel. 10mm (5mm x 2) thick, 20mm wide cross PVC sheet be provided as gap insert for top rail & bottom rail. paneling of 5mm thick both side PVC sheet to be fitted in the M.S. frame welded/ sealed to the styles & rails with 7mm (5mm+2mm) thick x 15mm wide PVC sheet beading on inner side, and joined together with solvent cement adhesive. An additional 5mm thick PVC strip of 20mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete as per Manufacturer's specification including 3 nos ISI marked stainless steel hinges of size 100x58x1.9 mm complete. (for W.C. and bathroom door shutter). | | | | |
| | 52.2 Both side Pre-laminated panel PVC door shutter | sqm | 3.36 | 2832.00 | 9,515.52 |
| 21 | 9.16 Providing and fixing M.S. frames of doors, windows, ventilators and cupboards joints mitred and welded with 15x3 mm lugs 10cm long embedded in cement concrete blocks 15x10x10cm of grade M-10 or with wooden plugs and screws or with dash fastener or rawl plugs and screws or with fixing clips or with bolts and nuts as required including fixing of necessary butt hinges and screws and applying a priming coat of approved steel primer. | | | | |
| | 16.2 Angle-iron frames | kg | 120 | 73.50 | 8,820.00 |
| 22 | 9.13 Providing and fixing steel door/ window with M.S. sheet 1mm thick, frame of angle iron, diagonal braces of angle/ flat iron of suitable size, 3.00 mm M.S. gusset plates at junctions and corners, all necessary fittings complete including applying a priming coat of red oxide zinc chromate primer. | kg | 80 | 75.00 | 6,000.00 |
| 23 | 9.15 Providing and fixing M.S. grill of approved pattern made of M.S. flats or square or round bars welded to steel frames of windows etc. including applying a priming coat welded to frame with all necessary fitting complete including applying a priming of red oxide zinc chromate primer. | kg | 15 | 67.50 | 1,012.50 |
| 24 | 12.7 Providing and fixing ceramic glazed wall tiles conforming to IS : 15622 of approved make, colours, shades and size on wall and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with matching pigment complete. | | | | |
| | 7.2 Size above 200x300mm | sqm | 41.2 | 646.00 | 26,615.20 |
| 25 | 12.9 Providing and laying ceramic glazed floor tiles conforming to IS : 15622 of approved size, make, colour, shade laid on 20 mm thick Cement Mortar 1:4 (1 cement : 4 coarse sand) including pointing the joints with white cement mixed with matching pigment etc., complete. | | | | |
| | 9.2 Size above 300x300mm | sqm | 24 | 728.00 | 17,472.00 |
| 26 | 13.17 Providing and fixing 15mm thick Granite (machine cut, table rubbed & mirror polished on both sides) for partition curtain in toilets or similar locations of required size in wall with cement mortar 1:4 (1 cement : 4 coarse sand) including cutting chase in wall and joint with wall treated with white cement mixed with matching pigment including rubbing and | | | | |

| REF | ITEM DESCRIPTION | UNIT | QTY | RATE | AMOUNT |
|-------|--|------|--------|---------|-----------|
| | polishing to edge moulding to give high gloss finish. | | | | |
| 17.1 | Granite stone grey/pink | sqm | 6.84 | 2111.00 | 14,439.24 |
| 11.1 | Providing and making 6mm thick cement plaster of mix: | | | | |
| 1.2 | In Cement mortar 1:4 (1 cement : 4 fine sand) | sqm | 40 | 87.00 | 3,480.00 |
| 11.2 | Providing and making 12mm thick cement plaster of mix: | | | | |
| 2.3 | In Cement Mortar 1:5 (1 cement : 5 fine sand) | sqm | 35.54 | 96.50 | 3,429.61 |
| 11.3 | Providing and making 15mm thick cement plaster on the rough side of single or half brick wall of mix: | | | | |
| 3.3 | In Cement Mortar 1:5 (1 cement : 5 fine sand) | sqm | 59.68 | 113.00 | 6,743.84 |
| 14.13 | Providing and applying 2mm thick ready mix exterior grade approved make putty (like Birla wall care, Alltek Superfine W/R of (NCL), Aslan, ICI, Nerolac, J.K. wall putty) on walls to make the surface smooth and even. | sqm | 121.08 | 94.50 | 11,442.06 |
| 14.15 | Painting exterior surface with ACRYLIC SMOOTH exterior paint of required shade as per manufacturer's specifications to give protective and decorative finish including cleaning washing of surface etc. complete with: | | | | |
| 15.1 | On new work (Two or more coats applied @ 1.43 lb/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm) | sqm | 57 | 56.00 | 3,192.00 |
| 14.11 | Wall painting with acrylic luxury emulsion (plastic) paint of required shade to give an even shade. | | | | |
| 11.1 | On new work (two or more coats) | sqm | 64.08 | 52.50 | 3,364.20 |
| 14.22 | Painting on new work (two or more coats) to give an even shade with: | | | | |
| 22.1 | Satin synthetic enamel paint | sqm | 1.5 | 55.00 | 82.50 |
| 14.30 | Painting small articles not exceeding 0.10 sqm of painted surface with superior quality enamel paint, not in conjunction to similar painted work. | each | 600 | 5.10 | 3,060.00 |
| 18.1 | Providing and fixing water closet squatting pan (Indian type W.C. pan), 100mm sand cast Iron P or S trap, 10 litre low level P.V.C. flushing cistern (same colour) conforming to IS : 7231, with flush bend and other fittings and fixtures complete including cutting and making good the walls and floors wherever required : | | | | |
| 1.1 | White Long pattern W.C. pan of size 580 mm | each | 2 | 2459.00 | 4,918.00 |
| 18.13 | Providing and fixing white vitreous china urinal basin with waste fitting as per IS : 2556, and other couplings in C.P. brass complete: | | | | |
| 13.1 | Flat back half stall urinal of size 460x380x250mm . | each | 3 | 1776.00 | 5,328.00 |
| 18.16 | Providing and fixing one piece construction white vitreous china squatting plate urinal with an integral rim longitudinal flushing pipe. | each | 3 | 1401.00 | 4,203.00 |
| 18.20 | Providing and fixing stainless steel AISI-304(18/8) wash basin with C.I. brackets, 32 mm C.P. brass waste of standard pattern, including painting of brackets, cutting and making good the walls wherever required : | | | | |
| 20.2 | Size 510x410 mm | each | 2 | 4095.00 | 8,190.00 |
| 18.25 | Providing and fixing flexible P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete. | | | | |
| 25.1 | 32 mm dia | each | 5 | 68.50 | 342.50 |
| 18.26 | Providing and fixing PVC waste coupling in wash basin/ sink. | | | | |
| 26.1 | 25 mm | each | 5 | 49.50 | 247.50 |
| 18.76 | Providing and fixing on wall face or under floor UV stabilized Unplasticised Rigid PVC pipes (single socketed) having 3.2mm wall thickness conforming to IS : 13592 (4kg/sqm) including required couplers, jointing with seal ring conforming to IS : 5362 leaving 10 mm gap for thermal expansion etc complete. | | | | |

| REF | ITEM DESCRIPTION | UNIT | QTY | RATE | AMOUNT |
|-------|---|-------|---------|--------|----------|
| 18.77 | 110 mm dia pipe. | metre | 12 | 267.00 | 3,204.00 |
| | Providing and fixing on wall face UV stabilized Unplasticised - PVC moulded fittings/ accessories having 3.2mm wall thickness for Rigid PVC pipes conforming to IS : 13592 (heavy) jointing with seal ring conforming to IS : 5382 leaving 10 mm gap for thermal expansion. | | | | |
| 3.2 | 110 mm | each | 2 | 44.00 | 88.00 |
| 77.5 | \"PI\" trap 110mmx110mm long | each | 6 | 227.00 | 1,362.00 |
| 77.6 | Nahani trap 110x75mm | each | 2 | 90.50 | 181.00 |
| 43 | 19.5 Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply including all CPVC plain & brass threaded fittings l/c fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and the cost of cutting chases and making good the same including testing of joints complete as per direction of Engineer In Charge. CONCEALED WORK including cutting chases and making good the walls etc., | | | | |
| 5.1 | 15 mm nominal outer dia .Pipes. | metre | 36 | 133.00 | 4,788.00 |
| 5.2 | 20 mm nominal outer dia .Pipes. | metre | 18 | 167.00 | 3,006.00 |
| 5.3 | 25 mm nominal outer dia .Pipes. | metre | 12 | 213.00 | 2,556.00 |
| 44 | 19.10 Making connection of G.I. distribution branch in G.I. main of following sizes by providing and fixing tee, including cutting and threading the pipe etc. complete: (dia of main line to be measured) | | | | |
| 10.1 | 25 mm nominal bore | each | 2 | 200.00 | 400.00 |
| 45 | 19.11 Providing and fixing G.I. Union in G.I. pipe (New work) including cutting and threading the pipe and making long screws etc. complete: | | | | |
| 11.1 | 15 mm nominal bore | each | 6 | 85.00 | 510.00 |
| 11.2 | 20 mm nominal bore | each | 4 | 98.00 | 392.00 |
| 11.3 | 25 mm nominal bore | each | 2 | 117.00 | 234.00 |
| 46 | 19.13 Providing and fixing 15 mm nominal bore Brass bib/stop cock of approved quality: | | | | |
| 13.2 | Bib cock (350 grams) | each | 4 | 237.00 | 948.00 |
| 13.3 | Stop cock (350 grams) | each | 4 | 237.00 | 948.00 |
| 47 | 19.14 Providing and fixing 15 mm nominal bore C.P. brass fittings of approved make and conforming to IS:8931 including C.P. brass extension if required: | | | | |
| 12 | Bottle trap set with extension pipes | each | 2 | 473.00 | 946.00 |
| 48 | 19.16 Providing and fixing brass/ gun metal gate valve with C.I. wheel of approved quality (screwed end): | | | | |
| 16.1 | 25 mm nominal bore | each | 2 | 436.00 | 872.00 |
| 49 | 19.17 Providing and fixing ball valve (brass) of approved quality, High or low pressure, with plastic floats complete : | | | | |
| 17.1 | 15 mm nominal bore | each | 6 | 284.00 | 1,704.00 |
| 17.2 | 20 mm nominal bore | each | 4 | 394.00 | 1,576.00 |
| 17.3 | 25 mm nominal bore | each | 2 | 432.00 | 864.00 |
| 50 | 19.42 Providing and placing on terrace (at all floor levels) polyethylene water storage tank ISI : 12701 marked with cover and suitable locking arrangement and making necessary holes for inlet, outlet and overflow pipes but without fittings and the base support for tank | | 1000.00 | 7.30 | 7,300.00 |
| 51 | 19.43 Cutting holes more than 20x20 cm and upto 30x30 cm in walls including | each | 1 | 125.00 | 125.00 |
| 52 | 19.47 Constructing masonry Chamber 30x30x50 cm, inside with modular well | each | 2 | 754.00 | 1,508.00 |

| ITEM DESCRIPTION | | UNIT | QTY | RATE | AMOUNT |
|--------------------------------------|--|-------|-----|---------|------------|
| | burnt clay bricks of 35 kg/ cm ² in cement mortar 1:4 (1 cement : 4 coarse sand) for stop cock, with C. I. surface box 100x100 x 75 mm (inside) with hinged cover fixed in cement concrete slab 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) necessary excavation foundation concrete 1:5:10 (1 cement : 5 fine sand:10 graded stone aggregate 40mm nominal size) and inside plastering with cement mortar 1:3 (1 cement : 3 coarse sand) 12mm thick finished with a floating coat of neat cement complete as per standard design : | | | | |
| 53 | 20.1 Providing, laying and jointing glazed stoneware pipes grade 'A' with stiff mixture of cement mortar in the proportion of 1:1 (1 cement : 1 fine sand) including testing of joints etc. | | | | |
| | 1.1 100 mm diameter | Metre | 24 | 162.00 | 3888.00 |
| 54 | 20.6 Providing, lowering, laying, aligning, fixing in position at and jointing at all level/ depths ISI marked HDPE pipes of PE-100 grade and PN 6 for sewer application as per IS 14333-1996 (amended upto date) in trenches in complete including all material, labour, testing and commissioning as per direction of Engineer Note : EHV to be measured and paid separately. | | | | |
| | 6.2 150 mm dia | Metre | 12 | 771.00 | 9252.00 |
| 55 | 20.7 Constructing brick masonry manhole with well burnt modular clay bricks crushing strength not less than 35kg/cm ² in cement mortar 1:4 (1 cement : 4 coarse sand), R.C.C. top slab with 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size), foundation in cement concrete 1:4:8 mix (1 cement : 4 coarse sand : 8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with floating coat of neat cement and making channels in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20mm nominal size) finished with a floating coat of neat cement complete as per standard design | | | | |
| | 7.1 20.7.1 Inside size 90x80 cm and 45 cm deep including C.I. cover with frame (light duty) 455x610 mm internal dimensions total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg) | Each | 2 | 6703.00 | 13406.00 |
| 56 | 19.14 Providing and fixing 15 mm nominal bore C.P. brass fittings of approved make and conforming to IS:8931 including C.P. brass extension if required: | | | | |
| | 14.4 Piller Cock (400 grams) | Each | 2 | 398.00 | 796.00 |
| As per SOR Total Estimate Amount Rs. | | | | | 500031.68 |
| Say Amount Rs. | | | | | 500000.00 |
| 13 Nos School X 500000.00= | | | | | 6500000.00 |


 Sub Engineer
 Municipal Corporation
 Korba (C.G.)


 Asstt Engineer
 Municipal Corporation
 Korba (C.G.)