

कार्यालय, नगर पालिक निगम, कोरबा (छत्तीसगढ़)

फा.क 780/उद्यान/2019/

कोरबा, दिनांक 5/6/19


निविदा आमंत्रण सूचना

नगर पालिक निगम कोरबा द्वारा शासकीय अर्द्धशासकीय विभागों में कार्यरत व्यवसाय से संबंधित अधिकृत विक्रेता/फर्मों/प्रदायकर्ताओं से (निविदा खुलने के दिनांक तक समस्त संशोधनों के साथ) शेड्यूल अनुसार आयटम दरों पर निविदाएं आमंत्रित की जाती हैं :-

क्र.	कार्य का नाम	प्राक्कलन राशि	धरोहर राशि	निविदा प्रपत्र का मूल्य	कार्यावधि	निविदा प्रपत्र प्राप्त करने हेतु आवेदन जमा करने की अंतिम तिथि	निविदा प्रपत्र प्राप्त करने की तिथि	निविदा खुलने की तिथि
1	अप्पू गार्डन के पीछे ओपन ग्राउण्ड में जीम सामग्री प्रदाय एवं स्थापना कार्य	499600.00	3750.00	750.00	1 माह	21-06-2019	25-06-2019	28-06-2019

शर्त :-

- जिन अधिकृत विक्रेता/ फर्मों /प्रदायकर्ताओं द्वारा नगर पालिक निगम (साडा) के किसी ठेके के कार्य में अनुबंध के अनुरूप कार्य ना किया गया हो अथवा नगर पालिक निगम (साडा) के हित के विरुद्ध कार्य किया गया हो उन्हें निविदा भरने की पात्रता नहीं होगी।
- निविदा प्राप्त करने हेतु इच्छुक अधिकृत विक्रेता/ फर्मों /प्रदायकर्ताओं को आवेदन के साथ उचित वर्ग में पंजीयन की प्रमाणित प्रतिलिपि यदि साझेदारी फर्म हो तो उसका प्रमाण पत्र (पार्टनीशप डीड) की सत्य प्रतिलिपि, पूर्व में इस प्रकार की किए गए कार्यों की प्रमाणित सूची, उपलब्ध तकनीकी अमले की जानकारी पिछले वित्तीय वर्ष का आय प्रमाण पत्र/पेन नम्बर पत्र एवं जी.एस.टी. का पंजीयन प्रमाण पत्र एवं धरोहर राशि प्रस्तुत करना होगा।
- निविदा प्रपत्र उन्ही अधिकृत विक्रेता/ फर्मों /प्रदायकर्ताओं को दिया जायेगा जिन्हे इस प्रकार के कार्यों का अनुभव हो।
- निविदा अहस्तांतरणीय होगा एवं सशर्त निविदाओं पर विचार नहीं किया जावेगा।
- निविदाकार संबंधित ओपन जिम सामग्री के आई.एस.ओ. प्रमाणित सर्टिफिकेट होना आवश्यक है।
- निविदाकारों को निविदा भरने हेतु ओपन जिम सामग्री निर्माताओं से आयटम एवं केटलॉक एवं स्पेशिफिकेशन, आयकर निटर्न, पेन नम्बर एवं ओपन जिम से संबंधित कार्य का अनुभव प्रमाण पत्र एवं खरीदी आदेश (पर्चेस आर्डर) की प्रति प्रस्तुत करना अनिवार्य होगा, अन्यथा निविदा भरने की पात्रता नहीं होगी।
- निविदाकारों को निविदा प्रपत्र भरने हेतु अधिकृत विक्रेता/फर्मों/प्रदायकर्ताओं का डीलरशीप/आयटम एवं जिम सामग्री संबंधित अनुभव प्रमाण पत्र प्रस्तुत करना अनिवार्य होगा, अन्यथा निविदा भरने की पात्रता नहीं होगी।
- निविदा के संबंध में किसी प्रकार की विवाद होने की स्थिति में आयुक्त का निर्णय अंतिम एवं सर्वमान्य होगा।
- निविदा स्वीकृत करने अथवा अस्वीकृत करने का अधिकार नगर पालिक निगम के पास सुरक्षित रहेगा।


कार्यपालन अभियन्ता
नगर पालिक निगम
कोरबा (छत्तीसगढ़)

OFFICE OF THE MUNICIPAL CORPORATION, KORE

DETAILED ESTIMATE

Name of work - Supply & Installation of open GYM at Open Ground.

S. No	Item Description	Qty.	Unit
1	<p>OUTDOOR OPEN MULTIGYM GALVANISED PIPE - 5 STATION Structure made of angle iron 50mm x 50mm x 5mm covered with metallic provision of different exercises.</p> <p>a) Abdominal Exerciser b) Roman Chair c) Hip Flexer d) Dipping Bars e) Chinup Bars</p> <p>1 There are two foundation rectangular pipes of length 556mm breadth 79mm and height 40mm.</p> <p>2 These 2 foundation rectangular pipes are connected with foundation connector of length 760mm breadth 80mm and height 40mm foundation connector is welded to both foundation rectangular pipe through the middle of the same pipes.</p> <p>3 Standing rectangular pipe no. 1 of length 930 diameter 89mm is welded to one of the foundation rectangular pipes top through the center.</p> <p>4 Standing rectangular pipe no. 02 of length 745mm diameter 89mm is welded to another foundation rectangular pipes top through the center.</p> <p>5 Cylindrical pipes are welded on the top and center of the both standing pipes diameter of cylindrical pipe is 60mm and length is of 457 mm.</p> <p>6 On the both ends of cylindrical pipes 2 pendulum bar big and pendulum bar small are suspended through pin bearing connection these pendulum bars can swing in forward and backward notion length of big pendulum bar is 770mm and length of small pendulum bar is 515mm gaps between the 2 pin bearing is 338mm these pendulum bars are welded to the bush.</p> <p>7 Free ends of the big pendulum bars and small pendulum bars are welded with bushes these welded bushes are fitted in the brackets.</p> <p>8 bridge rectangular pipe of length 920mm breadth 40 and height 60mm is connected between one big pendulum and small pendulum bar of same side.</p> <p>9 Brackets are welded on the both sides of the bridge rectangular pipe for connection of big pendulum bar and small pendulum bar with steel screws.</p> <p>10 In the middle of the bridge rectangular pipe standing pads (foot rest) are attached with steel screw standing pads may be plastic or of metal.</p>	1	Pcs

	<p>PULL CHAIR (DOUBLE) GALVANISED PIPE</p> <ol style="list-style-type: none"> 1 Acircular mounting plate of diameter 233 mm and thickness 8mm it has 4 holes at 90 degrees which P.C.D. 170mm hole diameter is 20mm 2 On circular mounting plate a center pillar is welded diameter of the center pillar is 114mm and height is 223mm 3 Trapezium shaped pipe is welded to the center pillar from the middle at the base trapexium shaped pipe upper portion is open with two branches. 4 Cap is on the two branches of upper portion/top of the branches are 925mm wide and length of each branch is 885mm at the base of the branches the gap is 925mm with a radius bend 235mm. 5 Openend of trapezium shaped pipe is welded with a holding pipe holding pipe has a straight length of 810mm and a 90 degrees radius on both sides then a small straight length of 246mm through the small straight length holding pipe is welded to trapezium shapes pipe holding pipe is welded at an angle of 40 degrees to the open ends of trapezium shaped pipe height of joint is 1212mm. 6 Hinge support of length 126mm is welded on the branches of trapezium shaped pipe at a height of 1117mm from the base. 7 2 Obtuse L shaped pipes are connected to the hinge supporter by the bushes. Bushes are welded at the upper portion of the obtuse L Shaped pipe lower portion of obtuse L shaped pipe is welded with rectangular pipe of length 705mm radius 124mm and short length 137mm. 8 On rectangular pipe standing pad are tightly screwed standing pad (foot rest) is of plastic 9 Tringular hinge supporter are welded to the hinge supporter to provide better strength. <p>Note: All the movable jionts have a PIN BEARING in between tightned with the Allen bolt polydrive head bolt having plastic caps on the ends Since plastic caps are fixed on the ends the bolt can't be opened until they will be broken.</p>	1	Pcs
3	<p>LEG PRESS (DOUBLE) GALVANISED PIPE</p> <ol style="list-style-type: none"> 1 Acircular mounting plate of diameter 233 mm and thickness 8mm it has 4 holes at 90 degrees which P.C.D. 170mm hole diameter is 20mm 2 On circular mounting plate a center pillar is welded diameter of the center pillar is 144mm and height is 1345mm 3 Cap is fixed on the top of the center pillar with rivets. 4 2 horizontal armholding pipes of length 992 mm are welded on both sides of center pillar at a height of 1222mm from the mounting plate. 5 2 Bending arm holder and supporters are welded on the both sides of cente pillar at a height of 1355mm from the mounting plate. 6 2 arm are connected to the both arm holding pipes and arm holder/supporter through welding length of arms are 814mm. 7 2 pipe pendulum holders are welded on the sides of center pillar byt perpendicular to the arm holding pipe the heioght of the pendulum pipe is 1121mm from the base of mounting plate. 	1	Pcs

	<p>8 Pendulum pipe is fitted in to the pendulum pipe holder with a self greasing high quality bearing pendulum pipe is movable and swing side ways length of pendulum pipe is 863mm.</p> <p>9 Pendulum pipe is suspended at an angle of 3 degrees at the base of free end of the pendulum pipe is welded to the square pipe at a distance of 5mm from the starting point.</p> <p>10 Standing pads are tightly screwed with steel screw to the square pipe standing pad may be of plastic or steel metal. Note: All the movable joints have a PIN BEARING in between tightened with the Allen bolt polydrive head bolt having plastic caps on the ends Since plastic caps are fixed on the ends the bolt can't be opened until they will be broken.</p>		
4	<p>CHEST PRESS (DOUBLE) GALVANISED PIPE</p> <p>1 A circular mounting plate of diameter 233 mm and thickness 8mm it has 4 holes at 90 degrees which P.C.D. 170mm hole diameter is 20mm</p> <p>2 In this circular mounting plate a center pillar is welded diameter of the center pillar is 114mm and the height is 568mm.</p> <p>3 Cap is fixed on the top of the center pillar with rivets.</p> <p>4 Two main pipes are welded opposite to each other with the center pillar having length 266mm height from the bottom edge is 174mm and diameter 48mm.</p> <p>5 Two square mounting plates are welded on the main pipes apart from the edges of the mounting main pipes 91mm these plates are of length 190mm breadth 150mm and thickness 5mm.</p> <p>6 A frame base pipe is welded with the square mounting plate at a distance of 14mm from the one of the edge of base pipe having 2 parts first length straight pipe 108mm and radius 119mm therefore we have four base pipes welded on the 2 square mounting plate (2x2) towards the welding the distance between the two base pipes is 218mm</p> <p>7 A foot rest pipe is welded on the radial edge of the 2 base pipes of one square mounting plate rest pipes are extended equally from the center.</p> <p>8 A frame support is welded on the frame base pipe having length 385mm and diameter 38mm from the straight edge of the frame base pipe is 84mm these support pipes are welded on 4 base pipes.</p> <p>9 A curved frame having a curved radius 2384mm and flat radius 74mm is welded with the straight edge of the frame base pipe and 2nd side is with the foot rest pipe flat radius is on the four corners of the curved frame the pipe used to make the curved frame have</p> <p>10 A PVC pad is mounting on the curved frame having same dimension as of the curved frame with the help of the mushroom head screws (steel).</p> <p>11 Bending support is welded on the either side of the center pillar having 3 parts short length 34mm radius 150mm and long straight length 179mm the bending support is welded 322mm from the center pillar on the main pipe whereas other edge (towards short length) welded with center pillar Note: All the movable joints have a PIN BEARING in between tightened with the Allen bolt polydrive head bolt having plastic caps on the ends Since plastic caps are fixed on the ends the bolt can't be opened until they will be broken.</p>	1	Pcs

	<p>ABDOMINAL EXERCISER/SIT UP BOARD (DOUBLE) GALVANISED PIPE</p> <p>a) Central standing pipe 114mm "B" class (2.5mm thickness)</p> <p>b) Board lower frame 32mm 'B' class (2.5mm thickness)</p> <p>c) Board outer frame 32mm 'B' class (2.5mm thickness)</p> <p>d) Board top metallic sheet/rectangular pipe 25mm x 50mm /frp sheet</p> <p>e) Board leg support pipe 50mm 'B' class (2.5mm thickness)</p>	1	Pcs
6	<p>OVERHUNG ROTATING WHEEL</p> <p>The standing seating twister made of galvanized pipe with thickness approx (3mm) with stainless steel screw and Argon/MIG welding along with comfortable plastic seats with material to bear outer weathering action the complete machine should be with double powder coating baked at temperatures + 200 degrees for minimum of 25 minutes ensuring a very good quality weather resistant product colors dark green red and yellow. The foundations should be embedded properly by digging and jamming through cement concrete with all necessary equipment all works complete. Material should be ISO approved of possess IS standard including 1st year maintenance</p>	1	Pcs
7	<p>SCALING LADDER GALVANISED PIPE</p> <p>1 Acircular mounting plate of diameter 233 mm and thickness 8mm it has 4 holes at 90 degrees which P.C.D. 170mm hole diameter is 20mm</p> <p>2 On these circular mounting plate a center pillar is welded diameter of the center pillar is 114mm and height is 192mm</p> <p>3 Main supporter is connected to the centre pillar main supporter have 5 parts vertical length 585mm radius 1 235mm straight length 577mm radius2 235mm angle 230 degree diameter of the main supporter pipe is 89mm the last length is tilted whose length is 179mm main supporter pipe is welded at height of 148mm from the mounting plate</p> <p>4 Big cylindrical pipe is welded at 967mm from the mounting plate on the vertical length of the main supporter pipe length of the pipe used 280mm and diameter is 60mm.</p> <p>5 Small cylindrical pipe is welded at the edge of the tilted length at 184mm and diameter 60mm small cylindrical pipe is welded at the middle of the tilted length of the main supporter pipe bridge of length 1045mm breadth 60mm height 40mm one edge of the bridge is connected with the bearing of the rotators and brackets are welded at the other edge and connected with the pendulum bar joints have a bearing and pin in between tightened with the allen bolt polydrive head bolt having plastic caps on the ends Since plastic caps are fixed on the ends the bolt can't be opened until they will be broken.</p>	1	Pcs

6 Pendulum bar of length 718mm and diameter and diameter of 38mm is welded with the small pipe of length 60mm and diameter 60mm downward direction small pipe is connected vertically with the holding pipe having 3 parts length 153mm radius 96mm and angular length 120mm at an angle of 26 degree holding pipe consists of extended length 137mm *studded* with the gripper either of plastic or rubber both ends of the cylindrical pipe is connected the small pipe joints have a bearing and pin in between tightened with the allen bolt polydrive head bolt having plastic caps on the ends Since plastic caps are fixed on the ends the bolt can't be opened until they will be broken.

7 Standing pad is fixed with the bridge from the middle and tightened with the Allen bolt polydrive head it is of plastic.

8 Rotators have a metallic strip of length 214mm thickness 10mm and connected with the pipe of length 23mm and diameter 60mm on both sides during rotation through the rotators one of the bridges will be straight while other in angular way angle 17 degrees.

9 Rotators small cylindrical pipe and bridge are connected with each other by bearing and pin in between tightened with Allen polydrive head bolt having cap fixed of plastic.

Note: All the movable joints have a PIN BEARING in between tightened with the Allen bolt polydrive head bolt having plastic caps on the ends Since plastic caps are fixed on the ends the bolt can't be opened until they will be broken.

8 **STANDING WAIST TRAINER
GALVANISED PIPE**

1 Pcs

1 A circular mounting plate of diameter 233 mm and thickness 8mm it has 4 eye holes made on this plate at 90 degrees which P.C.D. 170mm hole diameter is 20mm length is 39.9mm

2 On circular mounting plate a center pillar is welded diameter of the center pillar is 114mm and height is 209mm

3 Main pipe of diameter 60mm and thickness 4mm have five parts long length 795mm short long length 509.7mm short length 220.1mm radius 1 and radius 2 of 150mm.

4 The midpoint of the short length of the main pipe is welded with the center pillar the right edge of the short length having a radius 2 bent at an angle of 10 degree and short long length is with that radius 2 angularly.


5 The left edge of the short length having a radius 1 bent at an angle of 13.7 degree and long length is with that radius 1 angularly.

6 On the edge of the short long length of main pipe a seat having ISO standard shape is fitted horizontally.

7 The plastic seat is tightened with the help of Allen bolts (polydrive head)

8 On the edge of the long length of the main pipe a plastic cap is fixed.

- 9 Arm having diameter 32mm thickness 3mm have five parts length 1 161.8mm radius 1 70.2mm bent at angle of 30 degree straight length 2 100mm radius 276mm bent at angle of 60 degree and a straight edge 150mm arms are welded on both either faces of the main pipe at a height 1043mm from the mounting plate and 401mm apart from the center of the mounting plate.
- 10 Gripper are fitted with the straight edge of the arm pipe gripper made up of either rubber or plastic.
- 11 Support pipe having diameter 38mm length of 516.6mm and thickness 3mm the edge of the support pipe are welded one with the long length and other with the short long length of the main pipe the height of the support pipe from the mounting plate is 546.6mm.
- 12 Two strip having dimensions length 170mm thickness 6mm and height 42mm are welded on both the faces of the short length of the main pipe the distance between the strips is 50mm.
- 13 Axle pipe of diameter 70mm length 130mm thickness 5mm is welded on the strips and extended 34mm equally both sides on both the edges of the axle pipe bearing are fitted and axle pin is fitted through out the pipe having bigger diameter 35mm and diameter fitted with the bearing is 30mm axle pin is 40.5mm extended outwards in which wheel plates of thickness 10mm are fitted on both sides a nut is adjusted with the washer along the axle pin and tightly fit a plastic cap is fixed on the open edge of the wheel plate.
- 14 A hole of diameter 12mm is made on the wheel plate 165mm apart from the center of the wheel plate the paddle rod is 151.5mm it is 31mm a part from the face of the wheel plate the paddle is adjusted with the paddle rod as it can freely rotate on the other edge of the paddle rod a washer is fixed along with the nut to avoid displacement of the paddle from the paddle rod the paddle could be of any type of shape as per the requirement a plastic cap is fixed on the nut to avoid dirt.
- 15 A particular key slot is made at the center of the wheel plate so that the paddles adjusted in such a manner if one is in upward direction then other is in the downward direction.


Asstt. Engineer
Municipal Corporation
Korba (C.G.)


Executive
Municipal
Korba