

## कार्यालय, नगर पालिक निगम, कोरबा (छ.ग.)

मुख्य कार्यालय - साकेत भवन, आई.टी.आई. चौक, कोरबा (छ.ग.)

पं.रविशंकर शुक्ल नगर जोन

फौ.क. / 127,165,172 एवं 173 / निर्माण (पं.रविशंकर शुक्ल नगर जोन) / 2024 /

कोरबा, दिनांक 07.06.2024

## निविदा आमंत्रण की सूचना

लोक निर्माण विभाग से एकीकृत पंजीयन प्रणाली अंतर्गत सक्षम श्रेणी में पंजीकृत ठेकेदारों से निम्नलिखित कार्य हेतु प्रमुख अभियन्ता लोक निर्माण विभाग, रायपुर द्वारा प्रचलित PWD Building SOR 01.01.2015 & PWD Electrical SOR 01.06.2020 से प्रभावशील दर अनुसूची पर (निविदा खुलने के दिनांक तक समस्त संशोधनों के साथ) कम अधिक या समान दरों पर तथा शेड्युल अनुसार आयटम दरों पर निम्नलिखित निर्माण कार्य हेत् मैन्युअल निविदा वेबसाईट से डाउनलोड कर मुहरबंद लिफाफा में निविदा आमंत्रित की जाती है :-

1. निर्धारित प्रारूप में निविदा प्रपत्र प्राप्त होने की अंतिम तिथि - 01.07.2024 सायंकाल 3:00 बजे तक

2. निविदा खुलने की अंतिम तिथि

- 01.07.2024 सायंकाल 4:30 बजे तक

क्र.	कार्य का नाम	प्राक्कलन राशि में	धरोहर राशि रू	निविदा प्रपत्र	निविदा प्रपत्र	कार्यावधि	ठेकेदार का वर्ग	निविदा खुलने की
			में	का मूल्य				अंतिम तिथि
1	वार्ड क्र. 25 अंतर्गत सुभाष ब्लॉक में सांस्कृतिक भवन का संधारण एवं अन्य सुविधाओं की व्यवस्था कार्य। (पार्षद मद 2022–23) (चतुर्थ निविदा)	2,00,000/-	2,000 /-	300/-	Form-A	02 माह	सक्षम श्रेणी	01.07.2024
2	वार्ड क्र. 25 बाईपास रोड अंतर्गत पूर्वान्चल विकास समिति के समीप बाउण्ड्रीवाल से प्रेस क्लब बाउण्ड्रीवाल तक बाउंण्ड्रीवाल का निर्माण कार्य। (निगम मद) (द्वितीय निविदा)	14,48,000/-	11,000 /-	750/-	Form-A	04 माह	सक्षम श्रेणी	01.07.2024
3	वार्ड क्र. 27 रामनगर अंतर्गत वरूण गोस्वामी घर के समीप सी. सी. रोड का मरम्मत कार्य। (मरम्मत एवं संधारण मद)	3,78,000/-	4,000 /-	300/-	Form-A	03 माह	सक्षम श्रेणी	01.07.2024
4	वार्ड क्र. 30 मानिकपुर बाजार के समीप मूत्रालय एवं शौचालय का मरम्मत एवं जीर्णोद्धार कार्य। (मरम्मत एवं संधारण मद)	3,93,000/-	4,000 /-	300/-	Form-A	03 माह	सक्षम श्रेणी	01.07.2024

निविदा की शर्ते:--

1. निविदा दरे प्रचलित सी.एस.आर.से कम या अधिक प्रतिशत् दरों पर दिया जावे सी.एस.आर.के अंतर्गत के

आयटमों पर पृथक से आयटम दरों का उल्लेख करने पर निविदा निरस्त मानी जावेगी।

2. निविदा के दस्तावेज हाथो-हाथ न लिया जाकर रजिस्टर्ड पोस्ट अथवा स्पीड पोस्ट से प्राप्त किया जावेगा। अन्य माध्यमों यथा कोरियर सर्विस, साधारण डाक इत्यादि से प्राप्त अथवा समयावधि के पश्चात् प्राप्त निविदाओं पर विचार नहीं किया जावेगा। निविदा आयुक्त, नगर पालिक निगम, आई.टी.आई. चौक साकेत भवन, जिला-कोरबा (छ.ग.) पिन नं.-495677 के पते पर भेजना होगा। निर्धारित तिथि को सायं 3:00 के पश्चात् प्राप्त निविदाएँ स्वीकार नहीं किए जार्वेगे।

निविदा प्रपत्र नगर पालिक निगम, कोरबा के वेबसाईट www.korbamunicipal.in/uad.cg.gov.in डाउनलोड किया जाकर नवीन निविदा प्रपत्र Form - A/B/ABC (जारी दिनॉक तक समस्त संशोधनों के साथ) निर्धारित शुल्क की डीडी के साथ संबंधित कार्य का नाम पूर्ण विवरण सहित भरकर भेजना होगा।

4. निविदा मुहरबंद लिफाफा में मान्य किया जावेगा जो निम्नानुसार होगा:-प्रथम लिफाफा में ठेकेदार का जीवित पंजीयन प्रमाण पत्र, आयकर चुकता प्रमाण पत्र, निविदा सूचना आमंत्रण में उल्लेखित अन्य दस्तावेज के साथ निर्धारित प्रपत्र शुल्क का डीडी, निविदाओं में निविदाकार को फिजिकल दस्तावेज के साथ निविदा सूचना जारी होने के पश्चात दिनांक का शपथ पत्र जिसमें संबंधित कार्य का नाम एवं कार्य की निविदा क्रमांक अंकित हो प्रेषित करना अनिवार्य होगा एवं अमानत राशि का टी.डी.आर. / एफ.डी.आर. जो

कि आयुक्त, नगर् पालिक निगम कोरबा के नाम पर देय होगा प्रस्तुत करना होगा।

कि आयुक्त, नगर पालिक निगम करिबा के नाम पर देय होगा प्रस्तुत करना होगा।
(३) द्वितीय लिफाफा में ठेकेदार द्वारा भरा हुआ निविदा प्रपत्र होगा।
(५) तृतीय लिफाफा में उपरोक्त दोनो लिफाफ होंगे तथा आवश्यकता पड़ने पर मूल अभिलेख प्रस्तुत करना होगा।
जिन ठेकेदारों द्वारा नगर पालिक निगम (साडा) के किसी ठेके के कार्य में अनुबंध के अनुरूप कार्य न किया गया हो अथवा
नगर पालिक निगम (साडा) के हित के विरूद्ध कार्य किया गया हो उन्हें निविदा भरने की पात्रता नहीं होगी।
निविदा हेतु इच्छुक ठेकेदारों को उचित वर्ग में पंजीयन की प्रमाणित प्रतिलिपि यदि साझेदारी फर्म हो तो उसका प्रमाण पत्र
(पार्टनरशीप डीड) की सत्य प्रतिलिपि, उपलब्ध तकनीकी अमले की जानकरी पिछले वित्तीय वर्ष का आय चुकता प्रमाण
पत्र, पेन नम्बर, जी.एस.टी. (जीवित) पंजीयन एवं प्रशिक्षित यंत्री नियुक्त करने संबंधी प्रमाण पत्र, कर्मचारी भविष्य
निधिसंगठन,कर्मचारी, राज्य बीमा निगम रायपुर से पंजीयन एवं विस्तृत निविदा आमंत्रण सूचना (एनआईटी) हस्ताक्षरयुक्त
निर्धारित प्रारूप में निविदा आमंत्रण सूचना के कंडिका क्र. 04 के अनुरूप लिफाफा (अ) में प्रस्तुत करना अनिवार्य होगा।
कार्य हेतु लिफाफे पर कार्य का नाम निविदा आमंत्रण सूचना क्रमॉक, निविदा खुलने की तिथि स्पष्ट रूप से लिखकर भेजना
होगा।

निविदाकार का यह दायित्व है कि वे निविदा भरने के पूर्व स्थल का स्वयं निरीक्षण कर लेवें ताकि प्रारंभ करने में किसी प्रकार की कठिनाई न हो।

निर्धारित निविदा प्रपन्न में उल्लेखित कंडिकाएँ स्वमेव लागू मानी जावेगी एवं निविदा आमंत्रण सूचना निविदा का ही भाग

10. निर्धारित प्रारूप में निविदा प्रपन्न, निविदा प्रपन्न शुल्क्, अमान्त राशि, निविदा आमंत्रण सूचना पत्र में उल्लेखित दस्तावेज सही पाए जाने पर ही निविदा दर संबंधी लिफाफा खोला जावेगा अन्यथा निविदा निरस्त कर दी जावेगी।

11. ठेकेदार को अपनी दरें शब्दों एवं अंको में लिखना अनिवार्य होगा।
12. शासन के विभिन्न विभागों जैसे:— खुजिन विभाग, श्रम विभाग, समाज कल्याण विभाग इत्यादि विभागों द्वारा समय—समय पर जारी निर्देशों/आदेशों के पालन की समस्त जिम्मेदारी संबंधित ठेकेदार की होगी।
13. ठेकेदार यदि कार्य को अपूर्ण स्थिति में छोड़ता है तो निविदा प्रपत्र में उल्लेख अनुसार इस संबंध में प्रावधान

के अंतर्गत कार्यवाही की जीवेगी।

14. कार्य प्रारंभ नहीं करने अथवा अपूर्ण स्थिति में छोड़ने पर निगम द्वारा ठेकेदार के विरुद्ध तत् समय में एम.आई. सी. द्वारा स्वीकृत प्रस्ताव के अधीन कार्यवाही की जावेगी जिसकी संपूर्ण जवाबदारी ठेकेदार की होगी।
15. सफल निविदा दाता से अनुबंध के समय अतिरिक्त परफार्मेंस राशि जमा कराई जावेगी जबकि निविदा की दरों में काफी कमी हो जैसे निविदादाता को निविदा दर एवं अनुमानित लागत से 10 प्रतिशत से अधिक निविदा दर होने पर सफल निविदादाता को निविदा दर एवं अनुमानित लागत के 90 प्रतिशत अंतर की राशि के समतुल्य परफार्मेंस गारंटी के रूप में राष्ट्रीयकृत बैंक का एफ.डी.आर. / टी.डी.आर. ऑफिस अथवा टाईम डिपॉजिट जो कि आयुक्त नगर पालिक निगम कोरबा के नाम से देय होगा, जो मांग तिथि से 15 दिवस के भीतर जमा करना अनिवार्य होगा। उपरोक्त राशि को जमा न करने की दशा में निविदा निरस्त कर दी जावेगी।

16. सम्पूर्ण किये गये कार्यों के लिये 5 प्रतिशत की दर से सुरक्षा राशि रिगंग देयकों के साथ 01 वर्ष हेतु साथ ही मरम्मत एवं अनुमान करने के कार्यों के लिये के कार्यों के लिये के कार्यों के लिये के कार्यों के लिये

संधारण प्रकृति के कार्यों को छोड़क्र शेष कार्यों के देयकों से 5 प्रतिशत की दर से पृथक से 03 वर्ष की गारंटी के लिये

प्रफार्नेस् सिंक्यूरिटी के रूप् में रोंकी जावेगी।

17. निविदा में भाग लेने वाले ठेकेदारों को छ.ग. भवन और अन्य सन्निर्माण कर्मकार (नियोजन एवं सेवा शर्तों का विनियमन) अधिनियम 1996 एवं तद्अंतर्गत निर्धारित नियमों के तहत पंजीयन कराना आवश्यक होगा तथा निर्माण लागत का 1 प्रतिशत उपकर के रूप में प्रत्येक देयक से कटौती की जावेगी।

18. निविदाकार को प्रत्येक निविदा में पंजीयन क्षमता के अंतर्गत वर्तमान में नुगर निगम या अन्य विभागों में किये जा रहे कार्यों का विवरण राशि सहित मूल प्रति में वैध्र शपृथ पत्र राशि रू. 100/- नॉन ज्यूडिशियल स्टॉम्प पेपर पर कंडिका क्र. 04 के

पूथम लिफाफा (अ) में प्रस्तुत करना अनिवार्य होगा।

19. ईंट से संबंधित निर्माण कार्यों में पलाई एश ब्रिक का उपयोग किया जाना अनिवार्य होगा।

20. निविदा प्रपत्र अहस्तांतरणीय होगा एवं सशर्त निविदाओं पर विचार नहीं किया जावेगा।

21. निविदा के संबंध में किसी प्रकार की विवाद होने की स्थिति में आयुक्त के द्वारा अधीनस्थ अधिकारियों का निर्णय अंतिम एवं

22. निविदा प्रपत्र Form-A के क्लॉज नम्बर—11 अनुसार एस्केलेशन देय नहीं होगा।

23. निविदा स्वीकृत करने अथवा अस्वीकृत् करने का अधिकार आयुक्त, नगर पालिक निगम के पास सुरक्षित रहेगा। 24. निविदा खुलने की तिथि में अवकाश होने पर आगामी तिथि (कार्य दिवस) को निविदा संबंधी कार्यवाही मानी जावेगी।

1. अमानत राशि के रूप में एफ.डी.आर. /टी.डी.आर. अथवा नगद जमा रसीद पृथक से लिफाफे में स्वीकार किए जावेंगे आयुक्त, नगर पालिक निगम, कोरबा के नाम पर देय हो।

उपरोक्त तिथियों में किसी भी तिथि को शासकीय/स्थानीय अवकाश होने की स्थिति में अगले कार्य दिवस को निर्धारित तिथि समय एवं स्थान माना जावे।

प्रतिलिपि :--प्रोग्रामर, संचालनालय, नगरीय प्रशासन एवं विकास विभाग, नया रायपूर (छ.ग.) को Uad.cg.gov.in में अपलोड किये जाने हेत् प्रेषित।

(ठेकेदार के हस्ताक्षर)	Exertitive Engineer, Municipality of Furation,
नाम	Municipal Corporación (Chiartisgarh)
पूर्ण पता	
मोबाईल नं	

## OFFICE OF THE MUNICIPAL CORPORATION, KORBA (C.G.)

## **ABSTRACT**

of Work :- Construction of Boundary Wall Near Purvanchal Vikash Samiti Boundary Wall To Press Club Boundary At Bypass Road Under Ward No. 25

Club Boundary At Bypass Road Under Ward No. 25

Pe Sor :- Schedule of Rates Public Works Department [ PWD BUILDING 01-01-2015]

ITEM DESCRIPTION	N	L	В	H/D	Qty	Unit	Rate	
						0	- Nato	Amount
Excavation for all types and sizes of foundations,								
trenches and drains or for any other purpose		-						
including disposal of excavated stuff upto 1.5 m								
				ļ				
In All Types of Soil								
					205.38	Cum	185.00	37995.30
Filling from available excavated stuff (Excluding					l		<del>-</del>	
		1						-
					82.15	Cum	65.00	5339.88
			İ		02.13	""	03.00	3333.00
with a lead upto 50 M. and lift upto 1.5 M.			İ					
		-	<del> </del>					
			l					
in foundation, plinth and at ground level excluding								
cost of form work.		-						
				<b>-</b>	<del></del>			
aggregate 40mm nominal size).				1			İ	
			_	-	<del> </del>			
					24.84	cum	2970.00	73774.80
			1			1		
1:11/2:3 (1 cement : 11/2 coarse sand : 3 graded								
stone aggregate 20mm nominal size).						1 1		
					4.80	cum	4073.00	19550.40
							1075.00	15550.40
Providing and fixing formwork including			_					
bracing etc. complete and including its removal as								
all levels, for:					1			
Foundations, footings, base of columns and plints	-	<del>-</del>						
beam in any shape and size.	1		1			1 1		
		+	+	-	450.00			
Columns Pillars Piers and likes agets	-	-			459.00	sqm	139.00	63801.00
square in shape								
- 1 onapo	-	_	+					
Describing a late to					165.00	sqm	297.00	49005.00
rroviding and laying nominal mix reinforcemen	t					+		.5555.00
using concrete with crushed stone aggregate						1		
level evaluation of all works upto floor five	2		-					
level excluding cost of reinforcement and form	1			1		1		
stone segment : 1½ coarse sand : 3 graded	1					+		
stone aggregate 20mm nominal size).								
					66.04	+	44.65 -	
Extra for laying PCC/RCC of any grade in	1		_	-	00.84	cum	4163.00	278254.92
superstructure above plinth level for every floor of				1				
part thereof in addition to rate for foundation on	<u>.</u>				9.90	cum	97.50	065.35
punth:						""	37.50	965.25
	lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of In All Types of Soil  Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work.  1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size).  Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, base of columns and plinth beam in any shape and size.  Columns, Pillars, Piers and likes- rectangular of square in shape  Providing and laying nominal mix reinforcement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and formwork.  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure above plinth level for every floor of superstructure.	lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of In All Types of Soil  Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work.  1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size).  Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, base of columns and plinth beam in any shape and size.  Columns, Pillars, Piers and likes- rectangular or square in shape  Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and	lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of In All Types of Soil  Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work.  1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size).  Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, base of columns and plinth beam in any shape and size.  Columns, Pillars, Piers and likes- rectangular or square in shape  Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and	lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of In All Types of Soil  Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work.  1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size).  Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, base of columns and plinth beam in any shape and size.  Columns, Pillars, Piers and likes- rectangular or square in shape  Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and the position of part thereof in addition to rate for foundation and the position of part thereof in addition to rate for foundation and the position and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in additio	lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of In All Types of Soil  Filling from available excavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work.  1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size).  Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, base of columns and plinth beam in any shape and size.  Columns, Pillars, Piers and likes- rectangular or square in shape  Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and any part of part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part thereof in addition to rate for foundation and part and part and part and part and part and part and part and part and part and part and part and part and part	lift and lead upto 50m (at least 5m away from the exeavated area), including dressing and leveling of In All Types of Soil  205.38  Filling from available exeavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work.  1:1½:36 (1 cement : 1½ coarse sand : 6 graded stone aggregate 40mm nominal size).  24.84  1:1½:31 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  4.80  Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, base of columns and plinth beam in any shape and size.  459.00  Columns, Pillars, Piers and likes- rectangular or square in shape  Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.  1:1½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  66.84  Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition to rate for fundation or part thereof in addition t	lift and lead upto 50m (at least 5m away from the exeavated area), including dressing and leveling of In All Types of Soil  205.38 Cum  Filling from available exeavated stuff (Excluding rock) in trenches, plinth, sides of foundation etc. in layers not exceeding 20cm in depth consolidating each deposited layer by ramming and watering with a lead upto 50 M. and lift upto 1.5 M.  Providing and laying nominal mix cement concrete with crushed stone aggregate using concrete mixer in foundation, plinth and at ground level excluding cost of form work.  1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40mm nominal size).  24.84 cum  1:11½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  4.80 cum  Providing and fixing formwork including centering, shuttering, strutting, staging, propping bracing etc. complete and including its removal at all levels, for:  Foundations, footings, base of columns and plinth beam in any shape and size.  Columns, Pillars, Piers and likes- rectangular or square in shape  Providing and laying nominal mix reinforcement cement concrete with crushed stone aggregate using concrete mixer in all works upto floor five level excluding cost of reinforcement and form work.  1:11½:3 (1 cement : 1½ coarse sand : 3 graded stone aggregate 20mm nominal size).  Extra for laying PCC/RCC of any grade in superstructure above plinth level for every floor or part thereof in addition to rate for foundation and the part of the property and the property of the property and the property of the property and the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the property of the	lift and lead upto 50m (at least 5m away from the excavated area), including dressing and leveling of In All Types of Soil    205.38

				В	H/D	Qty	Unit	Rate	Amount
	ITEM DESCRIPTION	N	L	В	H/D	- 419	0		
	roviding and placing in position reinforcement					İ			
	for D C C work including straightening, cutting,				l				
- 版	hending binding etc. complete as per diawings				1				
1	including cost of binding wire all complete.					6684.00	kg	54.50	364278.00
	In mo-Mechanically treated bars						<u> </u>		
(	mit with modular fly-ash lime bricks					1			
,	LEAL C. Pricks) confirming to 18:12894-2002 of								
	class designation 40 in foundation and pintit in.						-		
-	Cement Mortar 1:6 (1 cement : 6 coarse sand)								
-						94.52	cum	3263.00	308418.76
10	Extra for brick work in superstructure:					83.40	cum	121.00	10091.40
	Above plinth and upto floor five level.					03.10			
							-		
	Providing and fixing M.S. grill of approved pattern								
	made of M.S. flats or square or round bars welded					300.00	kg	67.50	20250.00
11	to steel frame of windows etc. including applying					300.00	^6	0,100	
	a priming coat welded to frame with all necessary								
	fitting complete including applying a priming of								
	red oxide zinc chromate primer.								
l 12 I	Providing and making 12mm thick cement plaster								
	of mix:					570.00	sqm	91.50	52155.00
	In Cement Mortar 1:6 (1 cement : 6 fine sand)					37000	•		
13	15mm thick cement plaster on the rough side of								
	single or half brick wall of mix:					630.00	sqm	107.00	67410.00
	In Cement Mortar 1:6 (1 cement : 6 fine sand)					030.00	34	20,101	
	Painting exterior surface with SMOOTH exterior								
	emulsion paint manufactured with the cow dung				_				
14	processing to give protective and decorative finish								
	including cleaning washing of surface etc.								
	complete with								
	On new work (Tow or more coats applied @ 1.43					1200.00	sqm	69.00	82800.00
	tr/ 10 sqm over								
	Painting on new work (two or more coats) to give					-			
15	n even shade with:								
1	Satin synthetic enamel paint								
-						27.20	Sqm	55.00	1496.00
	Carriage by mechanical transport upto 5 km lead:								
1	earth					123.23	Cum	111.00	13678.31
	Total Amount As Per SOR Rs.							1449264.02	
$\perp$	Below (-) 0.10 % As Per Annual Senction Rate						1449.26		
$\perp$	Net Amount Rs.						1447814.75		
	Say Amount Rs.						1448000.00		
	Say Amount Rs.							2.70000.00	

Sub Engineer

Municipal Corporation

Korba (C.G.)

Asst. Engineer Municipal Corporation Korba (C.G.)